



ISALNOX IMPRIMACIÓN MUL TIADHERENTE ACQUA
Code : 1010

Version: 15

Revision: 05/12/2022

Previous revision: 09/03/2020

Date of printing: 05/12/2022

According to Article 31 of Regulation (EC) No. 1907/2006 (REACH), a safety data sheet (SDS) must be provided for dangerous substances or mixtures. This product does not meet the classification criteria of Regulation (EC) No. 1272/2008 (CLP). Therefore, this document is outside the scope of Article 31 of REACH and the requirements regarding the content of each section are not applicable.

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1	<p>PRODUCT IDENTIFIER: ISALNOX IMPRIMACIÓN MUL TIADHERENTE ACQUA Code: 1010</p>
1.2	<p>RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST: <u>Intended uses (main technical functions):</u> <input type="checkbox"/> Industrial <input checked="" type="checkbox"/> Professional <input checked="" type="checkbox"/> Consumers Liquid paint. <u>Sectors of use:</u> Consumer uses (SU21), Professional uses (SU22), <u>Uses advised against:</u> None. As there is not classified as dangerous, this product can be used in ways other than the identified uses, but all uses have to be consistent with the safety guidelines provided. <u>Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006:</u> Not restricted.</p>
1.3	<p>DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET: PINTURAS ISAVAL, S.L. c/Velluters, Parcela 2-14- P.I. Casanova - 46394 Ribarroja del Turia (Valencia) ESPAÑA Phone number: +34 96 1640001 - Fax: +34 96 1640002 - www.isaval.es <u>- E-mail address of the person responsible for the Safety Data Sheet:</u> atencionalcliente@isaval.es</p>
1.4	<p>EMERGENCY TELEPHONE NUMBER: +34 96 1640001 8:00-18:00 h.</p>

SECTION 2 : HAZARDS IDENTIFICATION

2.1	<p>CLASSIFICATION OF THE SUBSTANCE OR MIXTURE: This product is not classified as dangerous, in accordance with Regulation (EU) No. 1272/2008~2021/849 (CLP). Note: This product does not require a Safety Data Sheet according to the Regulation (EC) no. 2020/878. When used as recommended or under ordinary conditions, it should not present a physicochemical, health safety or environmental hazard. However, an MSDS can be provided as a courtesy in response to a customer request.</p>
2.2	<p>LABEL ELEMENTS: This product does not require pictograms, in accordance with Regulation (EU) No. 1272/2008~2021/849 (CLP). <u>- Hazard statements:</u> None. <u>- Precautionary statements:</u> P102 Keep out of reach of children. P262 Do not get in eyes, on skin, or on clothing. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. <u>- Supplementary statements:</u> EUH208 Contains 1,2-benzisothiazol-3(2H)-one, 3-aminopropyltriethoxysilane, Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1). May produce an allergic reaction. EUH210 Safety data sheet available on request. <u>- Substances that contribute to classification:</u> None in a percentage equal to or higher than the limit for the name.</p>
2.3	<p>OTHER HAZARDS: Hazards which do not result in classification but which may contribute to the overall hazards of the mixture: <u>- Other physicochemical hazards:</u> No other relevant adverse effects are known. <u>- Other adverse human health effects:</u> Prolonged exposure to vapours may produce transient drowsiness. Prolonged contact may cause skin dryness. <u>- Other negative environmental effects:</u> Does not contain substances that fulfil the PBT/vPvB criteria. <u>Endocrine disrupting properties:</u> This product contains substances with endocrine disrupting properties identified or under evaluation in a concentration of less than 0.1% by weight: 2,2-dibromo-2-cyanoacetamide (DBNPA).</p>



ISALNOX IMPRIMACIÓN MUL TIADHERENTE ACQUA
Code : 1010









Version: 15

Revision: 05/12/2022


Previous revision: 09/03/2020

Date of printing: 05/12/2022

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1	SUBSTANCES: Not applicable (mixture).		
3.2	MIXTURES: This product is a mixture. Chemical description: Solution of Stirenated acrylic resin in aqueous media. HAZARDOUS INGREDIENTS: Substances taking part in a percentage higher than the exemption limit:		
	0,1 < C < 0,2 %  	3-aminopropyltriethoxysilane CAS: 919-30-2, EC: 213-048-4, REACH: 01-2119480479-24 CLP: Danger: Acute Tox. (oral) 4:H302 Skin Corr. 1B:H314 Skin Sens. 1:H317	REACH
	C < 0,025 %   	1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5, EC: 220-120-9 CLP: Danger: Acute Tox. (oral) 4:H302 (ATE=567 mg/kg) Skin Irrit. 2:H315 Eye Dam. 1:H318 Skin Sens. 1:H317 Aquatic Acute 1:H400	CLP00 Skin Sens. 1, H317: C ≥ 0,05 %
	C < 0,001 %   	Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1) CAS: 55965-84-9, EC: 611-341-5 CLP: Danger: Acute Tox. (inh.) 2:H330 Acute Tox. (skin) 2:H310 Acute Tox. (oral) 3:H301 Skin Corr. 1C:H314 Eye Dam. 1:H318 Aquatic Acute 1:H400 (M=100) Aquatic Chronic 1:H410 (M=100) EUH071 Skin Sens. 1A:H317 (Note B)	ATP13 Skin Corr. 1C, H314: C ≥ 0,6 % Skin Irrit. 2, H315: 0,06 % ≤ C < 0,6 % Eye Dam. 1, H318: C ≥ 0,6 % Eye Irrit. 2, H319: 0,06 % ≤ C < 0,6 % Skin Sens. 1A, H317: C ≥ 0,0015 %
	Impurities: Does not contain other components or impurities which will influence the classification of the product.		
	Stabilizers: None.		
	Reference to other sections: For more information, see sections 8, 11, 12 and 16.		
	SUBSTANCES OF VERY HIGH CONCERN (SVHC): List updated by ECHA on 10/06/2022.		
	Substances SVHC subject to authorisation, included in Annex XIV of Regulation (EC) no. 1907/2006: None.		
	Substances SVHC candidate to be included in Annex XIV of Regulation (EC) no. 1907/2006: None.		
	PERSISTENT, BIOACCUMULABLE AND TOXIC PBT, OR VERY PERSISTENT AND VERY BIOACCUMULABLE VPVB SUBSTANCES: Does not contain substances that fulfil the PBT/vPvB criteria.		

SECTION 4: FIRST AID MEASURES

4.1	DESCRIPTION OF FIRST AID MEASURES:  Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.		
	Route of exposure	Symptoms and effects, acute and delayed	Description of first-aid measures
	Inhalation:	It is not expected that symptoms will occur under normal conditions of use.	Should there be any symptoms, transfer the person affected to the open air.
	Skin:	Prolonged contact may cause skin dryness.	Remove contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser.
	Eyes:	Contact with the eyes produces redness and pain.	Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water, holding the eyelids apart. If irritation persists, consult a physician.
	Ingestion:	If swallowed in high doses, may cause gastrointestinal disturbances.	Do not induce vomiting, due to the risk of aspiration. Keep the patient at rest.
4.2	MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED: The main symptoms and effects are indicated in sections 4.1 and 11.1		
4.3	INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED: Notes to physician: Treatment should be directed at the control of symptoms and the clinical condition of the patient.. Antidotes and contraindications: Specific antidote not known.		



ISALNOX IMPRIMACIÓN MUL TIADHERENTE ACQUA
Code : 1010

Version: 15

Revision: 05/12/2022

Previous revision: 09/03/2020

Date of printing: 05/12/2022

SECTION 5: FIREFIGHTING MEASURES

- 5.1 **EXTINGUISHING MEDIA:**
In case of fire in the surroundings, all extinguishing agents are allowed.
- 5.2 **SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:**
As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, Carbon dioxide, nitrogen oxides, sulfur oxides, halogenated compounds, hydrochloric acid. Exposure to combustion or decomposition products may be a hazard to health.
- 5.3 **ADVICE FOR FIREFIGHTERS:**
Special protective equipment:
Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or is not being used, combat fire from a sheltered position or from a safe distance. The standard EN469 provides a basic level of protection for chemical incidents.
Other recommendations:
Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.

SECTION 6: ACCIDENTAL RELEASE MEASURES

- 6.1 **PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:**
Avoid direct contact with this product. Avoid breathing vapours. Keep people without protection in opposition to the wind direction.
- 6.2 **ENVIRONMENTAL PRECAUTIONS:**
Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.
- 6.3 **METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:**
Contain and mop up spills with absorbent materials (sawdust, earth, sand, vermiculite, diatomaceous earth, etc.). Keep the remains in a closed container.
- 6.4 **REFERENCE TO OTHER SECTIONS:**
For contact information in case of emergency, see section 1.
For information on safe handling, see section 7.
For exposure controls and personal protection measures, see section 8.
For waste disposal, follow the recommendations in section 13.

SECTION 7: HANDLING AND STORAGE

- 7.1 **PRECAUTIONS FOR SAFE HANDLING:**
Comply with the existing legislation on health and safety at work.
- General recommendations:
Avoid any type of leakage or escape. Keep the container tightly closed.
- Recommendations for the prevention of fire and explosion risks:
The product is not liable to ignite, deflagrate or explode, and does not sustain the combustion reaction by oxygen from air in the environment in which it is, so it is not included in the scope of Directive 2014/34/EU concerning equipment and protective systems intended for use in potentially explosive atmospheres.
- Recommendations for the prevention of toxicological risks:
Do not eat, drink or smoke while handling. After handling, wash hands with soap and water. For exposure controls and personal protection measures, see section 8.
- Recommendations for the prevention of environmental contamination:
It is not considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6.
- 7.2 **CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:**
Forbid the entry to unauthorized persons. Keep out of reach of children. Keep away from sources of heat. If possible, avoid direct contact with sunlight. In order to avoid leakages, the containers, after use, should be closed carefully and placed in a vertical position. For more information, see section 10.
- Class of store:
According to current legislation.
- Maximum storage period:
12 Months
- Temperature interval:
min:5 °C, max:40 °C (recommended).
- Incompatible materials:
Keep away from oxidizing agents, acids, water, alkalis.
- Type of packaging:
According to current legislation.
- Limit quantity (Seveso III): Directive 2012/18/EU:
Not applicable (product for non industrial use).
- 7.3 **SPECIFIC END USE(S):**
For the use of this product particular recommendations apart from that already indicated are not available.



ISALNOX IMPRIMACIÓN MUL TIADHERENTE ACQUA
Code : 1010

Version: 15

Revision: 05/12/2022

Previous revision: 09/03/2020

Date of printing: 05/12/2022

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1

CONTROL PARAMETERS:

If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

- OCCUPATIONAL EXPOSURE LIMIT VALUES (WEL)

Not established

- BIOLOGICAL LIMIT VALUES:

Not established

- DERIVED NO-EFFECT LEVEL (DNEL):

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from a occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

- DERIVED NO-EFFECT LEVEL, WORKERS:- Systemic effects, acute and chronic:	DNEL Inhalation mg/m3	DNEL Cutaneous mg/kg bw/d	DNEL Oral mg/kg bw/d
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	- (a) - (c)	- (a) - (c)	- (a) - (c)
3-aminopropyltriethoxysilane	59 (a) 59 (c)	8,3 (a) 8,3 (c)	- (a) - (c)
1,2-benzisothiazol-3(2H)-one	- (a) - (c)	- (a) - (c)	- (a) - (c)
- DERIVED NO-EFFECT LEVEL, WORKERS:- Local effects, acute and chronic:	DNEL Inhalation mg/m3	DNEL Cutaneous mg/cm2	DNEL Eyes mg/cm2
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	- (a) - (c)	- (a) - (c)	- (a) - (c)
3-aminopropyltriethoxysilane	- (a) - (c)	- (a) - (c)	- (a) - (c)
1,2-benzisothiazol-3(2H)-one	- (a) - (c)	- (a) - (c)	- (a) - (c)
- DERIVED NO-EFFECT LEVEL, GENERAL POPULATION:- Systemic effects, acute and chronic:	DNEL Inhalation mg/m3	DNEL Cutaneous mg/kg bw/d	DNEL Eyes mg/kg bw/d
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	- (a) - (c)	- (a) - (c)	- (a) - (c)
3-aminopropyltriethoxysilane	17,4 (a) 17,4 (c)	5 (a) 5 (c)	- (a) - (c)
1,2-benzisothiazol-3(2H)-one	- (a) - (c)	- (a) - (c)	- (a) - (c)
- LOCAL EFFECTS, ACUTE AND CHRONIC:- Local effects, acute and chronic:	DNEL Inhalation mg/m3	DNEL Cutaneous mg/cm2	DNEL Eyes mg/cm2
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	- (a) - (c)	- (a) - (c)	- (a) - (c)
3-aminopropyltriethoxysilane	- (a) - (c)	- (a) - (c)	- (a) - (c)
1,2-benzisothiazol-3(2H)-one	- (a) - (c)	- (a) - (c)	- (a) - (c)

(a) - Acute, short-term exposure, (c) - Chronic, long-term or repeated exposure.

(-) - DNEL not available (without data of registration REACH).

- PREDICTED NO-EFFECT CONCENTRATION (PNEC):

- PREDICTED NO-EFFECT CONCENTRATION, AQUATIC ORGANISMS:- Fresh water, marine water and intermittent release:	PNEC Fresh water mg/l	PNEC Marine mg/l	PNEC Intermittent mg/l
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	-	-	-
3-aminopropyltriethoxysilane	0.33	0.033	3.3
1,2-benzisothiazol-3(2H)-one	-	-	-
- WASTEWATER TREATMENT PLANTS (STP) AND SEDIMENTS IN FRESH- AND MARINE WATER:	PNEC STP mg/l	PNEC Sediments mg/kg dw/d	PNEC Sediments mg/kg dw/d
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	-	-	-
3-aminopropyltriethoxysilane	13	1.2	0.12
1,2-benzisothiazol-3(2H)-one	-	-	-



ISALNOX IMPRIMACIÓN MUL TIADHERENTE ACQUA
Code : 1010

Version: 15

Revision: 05/12/2022

Previous revision: 09/03/2020

Date of printing: 05/12/2022

- PREDICTED NO-EFFECT CONCENTRATION, TERRESTRIAL ORGANISMS:- Air, soil and effects for predators and humans:	PNEC Air mg/m ³	PNEC Soil mg/kg dw/d	PNEC Oral mg/kg dw/d
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	-	-	-
3-aminopropyltriethoxysilane	-	0.05	n/b
1,2-benzisothiazol-3(2H)-one	-	-	-

(-) - PNEC not available (without data of registration REACH).
n/b - PNEC not derived (not bioaccumulative potential).

8.2

EXPOSURE CONTROLS:
ENGINEERING MEASURES:



Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.

- Protection of respiratory system:

Avoid the inhalation of vapours.

- Protection of eyes and face:

It is recommended to install water taps or sources with clean water close to the working area.

- Protection of hands and skin:

It is recommended to install water taps or sources with clean water close to the working area. Barrier creams may help to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.

OCCUPATIONAL EXPOSURE CONTROLS: REGULATION (EU) NO. 2016/425:

As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding marking. For more information on personal protective equipment (storage, use, cleaning, maintenance, type and characteristics of the PPE, protection class, marking, category, CEN norm, etc.), you should consult the informative brochures provided by the manufacturers of PPE.

Mask: 	✓ A-type filter mask (brown) for gases and vapours of organic compounds with a boiling point higher than 65°C (EN14387). Class 1: low capacity up to 1000 ppm, Class 2: medium capacity up to 5000 ppm, Class 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers.
Safety goggles: 	✓ Safety goggles designed to protect against liquid splashes, with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.
Face shield:	No.
Gloves: 	✓ Gloves resistant against chemicals (EN374). When repeated or prolonged contact with the product is expected, gloves of protection level 5 or higher should be used, with a breakthrough time of >240 min. When short contact with the product is expected, use gloves with a protection level 2 or higher should be used, with a breakthrough time >30 min. The breakthrough time of the selected glove material should be in accordance with the pretended period of use. There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, the instructions/specifications provided by the glove supplier should be taken into account. Use the proper technique of removing gloves (without touching glove's outer surface) to avoid contact of the product with the skin. The gloves should be immediately replaced when any sign of degradation is noted.
Boots:	No.
Apron:	No.
Clothing:	No.

- Thermal hazards:

Not applicable (the product is handled at room temperature).

ENVIRONMENTAL EXPOSURE CONTROLS:

Avoid any spillage in the environment. Avoid any release into the atmosphere.

- Spills on the soil:

Prevent contamination of soil.

- Spills in water:

Do not allow to escape into drains, sewers or water courses.

-Water Management Act:



ISALNOX IMPRIMACIÓN MUL TIADHERENTE ACQUA
Code : 1010

Version: 15

Revision: 05/12/2022

Previous revision: 09/03/2020

Date of printing: 05/12/2022

This product does not contain any substance included in the list of priority substances in the field of water policy under Directive 2000/60/EC~2013/39/EU.

- Emissions to the atmosphere:

Because of volatility, emissions to the atmosphere while handling and use may result. Avoid any release into the atmosphere.

VOC (product ready for use*):

It is applicable the Directive 2004/42/EC, on the limitation of emissions of volatile compounds due to the use of organic solvents: PAINTS AND VARNISHES (defined in the Directive 2004/42/EC, Annex I.1): Emission subcategory i) One-pack performance coating, water-borne. VOC (product ready for use*): (ISALNOX IMPRIMACIÓN MUL Cod. 1010 = 100 in volume): 31,9 (VOC max.140 g/l* starting from 01.01.2010)

VOC (industrial installations):

If this product is used in an industrial installation, it must be verified if it is applicable the Directive 2010/75/CE (DL.127/2013, on the limitation of emissions of volatile compounds due to the use of organic solvents in certain activities and installations:Solvents: 3,10 % Weight, VOC (supply): 2,54 % Weight, VOC: 1,46 % C (expressed as carbon), Molecular weight (average): 147,20 , Number C atoms (average): 7,03

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:

Appearance

Physical state:	Liquid
Colour:	White
Odour:	Characteristic
Odour threshold:	Not available (mixture).

Change of state

Melting point:	Not available (mixture).
Boiling interval:	100* - 229* °C at 760 mmHg

- Flammability:

Flash point	Not flammable
Lower/upper flammability or explosive limits:	Not available
Autoignition temperature:	Not applicable (do not sustain combustion).

Stability

Decomposition temperature:	Not available (technical impossibility to obtain the data).
----------------------------	---

pH-value

pH:	8,5 at 20°C
-----	-------------

- Viscosity:

Dynamic viscosity:	80,00 Poise at 20°C
--------------------	---------------------

- Solubility(ies):

Solubility in water	1500 g/l at 20°C
Liposolubility:	Not applicable (inorganic product).
Partition coefficient: n-octanol/water:	Not applicable (mixture).

- Volatility:

Vapour pressure:	17,4987* mmHg at 20°C
Vapour pressure:	12,0879* kPa at 50°C
Evaporation rate:	Not available (lack of data).

Density

Relative density:	1,257* at 20/4°C	Relative water
Relative vapour density:	Not available.	

Particle characteristics

Particle size:	Not applicable.
----------------	-----------------

- Explosive properties:

Not available.

- Oxidizing properties:

Not classified as oxidizing product.

*Estimated values based on the substances composing the mixture.

9.2 OTHER INFORMATION:

Information regarding physical hazard classes

No additional information available.

Other security features:

VOC (supply):	2,5 % Weight	
VOC (supply):	31,9 g/l	
Nonvolatile:	51,21 * % Weight	1h. 60°C

The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the corresponding technical data sheet. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.



ISALNOX IMPRIMACIÓN MUL TIADHERENTE ACQUA
Code : 1010

Version: 15

Revision: 05/12/2022

Previous revision: 09/03/2020

Date of printing: 05/12/2022

SECTION 10: STABILITY AND REACTIVITY

10.1	<p>REACTIVITY:</p> <p>- Corrosivity to metals: It is not corrosive to metals.</p> <p>- Pyrophorical properties: It is not pyrophoric.</p>
10.2	<p>CHEMICAL STABILITY: Stable under recommended storage and handling conditions.</p>
10.3	<p>POSSIBILITY OF HAZARDOUS REACTIONS: Possible dangerous reaction with oxidizing agents, acids, water, alkalis.</p>
10.4	<p>CONDITIONS TO AVOID:</p> <p>- Heat: Keep away from heat.</p> <p>- Light: If possible, avoid direct contact with sunlight.</p> <p>- Air: The product is not affected by exposure to air, but should not be left the containers open.</p> <p>- Pressure: Not relevant.</p> <p>- Shock: The product is not sensitive to shocks, but as a recommendation of a general nature should be avoided bumps and rough handling to avoid dents and breakage of packaging, especially when the product is handled in large quantities, and during loading and download operations.</p>
10.5	<p>INCOMPATIBLE MATERIALS: Keep away from oxidizing agents, acids, water, alkalis.</p>
10.6	<p>HAZARDOUS DECOMPOSITION PRODUCTS: As consequence of thermal decomposition, hazardous products may be produced: nitrogen oxides, sulfur oxides, hydrochloric acid, halogenated compounds.</p>

SECTION 11: TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2021/849 (CLP).																																																			
11.1	<p>INFORMATION ON HAZARD CLASSES AS DEFINED IN REGULATION (EC) NO 1272/2008 :</p> <p>ACUTE TOXICITY:</p> <table border="1"> <thead> <tr> <th>Dose and lethal concentrations for individual ingredients:</th> <th>DL50 (OECD401) mg/kg bw Oral</th> <th>DL50 (OECD402) mg/kg bw Cutaneous</th> <th>CL50 (OECD403) mg/m³·4h Inhalation</th> </tr> </thead> <tbody> <tr> <td>Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)</td> <td>74,9 Rat</td> <td>140 Rat</td> <td>> 1230 Rat</td> </tr> <tr> <td>3-aminopropyltriethoxysilane</td> <td>1780 Rat</td> <td>4000 Rabbit</td> <td>> 7350 Rat</td> </tr> <tr> <td>1,2-benzisothiazol-3(2H)-one</td> <td>1020 Rat</td> <td>> 2000 Rat</td> <td>> 2050 Rat</td> </tr> <tr> <th>Estimates of acute toxicity (ATE) for individual ingredients:</th> <th>ATE mg/kg bw Oral</th> <th>ATE mg/kg bw Cutaneous</th> <th>ATE mg/m³·4h Inhalation</th> </tr> <tr> <td>Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)</td> <td>74,9</td> <td>140</td> <td>*> 50</td> </tr> <tr> <td>3-aminopropyltriethoxysilane</td> <td>1780</td> <td>-</td> <td>-</td> </tr> <tr> <td>1,2-benzisothiazol-3(2H)-one</td> <td>*567</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>(*) - Point estimates of acute toxicity corresponding to the classification category (see GHS/CLP Table 3.1.2). These values are designed to be used in the calculation of the ATE for classification of a mixture based on its components and do not represent test results. (-) - The components that are assumed to have no acute toxicity at the upper threshold of category 4 for the corresponding exposure route are ignored.</p> <p>- No observed adverse effect level Not available</p> <p>- Lowest observed adverse effect level Not available</p> <p>INFORMATION ON LIKELY ROUTES OF EXPOSURE: ACUTE TOXICITY:</p> <table border="1"> <thead> <tr> <th>Routes of exposure</th> <th>Acute toxicity</th> <th>Cat.</th> <th>Main effects, acute and/or delayed</th> <th>Criteria</th> </tr> </thead> <tbody> <tr> <td>Inhalation:</td> <td>ATE > 20000 mg/m³</td> <td>-</td> <td>Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).</td> <td>GHS/CLP 3.1.3.6.</td> </tr> <tr> <td>Not classified</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>				Dose and lethal concentrations for individual ingredients:	DL50 (OECD401) mg/kg bw Oral	DL50 (OECD402) mg/kg bw Cutaneous	CL50 (OECD403) mg/m ³ ·4h Inhalation	Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	74,9 Rat	140 Rat	> 1230 Rat	3-aminopropyltriethoxysilane	1780 Rat	4000 Rabbit	> 7350 Rat	1,2-benzisothiazol-3(2H)-one	1020 Rat	> 2000 Rat	> 2050 Rat	Estimates of acute toxicity (ATE) for individual ingredients:	ATE mg/kg bw Oral	ATE mg/kg bw Cutaneous	ATE mg/m ³ ·4h Inhalation	Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	74,9	140	*> 50	3-aminopropyltriethoxysilane	1780	-	-	1,2-benzisothiazol-3(2H)-one	*567	-	-	Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed	Criteria	Inhalation:	ATE > 20000 mg/m ³	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.	Not classified				
Dose and lethal concentrations for individual ingredients:	DL50 (OECD401) mg/kg bw Oral	DL50 (OECD402) mg/kg bw Cutaneous	CL50 (OECD403) mg/m ³ ·4h Inhalation																																																
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	74,9 Rat	140 Rat	> 1230 Rat																																																
3-aminopropyltriethoxysilane	1780 Rat	4000 Rabbit	> 7350 Rat																																																
1,2-benzisothiazol-3(2H)-one	1020 Rat	> 2000 Rat	> 2050 Rat																																																
Estimates of acute toxicity (ATE) for individual ingredients:	ATE mg/kg bw Oral	ATE mg/kg bw Cutaneous	ATE mg/m ³ ·4h Inhalation																																																
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	74,9	140	*> 50																																																
3-aminopropyltriethoxysilane	1780	-	-																																																
1,2-benzisothiazol-3(2H)-one	*567	-	-																																																
Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed	Criteria																																															
Inhalation:	ATE > 20000 mg/m ³	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.																																															
Not classified																																																			



ISALNOX IMPRIMACIÓN MUL TIADHERENTE ACQUA
Code : 1010

Version: 15

Revision: 05/12/2022

Previous revision: 09/03/2020

Date of printing: 05/12/2022

Skin: Not classified	ATE > 5000 mg/kg bw	-	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
Eyes: Not classified	Not available.	-	Not classified as a product with acute toxicity by eye contact (lack of data).	GHS/CLP 1.2.5.
Ingestion: Not classified	ATE > 5000 mg/kg bw	-	Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.

GHS/CLP 3.1.3.6: Classification of mixtures based on ingredients of the mixture (additivity formula).

CORROSION / IRRITATION / SENSITISATION :

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Respiratory corrosion/irritation: Not classified	-	-	Not classified as a product corrosive or irritant by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 1.2.6. 3.8.3.4.
- Skin corrosion/irritation: Not classified	-	-	Not classified as a product corrosive or irritant in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.2.3.3.
- Serious eye damage/irritation: Not classified	-	-	Not classified as a product corrosive or irritant in contact with eyes (based on available data, the classification criteria are not met).	GHS/CLP 3.3.3.3.
- Respiratory sensitisation: Not classified	-	-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.
- Skin sensitisation: Not classified	-	-	Not classified as a product sensitising by skin contact (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.

GHS/CLP 3.2.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.3.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.4.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

- ASPIRATION HAZARD:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Aspiration hazard: Not classified	-	-	Not classified as a product hazardous by aspiration (based on available data, the classification criteria are not met).	GHS/CLP 3.10.3.3.

GHS/CLP 3.10.3.3: Classification of the mixture when data are available for all components or only for some components.

SPECIFIC TARGET ORGANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Not classified as a dangerous product for target organs.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

CMR EFFECTS:

- Carcinogenic effects:

It is not considered as a carcinogenic product.

- Genotoxicity:

It is not considered as a mutagenic product.

- Toxicity for reproduction:

Does not harm fertility. Does not harm the unborn child.

- Effects via lactation:

Not classified as a hazardous product for children breast-fed.

DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:

Routes of exposure

May be absorbed by inhalation of vapour, through the skin and by ingestion.

- Short-term exposure:

May irritate the eyes and skin. Causes burns to the skin or eyes by direct contact or to the digestive tract if swallowed. The mists of fine particles are skin and respiratory tract irritants. Causes serious eye damage. Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness.



ISALNOX IMPRIMACIÓN MUL TIADHERENTE ACQUA

Code : 1010

Version: 15

Revision: 05/12/2022

Previous revision: 09/03/2020

Date of printing: 05/12/2022

- Long-term or repeated exposure:

Repeated or prolonged contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

INTERACTIVE EFFECTS:

Not available.

INFORMATION ABOUT TOXICOCINETICS, METABOLISM AND DISTRIBUTION:- Dermal absorption:

Not available.

- Basic toxicokinetics:

Not available.

ADDITIONAL INFORMATION:

Not available.

11.2 INFORMATION ON OTHER HAZARDS:Endocrine disrupting properties:

This product contains substances with endocrine disrupting properties identified or under evaluation in a concentration of less than 0.1% by weight: 2,2-dibromo-2-cyanoacetamide (DBNPA).

Other information:

No additional information available.

SECTION 12: ECOLOGICAL INFORMATION

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2021/849 (CLP).

12.1 TOXICITY:

- Acute toxicity in aquatic environment for individual ingredients	CL50 (OECD 203) mg/l · 96hours	CE50 (OECD 202) mg/l · 48hours	CE50 (OECD 201) mg/l · 72hours
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	0.19 - Fishes	0.16 - Daphniae	0.037 - Algae
3-aminopropyltriethoxysilane	934 - Fishes	331 - Daphniae	603 - Algae
1,2-benzisothiazol-3(2H)-one	1.2 - Fishes	0.85 - Daphniae	0.37 - Algae

- No observed effect concentration	NOEC (OECD 210) mg/l · 28 days	NOEC (OECD 211) mg/l · 21 days	NOEC (OECD 201) mg/l · 72 hours
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	0.02 - Fishes	0.011 - Daphniae	0.004 - Algae

- Lowest observed effect concentration

Not available

ASSESSMENT OF AQUATIC TOXICITY:

Aquatic toxicity	Cat.	Main hazards to the aquatic environment	Criteria
- Acute aquatic toxicity: Not classified	-	Not classified as a hazardous product with acute toxicity to aquatic life (based on available data, the classification criteria are not met).	GHS/CLP 4.1.3.5.5.3.
- Chronic aquatic toxicity:	-	Not classified as a dangerous product with chronic toxicity to aquatic life with long lasting effects (based on available data, the classification criteria are not met).	GHS/CLP 4.1.3.5.5.4.

CLP 4.1.3.5.5.3: Classification of a mixture for acute hazards, based on summation of classified components.

CLP 4.1.3.5.5.4: Classification of a mixture for chronic (long term) hazards, based on summation of classified components.

12.2 PERSISTENCE AND DEGRADABILITY:- Biodegradability:

Not available.

Aerobic biodegradation for individual ingredients	COD mgO2/g	%DBO/DQO 5 days 14 days 28 days	Biodegradabilidad
Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)		- - 55	Not easy
3-aminopropyltriethoxysilane		- - 67	Not easy



ISALNOX IMPRIMACIÓN MUL TIADHERENTE ACQUA
Code : 1010

Version: 15

Revision: 05/12/2022

Previous revision: 09/03/2020

Date of printing: 05/12/2022

	1,2-benzisothiazol-3(2H)-one		-	-	-	Not easy
	Note: Biodegradability data correspond to an average of data from various bibliographic sources.					
	<u>- Hydrolysis:</u> Not available.					
	<u>- Photodegradability:</u> Not available.					
12.3	<u>BIOACCUMULATIVE POTENTIAL:</u> Not available.					
	Bioaccumulation for individual ingredients	logPow		BCF L/kg		Potential
	Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	0.75		3.2 (calculated)		Unlikely, low
	3-aminopropyltriethoxysilane	1.7		3.2 (calculated)		Unlikely, low
	1,2-benzisothiazol-3(2H)-one	0.64		3.2 (calculated)		Unlikely, low
12.4	<u>MOBILITY IN SOIL:</u> Not available					
	Mobility for individual ingredients	log P _{oc}		Constant of Henry Pa·m ³ /mol 20°C		Potential
	Reaction mass of 5-chloro-2-methyl-2H-isothiazolin-3-one [EC 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	0,45				Unlikely, low
	3-aminopropyltriethoxysilane	1,07				Unlikely, low
	1,2-benzisothiazol-3(2H)-one	1,05				Unlikely, low
12.5	<u>RESULTS OF PBT AND VPVB ASSESMENT:(Annex XIII of Regulation (EC) no. 1907/2006):</u> Does not contain substances that fulfil the PBT/vPvB criteria.					
12.6	<u>ENDOCRINE DISRUPTING PROPERTIES:</u> This product contains substances with endocrine disrupting properties identified or under evaluation in a concentration of less than 0.1% by weight:2,2-dibromo-2-cyanoacetamide (DBNPA).					
12.7	<u>OTHER ADVERSE EFFECTS:</u> <u>- Ozone depletion potential:</u> Not available. <u>- Photochemical ozone creation potential:</u> Not available. <u>- Earth global warming potential:</u> Not available.					

SECTION 13: DISPOSAL CONSIDERATIONS

- 13.1 WASTE TREATMENT METHODS:Directive 2008/98/EC~Regulation (EU) no. 1357/2014:
Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose at an authorised waste collection point. Waste should be handled and disposed in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.
Disposal of empty containers:Directive 94/62/EC~2015/720/EU, Decision 2000/532/EC~2014/955/EU:
Emptied containers and packaging should be disposed in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of emptying of the same, being the holder of the residue responsible for their classification, in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in itself.
Procedures for neutralising or destroying the product:
Authorised landfill in accordance with local regulations.



ISALNOX IMPRIMACIÓN MUL TIADHERENTE ACQUA
Code : 1010

Version: 15

Revision: 05/12/2022

Previous revision: 09/03/2020

Date of printing: 05/12/2022

SECTION 14: TRANSPORT INFORMATION

14.1	<u>UN NUMBER OR ID NUMBER:</u> Not applicable
14.2	<u>UN PROPER SHIPPING NAME:</u> Not applicable
14.3	<u>TRANSPORT HAZARD CLASS(ES):</u> <u>Transport by road (ADR 2021) and</u> <u>Transport by rail (RID 2021):</u> No reglamented <u>Transport by sea (IMDG 39-18):</u> No reglamented <u>Transport by air (ICAO/IATA 2021):</u> No reglamented <u>Transport by inland waterways (ADN):</u> No reglamented
14.4	<u>PACKING GROUP:</u> No reglamented
14.5	<u>ENVIRONMENTAL HAZARDS:</u> Not applicable (not classified as hazardous for the environment).
14.6	<u>SPECIAL PRECAUTIONS FOR USER:</u> Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are upright and secure. Ensure adequate ventilation.
14.7	<u>MARITIME TRANSPORT IN BULK ACCORDING TO IMO INSTRUMENTS:</u> Not applicable.

SECTION 15: REGULATORY INFORMATION

15.1	<u>SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE:</u> The regulations applicable to this product generally are listed throughout this Safety Data Sheet. <u>Restrictions on manufacture, placing on market and use:</u> See section 1.2 <u>Tactile warning of danger:</u> Not applicable (the classification criteria are not met). <u>Child safety protection:</u> Not applicable (the classification criteria are not met). <u>VOC information on the label:</u> Contains VOC max. 31,9 for the product ready for use - The limit value 2004/42/EC-IIA cat. i) One-pack performance coating, water-borne. is VOC max. 140 g/l (2010) <u>OTHER REGULATIONS:</u> <u>Control of the risks inherent in major accidents (Seveso III):</u> See section 7.2 <u>Other local legislations:</u> The receiver should verify the possible existence of local regulations applicable to the chemical.
15.2	<u>CHEMICAL SAFETY ASSESSMENT:</u> A chemical safety assessment has not been carried out for this mixture.



ISALNOX IMPRIMACIÓN MUL TIADHERENTE ACQUA
Code : 1010

Version: 15

Revision: 05/12/2022

Previous revision: 09/03/2020

Date of printing: 05/12/2022

SECTION 16 : OTHER INFORMATION

16.1 TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:Hazard statements according the Regulation (EU) No. 1272/2008~2021/849 (CLP), Annex III:

H301 Toxic if swallowed. H302 Harmful if swallowed. H310 Fatal in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H330 Fatal if inhaled. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. EUH071 Corrosive to the respiratory tract.

Notes related to the identification, classification and labelling of the substances or mixtures:

Note B : Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

EVALUATION OF THE INFORMATION ON THE DANGER OF MIXTURES:

See sections 9.1, 11.1 and 12.1.

ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of Safety Data Sheets and labelling of products as well.

MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:

- European Chemicals Agency: ECHA, <http://echa.europa.eu/>
- Access to European Union Law, <http://eur-lex.europa.eu/>
- Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970).
- Threshold Limit Values, (AGCIH, 2017).
- European agreement on the international carriage of dangerous goods by road, (ADR 2021).
- International Maritime Dangerous Goods Code IMDG including Amendment 39-18 (IMO, 2018).

ABBREVIATIONS AND ACRONYMS:

List of abbreviations and acronyms that can be used (but not necessarily used) in this Safety Data Sheet:

- REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- CLP: European regularion on Classificatin, Labelling amd Packaging of substances and chemical mixtures.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- ELINCS: European List of Notified Chemical Substances.
- CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials.
- SVHC: Substances of Very High Concern.
- PBT: Persistent, bioaccumulable and toxic substances.
- vPvB: Very persistent and very bioaccumulable substances.
- VOC: Volatile Organic Compounds.
- DNEL: Derived No-Effect Level (REACH).
- PNEC: Predicted No-Effect Concentration (REACH).
- LC50: Lethal concentration, 50 percent.
- LD50: Lethal dose, 50 percent.
- UN: United Nations Organisation.
- ADR: European agreement concerning the international carriage of dangeous goods by road.
- RID: Regulations concerning the international transport of dangeous goods by rail.
- IMDG: International Maritime code for Dangerous Goods.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.

SAFETY DATA SHEET REGULATIONS:

Safety Data Sheet in accordance with Article 31 of Regulation (EC) No. 1907/2006 (REACH) and Annex of Regulation (EU) No. 2020/878.

HISTORIC: REVISION:

Version: 14 09/03/2020

Version: 15 05/12/2022

Changes since previous Safety Data Sheet:

Changes that have been introduced with respect to the previous version due to the structural and content adaptation of the Safety Data Sheet to Regulation (EU) No. 2020/878: All sections.

The information of this Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users" working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product"s properties.