



EPOXI SELLADOR INCOLORO 40% SOLIDOS  
Code : 12113




Version: 6

Revision: 28/02/2023













Previous revision: 19/12/2022


Date of printing: 28/02/2023

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1	<b>PRODUCT IDENTIFIER:</b> EPOXI SELLADOR INCOLORO 40% SOLIDOS Code : 12113 UFI: NYH2-R10C-N005-E52W
1.2	<b>RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST:</b> <u>Intended uses (main technical functions):</u> <input checked="" type="checkbox"/> Industrial <input checked="" type="checkbox"/> Professional <input type="checkbox"/> Consumers Liquid paint. <u>Sectors of use:</u> # Professional uses (SU22), Industrial use (SU0-3), <u>Types of PCN use:</u> Paints/coatings - Decorative. <u>Uses advised against:</u> This product is not recommended for any use or sector of use (industrial, professional or consumer) other than those previously listed as "Intended or identified uses". <u>Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006:</u> Not restricted.
1.3	<b>DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:</b> PINTURAS ISAVAL, S.L. c/Velluters, Parcela 2-14- P.I. Casanova - 46394 Ribarroja del Turia (Valencia) ESPAÑA Phone number: +34 96 1640001 - Fax: +34 96 1640002 - www.isaval.es <u>- E-mail address of the person responsible for the Safety Data Sheet:</u> atencionalcliente@isaval.es
1.4	<b>EMERGENCY TELEPHONE NUMBER:</b> +34 96 1640001 8:00-18:00 h.  National Poisons Information Service (NPIS) - In England, Wales or Scotland: dial 111 - In N Ireland: contact your local GP or pharmacist during normal hours.

## SECTION 2 : HAZARDS IDENTIFICATION

2.1	<b>CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:</b> Classification of mixtures is carried out in accordance with the following principles: a) when data (tests) for the classification of mixtures are available, generally is carried out based on these data, b) in the absence of data (tests) for mixtures are generally used interpolation or extrapolation methods of assessing the risk, using the available data for mixtures similarly classified, and c) in the absence of tests and information which would allow to apply interpolation or extrapolation techniques, methods are used to classify risk assessment based on the data of the individual components in the mixture. The classification as corrosive has been carried out having in mind the criteria of corrosivity by pH. <u>Classification in accordance with Regulation (EU) No. 1272/2008~2021/849 (CLP):</u> DANGER:Flam. Liq. 2:H225 Skin Irrit. 2:H315 Eye Irrit. 2:H319 Skin Sens. 1:H317 STOT SE (irrit.) 3:H335 STOT SE (narcosis) 3:H336 STOT RE 2:H373 Aquatic Chronic 2:H411																																												
	<table border="1"> <thead> <tr> <th>Danger class</th> <th>Classification of the mixture</th> <th>Cat.</th> <th>Routes of exposure</th> <th>Target organs</th> <th>Effects</th> </tr> </thead> <tbody> <tr> <td>Physicochemical: </td> <td>Flam. Liq. 2:H225 c)</td> <td>Cat.2</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td rowspan="5">Human health:  </td> <td>Skin Irrit. 2:H315 c)</td> <td>Cat.2</td> <td>Skin</td> <td>Skin</td> <td>Irritation</td> </tr> <tr> <td>Eye Irrit. 2:H319 c)</td> <td>Cat.2</td> <td>Eyes</td> <td>Eyes</td> <td>Irritation</td> </tr> <tr> <td>Skin Sens. 1:H317 c)</td> <td>Cat.1</td> <td>Skin</td> <td>Skin</td> <td>Allergy</td> </tr> <tr> <td>STOT SE (irrit.) 3:H335 c)</td> <td>Cat.3</td> <td>Inhalation</td> <td>Respiratory tract</td> <td>Irritation</td> </tr> <tr> <td>STOT SE (narcosis) 3:H336 c)</td> <td>Cat.3</td> <td>Inhalation</td> <td>CNS</td> <td>Narcosis</td> </tr> <tr> <td>Environment: </td> <td>Aquatic Chronic 2:H411 c)</td> <td>Cat.2</td> <td>Inhalation</td> <td>Systemic</td> <td>Damage</td> </tr> </tbody> </table>	Danger class	Classification of the mixture	Cat.	Routes of exposure	Target organs	Effects	Physicochemical: 	Flam. Liq. 2:H225 c)	Cat.2	-	-	-	Human health:  	Skin Irrit. 2:H315 c)	Cat.2	Skin	Skin	Irritation	Eye Irrit. 2:H319 c)	Cat.2	Eyes	Eyes	Irritation	Skin Sens. 1:H317 c)	Cat.1	Skin	Skin	Allergy	STOT SE (irrit.) 3:H335 c)	Cat.3	Inhalation	Respiratory tract	Irritation	STOT SE (narcosis) 3:H336 c)	Cat.3	Inhalation	CNS	Narcosis	Environment: 	Aquatic Chronic 2:H411 c)	Cat.2	Inhalation	Systemic	Damage
Danger class	Classification of the mixture	Cat.	Routes of exposure	Target organs	Effects																																								
Physicochemical: 	Flam. Liq. 2:H225 c)	Cat.2	-	-	-																																								
Human health:  	Skin Irrit. 2:H315 c)	Cat.2	Skin	Skin	Irritation																																								
	Eye Irrit. 2:H319 c)	Cat.2	Eyes	Eyes	Irritation																																								
	Skin Sens. 1:H317 c)	Cat.1	Skin	Skin	Allergy																																								
	STOT SE (irrit.) 3:H335 c)	Cat.3	Inhalation	Respiratory tract	Irritation																																								
	STOT SE (narcosis) 3:H336 c)	Cat.3	Inhalation	CNS	Narcosis																																								
Environment: 	Aquatic Chronic 2:H411 c)	Cat.2	Inhalation	Systemic	Damage																																								
	Full text of hazard statements mentioned is indicated in section 16. Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.																																												

2.2	<b>#LABEL ELEMENTS:</b>  This product is labelled with the signal word DANGER in accordance with Regulation (EU) No. 1272/2008~2021/849 (CLP)
-----	---

- Hazard statements:

H225	Highly flammable liquid and vapour.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

#- Precautionary statements:



EPOXI SELLADOR INCOLORO 40% SOLIDOS  
Code : 12113



Version: 6

Revision: 28/02/2023

Previous revision: 19/12/2022

Date of printing: 28/02/2023

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take action to prevent static discharges.
P337+P313	If eye irritation persists: Get medical advice/attention.
P280	Wear protective gloves, clothing and eye protection. In case of inadequate ventilation wear respiratory protection.
P363	Wash contaminated clothing before reuse.
P303+P361+P353- P352-P312	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Wash with plenty of water and soap.. Call a POISON CENTER or doctor if you feel unwell.
P304+P340-P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.
P305+P351+P338- P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
P273-P391-P501	Avoid release to the environment. Collect spillage. Dispose of contents/container in accordance with local regulations.
<u>- Supplementary statements:</u>	
EUH205	Contains epoxy constituents. May produce an allergic reaction.

- Substances that contribute to classification:

Epoxy resin (average molecular weight &lt;700)

Xylene (mixture of isomers)

Ethylmethylketone

2.3

OTHER HAZARDS:

Hazards which do not result in classification but which may contribute to the overall hazards of the mixture:

- Other physicochemical hazards:

Vapours may form with air a mixture potentially flammable or explosive.

- Other adverse human health effects:

No other relevant adverse effects are known.

- Other negative environmental effects:

Does not contain substances that fulfil the PBT/vPvB criteria.

Endocrine disrupting properties:

This product does not contain substances with endocrine disrupting properties identified or under evaluation.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

3.1

SUBSTANCES:

Not applicable (mixture).

3.2

MIXTURES:

This product is a mixture.

Chemical description:

Solution of resins

HAZARDOUS INGREDIENTS:

Substances taking part in a percentage higher than the exemption limit:

40 < C < 50 %		Epoxy resin (average molecular weight <700) CAS: 25068-38-6, EC: 500-033-5, REACH: 01-2119456619-26 CLP: Warning: Skin Irrit. 2:H315   Eye Irrit. 2:H319   Skin Sens. 1:H317   Aquatic Chronic 2:H411	REACH / CLP00	Skin Irrit. 2, H315: C ≥ 5 % Eye Irrit. 2, H319: C ≥ 5 %
30 < C < 40 %		Xylene (mixture of isomers) CAS: 1330-20-7, EC: 215-535-7, REACH: 01-2119488216-32 CLP: Danger: Flam. Liq. 3:H226   Acute Tox. (inh.) 4:H332   Acute Tox. (skin) 4:H312   Skin Irrit. 2:H315   Eye Irrit. 2:H319   STOT SE (irrit.) 3:H335   STOT RE 2:H373   Asp. Tox. 1:H304	REACH	
15 < C ≤ 20 %		Ethylmethylketone CAS: 78-93-3, EC: 201-159-0, REACH: 01-2119457290-43 CLP: Danger: Flam. Liq. 2:H225   Eye Irrit. 2:H319   STOT SE (narcosis) 3:H336   EUH066	REACH / ATP01	

Impurities:

Does not contain other components or impurities which will influence the classification of the product.

Stabilizers:

None.

Reference to other sections:

For more information on hazardous ingredients, see sections 8, 11, 12 and 16.

SUBSTANCES OF VERY HIGH CONCERN (SVHC):

List updated by ECHA on 10/06/2022.

Substances SVHC subject to authorisation, included in Annex XIV of Regulation (EC) no. 1907/2006:

None.

Substances SVHC candidate to be included in Annex XIV of Regulation (EC) no. 1907/2006:

None.

PERSISTENT, BIOACCUMULABLE AND TOXIC PBT, OR VERY PERSISTENT AND VERY BIOACCUMULABLE VPVB SUBSTANCES:



EPOXI SELLADOR INCOLORO 40% SOLIDOS  
Code : 12113



Version: 6

Revision: 28/02/2023

Previous revision: 19/12/2022

Date of printing: 28/02/2023

Does not contain substances that fulfil the PBT/vPvB criteria.

**SECTION 4: FIRST AID MEASURES**

4.1	<b>DESCRIPTION OF FIRST AID MEASURES:</b>	
	Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Lifeguards should pay attention to self-protection and use the recommended protective equipment if there is a possibility of exposure. Wear protective gloves when administering first aid.	
	Route of exposure	Symptoms and effects, acute and delayed
	Inhalation:	Inhalation of solvent vapours may produce headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness. Inhalation produces irritation to mucus, coughing and breathlessness.
	Skin:	Skin contact causes redness. Prolonged contact may cause skin dryness.
	Eyes:	Contact with the eyes produces redness and pain.
	Ingestion:	If swallowed, may cause irritation of the throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea.
		Description of first-aid measures
		Remove the patient out of the contaminated area into the fresh air. If breathing is irregular or stops, administer artificial respiration. If the person is unconscious, place in appropriate recovery position. Keep the patient warm and at rest until medical attention arrives.
		Remove immediately contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser. Do not use solvents or thinners.
		Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water for at least 15 minutes, holding the eyelids apart, until the irritation is reduced. Call a physician immediately.
		If swallowed, seek medical advice immediately and show container or label. Do not induce vomiting, due to the risk of aspiration. Keep the patient at rest.
4.2	<b>MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:</b>	
	The main symptoms and effects are indicated in sections 4.1 and 11.1	
4.3	<b>INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:</b>	
	<u>Notes to physician:</u> Treatment should be directed at the control of symptoms and the clinical condition of the patient.. <u>Antidotes and contraindications:</u> Specific antidote not known.	

**SECTION 5: FIREFIGHTING MEASURES**

5.1	<b>EXTINGUISHING MEDIA:</b>
	Extinguishing powder or CO <sub>2</sub> .
5.2	<b>SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:</b>
	As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, Carbon dioxide. Exposure to combustion or decomposition products may be a hazard to health.
5.3	<b>ADVICE FOR FIREFIGHTERS:</b>
	<u>Special protective equipment:</u> Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or is not being used, combat fire from a sheltered position or from a safe distance. The standard EN469 provides a basic level of protection for chemical incidents. <u>Other recommendations:</u> Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.



EPOXI SELLADOR INCOLORO 40% SOLIDOS  
Code : 12113



Version: 6

Revision: 28/02/2023

Previous revision: 19/12/2022

Date of printing: 28/02/2023

## SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1	<b>PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:</b> Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product. Avoid breathing vapours. Keep people without protection in opposition to the wind direction.
6.2	<b>ENVIRONMENTAL PRECAUTIONS:</b> Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.
6.3	<b>METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:</b> Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc..). Clean preferably with a biodegradable detergent. Keep the remains in a closed container.
6.4	<b>REFERENCE TO OTHER SECTIONS:</b> For contact information in case of emergency, see section 1. For information on safe handling, see section 7. For exposure controls and personal protection measures, see section 8. For waste disposal, follow the recommendations in section 13.

## SECTION 7: HANDLING AND STORAGE

7.1	<p><b>PRECAUTIONS FOR SAFE HANDLING:</b></p> <p>Comply with the existing legislation on health and safety at work.</p> <p><b>- General recommendations:</b> Avoid any type of leakage or escape. Keep the container tightly closed.</p> <p><b>- Recommendations for the prevention of fire and explosion risks:</b> Vapours are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reach distant ignition sources and flame up or explode. Due to its flammability, this material should only be used in areas from which all naked lights and other sources of ignition have been excluded and away from other heat or electrical sources. Switch mobile phones off and do not smoke. No tools with a potential for sparks should be used.</p> <p>Flashpoint 4* °C (Pensky-Martens) CLP 2.6.4.3. Autoignition temperature: 470* °C Ventilation requirement: Not available.</p> <p><b>- Recommendations for the prevention of toxicological risks:</b> Do not eat, drink or smoke while handling. After handling, wash hands with soap and water. For exposure controls and personal protection measures, see section 8.</p> <p><b>- Recommendations for the prevention of environmental contamination:</b> # Avoid any spillage in the environment. Pay special attention to the cleaning water. In the case of accidental spillage, follow the instructions indicated in section 6.</p>
7.2	<p><b>CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:</b></p> <p>Forbid the entry to unauthorized persons. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area. If possible, avoid direct contact with sunlight. Avoid extreme humidity conditions. In order to avoid leakages, the containers, after use, should be closed carefully and placed in a vertical position. For more information, see section 10.</p> <p><b>- Class of store:</b> According to current legislation.</p> <p><b>- Maximum storage period:</b> 12 Months.</p> <p><b>- Temperature interval:</b> min:5 °C, max:40 °C (recommended).</p> <p><b>- Incompatible materials:</b> Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.</p> <p><b>- Type of packaging:</b> According to current legislation.</p> <p><b>- Limit quantity (Seveso III): Directive 2012/18/EU:</b></p> <ul style="list-style-type: none"> <li>- Named dangerous substances/mixtures: None</li> <li>- Hazard categories and lower-/upper threshold quantities in tonnes (t):</li> <li>· Physical hazards: Highly flammable liquid and vapour. (P5c) (5000t/50000t).</li> <li>· Health hazards: Not applicable</li> <li>· Environmental hazards: Toxic to aquatic life with long lasting effects. (E2) (200t/500t).</li> <li>· Other hazards: Not applicable</li> <li>- Threshold quantity for the application of lower-tier requirements: 200 tons</li> <li>- Threshold quantity for the application of upper-tier requirements: 500 tons</li> </ul> <p><b>- Remarks:</b> The qualifying quantities set out above relate to each establishment. The quantities to be considered for the application of the relevant Articles are the maximum quantities which are present or are likely to be present at any one time. Dangerous substances present at an establishment only in quantities equal to or less than 2 % of the relevant qualifying quantity shall be ignored for the purposes of calculating the total quantity present, if their location within an establishment is such that it cannot act as an initiator of a major accident elsewhere at that establishment. For more details, see note 4 of Annex I of the Seveso Directive.</p>
7.3	<b>SPECIFIC END USE(S):</b> For the use of this product particular recommendations apart from that already indicated are not available.



EPOXI SELLADOR INCOLORO 40% SOLIDOS  
Code : 12113



Version: 6

Revision: 28/02/2023

Previous revision: 19/12/2022

Date of printing: 28/02/2023

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1

**CONTROL PARAMETERS:**

If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

**- OCCUPATIONAL EXPOSURE LIMIT VALUES (WEL)**

EH40/2005 WELs (United Kingdom) 2018	Year	WEL-TWA		WEL-STEL		Remarks
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	
Xylene (mixture of isomers)	1996	100	434	150	651	BMGV, A4
Ethylmethylketone	1992	200	590	300	885	BMGV

WEL - Workplace Exposure Limit, TWA - Time Weighted Average (8 hours), STEL - Short Term Exposure Limit (15 min).

BMGV - Biological monitoring guidance value. BMGVs are non-statutory and any biological monitoring undertaken in association with a guidance value needs to be conducted on a voluntary basis (ie with the fully informed consent of all concerned).

A4 - Non classified as carcinogenic in humans.

**- BIOLOGICAL LIMIT VALUES:**

Biological monitoring can be a very useful complementary technique to air monitoring when air sampling techniques alone may not give a reliable indication of exposure. Biological monitoring is the measurement and assessment of hazardous substances or their metabolites in tissues, secretions, excreta or expired air, or any combination of these, in exposed workers. Measurements reflect absorption of a substance by all routes. Biological monitoring may be particularly useful in circumstances where there is likely to be significant skin absorption and/or gastrointestinal tract uptake following ingestion, where control of exposure depends on respiratory protective equipment, where there is a reasonably well-defined relationship between biological monitoring and effect, or where it gives information on accumulated dose and target organ body burden which is related to toxicity.

This preparation contains the following substances that have established a biological limit value:

- Methyl ethyl ketone (2012): Biological determinant: methyl ethyl ketone in urine, BEI: 2 mg/l, Sampling time: end of shift (2), Notation: (Ns).

These indicators accumulate in the body during the work week, therefore the sampling time is critical in relation to previous exposures. (2) When the end of the exposition not coincide with the end of the working day, the sample will be taken as soon as possible after the real exposition ceases. Once the steady state that depends on each biological indicator (weeks, months) has been reached, sampling of these can be done at any time. &The biological determinant is an indicator of exposure to the chemical, but the quantitative interpretation of the measurement is ambiguous. &(CDC: Guidelines for the identification and management of lead exposure in pregnant and lactating women, 2010).

**- DERIVED NO-EFFECT LEVEL (DNEL):**

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from an occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

- DERIVED NO-EFFECT LEVEL, WORKERS:- Systemic effects, acute and chronic:	DNEL Inhalation mg/m <sup>3</sup>		DNEL Cutaneous mg/kg bw/d		DNEL Oral mg/kg bw/d	
	(a)	(c)	s/r (a)	(c)	(a)	(c)
Xylene (mixture of isomers)	289	77	s/r	180	-	-
Epoxy resin (average molecular weight <700)	12,25	12,25	8,33	8,33	-	-
Ethylmethylketone	-	600	-	1161	-	-

- DERIVED NO-EFFECT LEVEL, WORKERS:- Local effects, acute and chronic:	DNEL Inhalation mg/m <sup>3</sup>		DNEL Cutaneous mg/cm <sup>2</sup>		DNEL Eyes mg/cm <sup>2</sup>	
	(a)	(c)	s/r (a)	(c)	(a)	(c)
Xylene (mixture of isomers)	289	s/r	s/r	(c)	-	-
Epoxy resin (average molecular weight <700)	-	-	-	(c)	-	-
Ethylmethylketone	-	(c)	-	(c)	-	(c)

**- Derived no-effect level, general population:**

Not applicable (product for professional or industrial use).

(a) - Acute, short-term exposure, (c) - Chronic, long-term or repeated exposure.

(-) - DNEL not available (without data of registration REACH).

s/r - DNEL not derived (not identified hazard).

**- PREDICTED NO-EFFECT CONCENTRATION (PNEC):**

- PREDICTED NO-EFFECT CONCENTRATION, AQUATIC ORGANISMS:- Fresh water, marine water and intermittent release:	PNEC Fresh water mg/l		PNEC Marine mg/l		PNEC Intermittent mg/l	
	(a)	(c)	(a)	(c)	(a)	(c)
Xylene (mixture of isomers)	0.327		0.327		0.327	
Epoxy resin (average molecular weight <700)	0.006		0.0006		0.018	
Ethylmethylketone	55.8		55.8		55.8	

- WASTEWATER TREATMENT PLANTS (STP) AND SEDIMENTS IN FRESH- AND MARINE WATER:	PNEC STP mg/l		PNEC Sediments mg/kg dw/d		PNEC Sediments mg/kg dw/d	
	(a)	(c)	(a)	(c)	(a)	(c)
Xylene (mixture of isomers)	6.58		12.46		12.46	
Epoxy resin (average molecular weight <700)	10		0.996		0.0996	





EPOXI SELLADOR INCOLORO 40% SOLIDOS  
Code : 12113



Version: 6

Revision: 28/02/2023

Previous revision: 19/12/2022

Date of printing: 28/02/2023

Ethylmethylketone	709	284.74	284.7
<b>- PREDICTED NO-EFFECT CONCENTRATION, TERRESTRIAL ORGANISMS:- Air, soil and effects for predators and humans:</b>	<b>PNEC Air</b> mg/m3	<b>PNEC Soil</b> mg/kg dw/d	<b>PNEC Oral</b> mg/kg dw/d
Xylene (mixture of isomers)	-	2.31	-
Epoxy resin (average molecular weight <700)	-	0.196	11
Ethylmethylketone	-	22.5	1000
(-) - PNEC not available (without data of registration REACH).			

8.2

**EXPOSURE CONTROLS:****ENGINEERING MEASURES:**

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.

**- Protection of respiratory system:**

Avoid the inhalation of vapours.

**- Protection of eyes and face:**

# It is recommended to install water taps, sources or eyewash bottles with clean water close to the working area.

**- Protection of hands and skin:**

It is recommended to install water taps or sources with clean water close to the working area. Barrier creams may help to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.

**OCCUPATIONAL EXPOSURE CONTROLS: REGULATION (EU) NO. 2016/425:**

As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding marking. For more information on personal protective equipment (storage, use, cleaning, maintenance, type and characteristics of the PPE, protection class, marking, category, CEN norm, etc.), you should consult the informative brochures provided by the manufacturers of PPE.

Mask: 	✓	A-type filter mask (brown) for gases and vapours of organic compounds with a boiling point higher than 65°C (EN14387). Class 1: low capacity up to 1000 ppm, Class 2: medium capacity up to 5000 ppm, Class 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. The respiratory equipment with filters does not work satisfactorily when the air contains high concentrations of vapour or oxygen content less than 18% in volume. In presence of high concentrations of vapour, use independent breathing apparatus.
Safety goggles: 	✓	Safety goggles designed to protect against liquid splashes, with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.
Face shield:		No.
Gloves: 	✓	Gloves resistant against chemicals (EN374). When repeated or prolonged contact with the product is expected, gloves of protection level 5 or higher should be used, with a breakthrough time of >240 min. When short contact with the product is expected, use gloves with a protection level 2 or higher should be used, with a breakthrough time >30 min. The breakthrough time of the selected glove material should be in accordance with the pretended period of use. There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, the instructions/specifications provided by the glove supplier should be taken into account. Use the proper technique of removing gloves (without touching glove's outer surface) to avoid contact of the product with the skin. The gloves should be immediately replaced when any sign of degradation is noted.
Boots:		No.
Apron:		No.
Clothing:		Advisable.

**- Thermal hazards:**

Not applicable (the product is handled at room temperature).

**ENVIRONMENTAL EXPOSURE CONTROLS:**

Avoid any spillage in the environment. Avoid any release into the atmosphere.

**- Spills on the soil:**

Prevent contamination of soil.

**- Spills in water:**

Do not allow to escape into drains, sewers or water courses.

**-Water Management Act:**



EPOXI SELLADOR INCOLORO 40% SOLIDOS  
Code : 12113



Version: 6

Revision: 28/02/2023

Previous revision: 19/12/2022

Date of printing: 28/02/2023

This product does not contain any substance included in the list of priority substances in the field of water policy under Directive 2000/60/EC~2013/39/EU.

- Emissions to the atmosphere:

Because of volatility, emissions to the atmosphere while handling and use may result. Avoid any release into the atmosphere.

VOC (product ready for use\*):

It is applicable the Directive 2004/42/EC, on the limitation of emissions of volatile compounds due to the use of organic solvents: PAINTS AND VARNISHES (defined in the Directive 2004/42/EC, Annex I.1): Emission subcategory j) Two-pack performance coating, solvent-borne. VOC (product ready for use\*): (EPOXI SELLADOR INCOLORO Cod. 12113 / ENDURECEDOR EPOXI SELLADOR Cod. 12114 = 100 / 33 in volume): 477,5 g/l (VOC max.500 g/l\* starting from 01.01.2010)

VOC (industrial installations):

If this product is used in an industrial installation, it must be verified if it is applicable the Directive 2010/75/CE (DL.127/2013, on the limitation of emissions of volatile compounds due to the use of organic solvents in certain activities and installations: Solvents: 51,87 % Weight, VOC (supply): 51,87 % Weight, VOC: 42,17 % C (expressed as carbon), Molecular weight (average): 93,08 , Number C atoms (average): 6,31

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:

Appearance

Physical state: Liquid  
Colour: Colourless  
Odour: Characteristic  
Odour threshold: Not available (mixture).

Change of state

Melting point: Not available (mixture).  
Initial boiling point: 79,6\* °C at 760 mmHg

- Flammability:

Flashpoint 4\* °C (Pensky-Martens) CLP 2.6.4.3.  
Lower/upper flammability or explosive limits: Not available - Not available  
Autoignition temperature: 470\* °C

Stability

Decomposition temperature: Not available (technical impossibility to obtain the data).

pH-value

pH: Not applicable (non-aqueous media).

- Viscosity:

Dynamic viscosity: 750\* cps at 20°C  
Kinematic viscosity: 500 cSt at 20°C  
Viscosity (flow time): 36 sec. CF6 at 20°C

- Solubility(ies):

Solubility in water 0,1583076 g/l at 20°C  
Liposolubility: Not applicable (inorganic product).  
Partition coefficient: n-octanol/water: Not applicable (mixture).

- Volatility:

Vapour pressure: 41,5007\* mmHg at 20°C  
Vapour pressure: 19,8669\* kPa at 50°C  
Evaporation rate: Not available (lack of data).

Density

Relative density: 1,007\* at 20/4°C Relative water  
Relative vapour density: 2,59\* at 20°C 1 atm. Relative air

Particle characteristics

Particle size: Not applicable.

- Explosive properties:

Vapours can form explosive mixtures with air and are able to flame up or explode in presence of an ignition source.

- Oxidizing properties:

Not classified as oxidizing product.

\*Estimated values based on the substances composing the mixture.

9.2 OTHER INFORMATION:

Information regarding physical hazard classes

Flammable liquids: Combustibility: Combustible.

Other security features:

VOC (supply): 51,9 % Weight  
VOC (supply): 477,5 g/l  
Nonvolatile: 48,13 \* % Weight 1h. 60°C

The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the corresponding technical data sheet. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.



EPOXI SELLADOR INCOLORO 40% SOLIDOS  
Code : 12113



Version: 6

Revision: 28/02/2023

Previous revision: 19/12/2022

Date of printing: 28/02/2023

## SECTION 10: STABILITY AND REACTIVITY

10.1	<p><b>REACTIVITY:</b></p> <p>- <b>Corrosivity to metals:</b> It is not corrosive to metals.</p> <p>- <b>Pyrophorical properties:</b> It is not pyrophoric.</p>
10.2	<p><b>CHEMICAL STABILITY:</b> Stable under recommended storage and handling conditions.</p>
10.3	<p><b>POSSIBILITY OF HAZARDOUS REACTIONS:</b> Possible dangerous reaction with oxidizing agents, acids, alkalis, amines.</p>
10.4	<p><b>CONDITIONS TO AVOID:</b></p> <p>- <b>Heat:</b> Keep away from sources of heat.</p> <p>- <b>Light:</b> If possible, avoid direct contact with sunlight.</p> <p>- <b>Air:</b> The product is not affected by exposure to air, but should not be left the containers open.</p> <p>- <b>Humidity:</b> Avoid extreme humidity conditions. Moisture absorption may have an effect on curing speed, and on other properties as well.</p> <p>- <b>Pressure:</b> Not relevant.</p> <p>- <b>Shock:</b> The product is not sensitive to shocks, but as a recommendation of a general nature should be avoided bumps and rough handling to avoid dents and breakage of packaging, especially when the product is handled in large quantities, and during loading and download operations.</p>
10.5	<p><b>INCOMPATIBLE MATERIALS:</b> Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.</p>
10.6	<p><b>HAZARDOUS DECOMPOSITION PRODUCTS:</b> As consequence of thermal decomposition, hazardous products may be produced: carbon monoxide.</p>

## SECTION 11: TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2021/849 (CLP).																																																				
11.1	<p><b>INFORMATION ON HAZARD CLASSES AS DEFINED IN REGULATION (EC) NO 1272/2008 :</b></p> <p><b>ACUTE TOXICITY:</b></p> <table border="1"> <thead> <tr> <th>Dose and lethal concentrations for individual ingredients:</th> <th>DL50 (OECD401) mg/kg bw Oral</th> <th>DL50 (OECD402) mg/kg bw Cutaneous</th> <th>CL50 (OECD403) mg/m<sup>3</sup>·4h Inhalation</th> </tr> </thead> <tbody> <tr> <td>Xylene (mixture of isomers)</td> <td>4300 Rat</td> <td>1700 Rabbit</td> <td>&gt; 22080 Rat</td> </tr> <tr> <td>Epoxy resin (average molecular weight &lt;700)</td> <td>11400 Rat</td> <td>&gt; 2000 Rabbit</td> <td></td> </tr> <tr> <td>Ethylmethylketone</td> <td>2737 Rat</td> <td>6480 Rabbit</td> <td>&gt; 23500 Rat</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Estimates of acute toxicity (ATE) for individual ingredients:</th> <th>ATE mg/kg bw Oral</th> <th>ATE mg/kg bw Cutaneous</th> <th>ATE mg/m<sup>3</sup>·4h Inhalation</th> </tr> </thead> <tbody> <tr> <td>Xylene (mixture of isomers)</td> <td>-</td> <td>*1700</td> <td>11000 Vapours</td> </tr> <tr> <td>Ethylmethylketone</td> <td>-</td> <td>-</td> <td>23500 Vapours</td> </tr> </tbody> </table> <p>(* ) - Point estimates of acute toxicity corresponding to the classification category (see GHS/CLP Table 3.1.2). These values are designed to be used in the calculation of the ATE for classification of a mixture based on its components and do not represent test results. (-) - The components that are assumed to have no acute toxicity at the upper threshold of category 4 for the corresponding exposure route are ignored.</p> <p>- <b>No observed adverse effect level</b> Not available</p> <p>- <b>Lowest observed adverse effect level</b> Not available</p> <p><b>INFORMATION ON LIKELY ROUTES OF EXPOSURE: ACUTE TOXICITY:</b></p> <table border="1"> <thead> <tr> <th>Routes of exposure</th> <th>Acute toxicity</th> <th>Cat.</th> <th>Main effects, acute and/or delayed</th> <th>Criteria</th> </tr> </thead> <tbody> <tr> <td>Inhalation: Not classified</td> <td>ATE &gt; 20000 mg/m<sup>3</sup></td> <td>-</td> <td>Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).</td> <td>GHS/CLP 3.1.3.6.</td> </tr> <tr> <td>Skin: Not classified</td> <td>ATE &gt; 5000 mg/kg bw</td> <td>-</td> <td>Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).</td> <td>GHS/CLP 3.1.3.6.</td> </tr> <tr> <td>Eyes: Not classified</td> <td>Not available.</td> <td>-</td> <td>Not classified as a product with acute toxicity by eye contact (lack of data).</td> <td>GHS/CLP 1.2.5.</td> </tr> </tbody> </table>				Dose and lethal concentrations for individual ingredients:	DL50 (OECD401) mg/kg bw Oral	DL50 (OECD402) mg/kg bw Cutaneous	CL50 (OECD403) mg/m <sup>3</sup> ·4h Inhalation	Xylene (mixture of isomers)	4300 Rat	1700 Rabbit	> 22080 Rat	Epoxy resin (average molecular weight <700)	11400 Rat	> 2000 Rabbit		Ethylmethylketone	2737 Rat	6480 Rabbit	> 23500 Rat	Estimates of acute toxicity (ATE) for individual ingredients:	ATE mg/kg bw Oral	ATE mg/kg bw Cutaneous	ATE mg/m <sup>3</sup> ·4h Inhalation	Xylene (mixture of isomers)	-	*1700	11000 Vapours	Ethylmethylketone	-	-	23500 Vapours	Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed	Criteria	Inhalation: Not classified	ATE > 20000 mg/m <sup>3</sup>	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.	Skin: Not classified	ATE > 5000 mg/kg bw	-	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.	Eyes: Not classified	Not available.	-	Not classified as a product with acute toxicity by eye contact (lack of data).	GHS/CLP 1.2.5.
Dose and lethal concentrations for individual ingredients:	DL50 (OECD401) mg/kg bw Oral	DL50 (OECD402) mg/kg bw Cutaneous	CL50 (OECD403) mg/m <sup>3</sup> ·4h Inhalation																																																	
Xylene (mixture of isomers)	4300 Rat	1700 Rabbit	> 22080 Rat																																																	
Epoxy resin (average molecular weight <700)	11400 Rat	> 2000 Rabbit																																																		
Ethylmethylketone	2737 Rat	6480 Rabbit	> 23500 Rat																																																	
Estimates of acute toxicity (ATE) for individual ingredients:	ATE mg/kg bw Oral	ATE mg/kg bw Cutaneous	ATE mg/m <sup>3</sup> ·4h Inhalation																																																	
Xylene (mixture of isomers)	-	*1700	11000 Vapours																																																	
Ethylmethylketone	-	-	23500 Vapours																																																	
Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed	Criteria																																																
Inhalation: Not classified	ATE > 20000 mg/m <sup>3</sup>	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.																																																
Skin: Not classified	ATE > 5000 mg/kg bw	-	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.																																																
Eyes: Not classified	Not available.	-	Not classified as a product with acute toxicity by eye contact (lack of data).	GHS/CLP 1.2.5.																																																





EPOXI SELLADOR INCOLORO 40% SOLIDOS  
Code : 12113



Version: 6

Revision: 28/02/2023

Previous revision: 19/12/2022

Date of printing: 28/02/2023

Ingestion: Not classified	ATE > 2000 mg/kg bw	Not available.	Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
------------------------------	---------------------	----------------	--	------------------

GHS/CLP 3.1.3.6: Classification of mixtures based on ingredients of the mixture (additivity formula).

#### CORROSION / IRRITATION / SENSITISATION :

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Respiratory corrosion/irritation: 	Respiratory tract 	Cat.3	IRRITANT: May cause respiratory irritation.	GHS/CLP 1.2.6. 3.8.3.4.
- Skin corrosion/irritation: 	Skin 	Cat.2	IRRITANT: Causes skin irritation.	GHS/CLP 3.2.3.3.
- Serious eye damage/irritation: 	Eyes 	Cat.2	IRRITANT: Causes serious eye irritation.	GHS/CLP 3.3.3.3.
- Respiratory sensitisation: Not classified	-	-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.
- Skin sensitisation: 	Skin 	Cat.1	SENSITISING: May cause an allergic skin reaction.	GHS/CLP 3.4.3.3.

GHS/CLP 3.2.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.3.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.4.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

#### - ASPIRATION HAZARD:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Aspiration hazard: Not classified	-	-	Not classified as a product hazardous by aspiration (based on available data, the classification criteria are not met).	GHS/CLP 3.10.3.3.

GHS/CLP 3.10.3.3: Classification of the mixture when data are available for all components or only for some components.

#### SPECIFIC TARGET ORGANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Effects	SE/RE	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Systemic:	RE 	Systemic 	Cat.2	HARMFUL: May cause damage to organs through prolonged or repeated exposure if inhaled.	GHS/CLP 3.8.3.4
- Respiratory effects:	SE 	Respiratory tract 	Cat.3	IRRITANT: May cause respiratory irritation.	GHS/CLP 3.8.3.4
- Neurological:	SE 	CNS 	Cat.3	NARCOSIS: May cause drowsiness or dizziness if inhaled.	GHS/CLP 3.8.3.4.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

#### CMR EFFECTS:

##### - Carcinogenic effects:

It is not considered as a carcinogenic product.

##### - Genotoxicity:

It is not considered as a mutagenic product.

##### - Toxicity for reproduction:

Does not harm fertility. Does not harm the unborn child.

##### - Effects via lactation:

Not classified as a hazardous product for children breast-fed.

#### DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:

##### Routes of exposure

May be absorbed by inhalation of vapour, through the skin and by ingestion.

##### - Short-term exposure:



EPOXI SELLADOR INCOLORO 40% SOLIDOS  
Code : 12113



Version: 6

Revision: 28/02/2023

Previous revision: 19/12/2022

Date of printing: 28/02/2023

# Exposure to solvent vapour concentrations in excess of the stated occupational exposure limit, may result in adverse health effects, such as mucous membrane and respiratory system irritation and adverse effects on kidneys, liver and central nervous system. Liquid splashes in the eyes may cause irritation and reversible damage. If swallowed, may cause irritation of the throat; other effects may be the same as described in the exposure to vapours. Causes burns to the skin or eyes by direct contact or to the digestive tract if swallowed. The mists of fine particles are skin and respiratory tract irritants. Causes serious eye damage. Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness.

- Long-term or repeated exposure:

Repeated or prolonged contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. May cause damage to organs through prolonged or repeated exposure if inhaled.

INTERACTIVE EFFECTS:

Not available.

INFORMATION ABOUT TOXICOKINETICS, METABOLISM AND DISTRIBUTION:

- Dermal absorption:

This preparation contains the following substances for which dermal absorption can be very high: Xylene (mixture of isomers).

- Basic toxicokinetics:

Not available.

ADDITIONAL INFORMATION:

It contains low molecular weight epoxy constituents which are irritating to eyes, mucous membrane and skin.

11.2 INFORMATION ON OTHER HAZARDS:

Endocrine disrupting properties:

This product does not contain substances with endocrine disrupting properties identified or under evaluation.

Other information:

No additional information available.

**SECTION 12: ECOLOGICAL INFORMATION**

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2021/849 (CLP).

12.1 TOXICITY:

- Acute toxicity in aquatic environment for individual ingredients	CL50 (OECD 203) mg/l · 96hours	CE50 (OECD 202) mg/l · 48hours	CE50 (OECD 201) mg/l · 72hours
Xylene (mixture of isomers)	14 - Fishes	16 - Daphniae	10 - Algae
Epoxy resin (average molecular weight <700)	1.5 - Fishes	1.7 - Daphniae	9.4 - Algae
Ethylmethylketone	2993 - Fishes	308 - Daphniae	1972 - Algae

- No observed effect concentration	NOEC (OECD 210) mg/l · 28 days	NOEC (OECD 211) mg/l · 21 days	NOEC (OECD 201) mg/l · 72 hours
Epoxy resin (average molecular weight <700)		0.3 - Daphniae	

- Lowest observed effect concentration

Not available

ASSESSMENT OF AQUATIC TOXICITY:

Aquatic toxicity	Cat.	Main hazards to the aquatic environment	Criteria
- Acute aquatic toxicity: Not classified	-	Not classified as a hazardous product with acute toxicity to aquatic life (based on available data, the classification criteria are not met).	GHS/CLP 4.1.3.5.5.3.
- Chronic aquatic toxicity:	Cat.2	TOXIC: Toxic to aquatic life with long lasting effects.	GHS/CLP 4.1.3.5.5.4.

CLP 4.1.3.5.5.3: Classification of a mixture for acute hazards, based on summation of classified components.

CLP 4.1.3.5.5.4: Classification of a mixture for chronic (long term) hazards, based on summation of classified components.

12.2 PERSISTENCE AND DEGRADABILITY:

- Biodegradability:

# Not available.

Aerobic biodegradation for individual ingredients	COD mgO2/g	%DBO/DQO 5 days 14 days 28 days	Biodegradabilidad
Xylene (mixture of isomers)	2620	52 81 88	Easy
Epoxy resin (average molecular weight <700)		- - 1	Not easy
Ethylmethylketone	2440	48 - 98	Easy

Note: Biodegradability data correspond to an average of data from various bibliographic sources.

- Hydrolysis:

Not available.

- Photodegradability:



EPOXI SELLADOR INCOLORO 40% SOLIDOS  
Code : 12113



Version: 6

Revision: 28/02/2023

Previous revision: 19/12/2022

Date of printing: 28/02/2023

Not available.

12.3 **BIOACCUMULATIVE POTENTIAL:**

May bioaccumulate.

Bioaccumulation for individual ingredients	logPow	BCF L/kg	Potential
Xylene (mixture of isomers)	3.16	56.5 (calculated)	Low
Epoxy resin (average molecular weight <700)	3.24	31 (calculated)	Low
Ethylmethylketone	0.29	3.2 (calculated)	No bioaccumulable

12.4 **MOBILITY IN SOIL:**

Not available

Mobility for individual ingredients	log P <sub>oc</sub>	Constant of Henry Pa·m <sup>3</sup> /mol 20°C	Potential
Xylene (mixture of isomers)	2,25	660 (calculated)	Low
Epoxy resin (average molecular weight <700)	0,65		Low
Ethylmethylketone	1,28	5,77 (calculated)	No bioaccumulable

12.5 **RESULTS OF PBT AND VPVB ASSESMENT:(Annex XIII of Regulation (EC) no. 1907/2006:)**

Does not contain substances that fulfil the PBT/vPvB criteria.

12.6 **ENDOCRINE DISRUPTING PROPERTIES:**

This product does not contain substances with endocrine disrupting properties identified or under evaluation.

12.7 **OTHER ADVERSE EFFECTS:****- Ozone depletion potential:**

Not available.

**- Photochemical ozone creation potential:**

Not available.

**- Earth global warming potential:**In case of fire or incineration liberates CO<sub>2</sub>.**SECTION 13: DISPOSAL CONSIDERATIONS**13.1 **WASTE TREATMENT METHODS:Directive 2008/98/EC~Regulation (EU) no. 1357/2014:**

Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose at an authorised waste collection point. Waste should be handled and disposed in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.

**Disposal of empty containers:Directive 94/62/EC~2015/720/EU, Decision 2000/532/EC~2014/955/EU:**

Emptied containers and packaging should be disposed in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of emptying of the same, being the holder of the residue responsible for their classification, in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in itself.

**Procedures for neutralising or destroying the product:**

Controlled incineration in special facilities for chemical waste, in accordance with local regulations.



EPOXI SELLADOR INCOLORO 40% SOLIDOS  
Code : 12113









Version: 6

Revision: 28/02/2023

Previous revision: 19/12/2022

Date of printing: 28/02/2023

## SECTION 14: TRANSPORT INFORMATION

14.1	<u>UN NUMBER OR ID NUMBER:</u> 1263
14.2	<u>UN PROPER SHIPPING NAME:</u> PAINT
14.3	<p><u>TRANSPORT HAZARD CLASS(ES):</u> <u>Transport by road (ADR 2021) and</u> <u>Transport by rail (RID 2021):</u></p> <p style="text-align: right;">FP&lt;23°C, viscous according 2.2.3.1.4. &lt;450 L (ADR) or 2.3.2.2. &lt;30 L (IMDG) or 3.3.3.1.1. &lt;30 L (IATA), VP&lt;110 kPa50°C</p> <p>- Class: 3 - Packing group: III - Classification code: F1 - Tunnel restriction code: (D/E) - Transport category: 2, max. ADR 1.1.3.6. 333 L - Limited quantities: 5 L (see total exemptions ADR 3.4) - Transport document: Consignment paper. - Instructions in writing: ADR 5.4.3.4</p> <p><u>Transport by sea (IMDG 39-18):</u></p> <p>- Class: 3 - Packing group: III - Emergency Sheet (EmS): F-E,S_E - First Aid Guide (MFAG): 310,313 - Marine pollutant: Yes. - Transport document: Shipping Bill of lading.</p> <p><u>Transport by air (ICAO/IATA 2021):</u></p> <p>- Class: 3 - Packing group: III - Transport document: Air Bill of lading.</p> <p><u>Transport by inland waterways (ADN):</u> Not available</p> <p style="text-align: center;">         </p>
14.4	<u>PACKING GROUP:</u> See section 14.3
14.5	<u>ENVIRONMENTAL HAZARDS:</u> Classified as hazardous for the environment.
14.6	<u>SPECIAL PRECAUTIONS FOR USER:</u> Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are upright and secure. Ensure adequate ventilation.
14.7	<u>MARITIME TRANSPORT IN BULK ACCORDING TO IMO INSTRUMENTS:</u> Not applicable.

## SECTION 15: REGULATORY INFORMATION

15.1	<p><u>SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE:</u></p> <p>The regulations applicable to this product generally are listed throughout this Safety Data Sheet.</p> <p><u>Restrictions on manufacture, placing on market and use:</u> See section 1.2</p> <p><u>Tactile warning of danger:</u> Not applicable (product for professional or industrial use).</p> <p><u>Child safety protection:</u> Not applicable (the classification criteria are not met).</p> <p><u>VOC information on the label:</u> Contains VOC max. 477,5 g/l for the product ready for use - The limit value 2004/42/EC-IIA cat. j) Two-pack performance coating, solvent-borne. is VOC max. 500 g/l (2010)</p> <p><u>OTHER REGULATIONS:</u> <u>Control of the risks inherent in major accidents (Seveso III):</u> See section 7.2</p> <p><u>Other local legislations:</u> The receiver should verify the possible existence of local regulations applicable to the chemical.</p>
15.2	<u>CHEMICAL SAFETY ASSESSMENT:</u> A chemical safety assessment has not been carried out for this mixture.



EPOXI SELLADOR INCOLORO 40% SOLIDOS  
Code : 12113



Version: 6

Revision: 28/02/2023

Previous revision: 19/12/2022

Date of printing: 28/02/2023

## SECTION 16 : OTHER INFORMATION

16.1 TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:

Hazard statements according the Regulation (EU) No. 1272/2008~2021/849 (CLP), Annex III:

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Notes related to the identification, classification and labelling of the substances or mixtures:

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

EVALUATION OF THE INFORMATION ON THE DANGER OF MIXTURES:

See sections 9.1, 11.1 and 12.1.

ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of Safety Data Sheets and labelling of products as well.

MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:

- European Chemicals Agency: ECHA, <http://echa.europa.eu/>
- Access to European Union Law, <http://eur-lex.europa.eu/>
- Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970).
- Threshold Limit Values, (AGCIH, 2021).
- European agreement on the international carriage of dangerous goods by road, (ADR 2021).
- International Maritime Dangerous Goods Code IMDG including Amendment 39-18 (IMO, 2018).

ABBREVIATIONS AND ACRONYMS:

List of abbreviations and acronyms that can be used (but not necessarily used) in this Safety Data Sheet:

- REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- CLP: European regularion on Classificatin, Labelling amd Packaging of substances and chemical mixtures.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- ELINCS: European List of Notified Chemical Substances.
- CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials.
- SVHC: Substances of Very High Concern.
- PBT: Persistent, bioaccumulable and toxic substances.
- vPvB: Very persistent and very bioaccumulable substances.
- VOC: Volatile Organic Compounds.
- DNEL: Derived No-Effect Level (REACH).
- PNEC: Predicted No-Effect Concentration (REACH).
- LC50: Lethal concentration, 50 percent.
- LD50: Lethal dose, 50 percent.
- UN: United Nations Organisation.
- ADR: European agreement concerning the international carriage of dangeous goods by road.
- RID: Regulations concerning the international transport of dangeous goods by rail.
- IMDG: International Maritime code for Dangerous Goods.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.

SAFETY DATA SHEET REGULATIONS:

Safety Data Sheet in accordance with Article 31 of Regulation (EC) No. 1907/2006 (REACH) and Annex of Regulation (EU) No. 2020/878.

HISTORIC: REVISION:

Version: 4 30/09/2022

Version: 5 19/12/2022

Version: 6 28/02/2023

Changes since previous Safety Data Sheet:

Legislative, contextual, numerical, methodological and normative changes since the previous version of the present Safety Data Sheet are identified by #.

The information of this Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users" working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product"s properties.