SAFETY DATA SHEET (REACH) In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2020/878

	dance with Regulation (EC		907/2006 and Regulation (EU) No	. 2020/87	8		(Language:
\mathbb{R}			NSA_BARNIZ INTERIOR- EXTER de : 12161	RIOR SAT	INADO		
'ersio	on: 6 Rev	vision	: 14/12/2022	Р	revious revision: 23/02/2022		Date of printing: 14/12/20
ECTIO	ON 1: IDENTIFICATION C	of the	SUBSTANCE/MIXTURE AND	OF THE	COMPANY/UNDERTAKI	ING	
1.1	-	RIOR-					
1.2			2-114E-A00W-6J20 JSES OF THE SUBSTANCE	OR MIX	TURE AND USES AD	VISED AGAINST:	
		<u>techn</u>	ical functions): [] Indus	trial [X]	Professional [X] Const	umers	
	Varnish. Sectors of use:						
	Consumer uses (SU2						
	Professional uses (SU Types of PCN use:	22),					
	Paints/coatings - Prote	ective a	ind functional.				
	Uses advised agains			- <i>(</i>	.		
	"Intended or identified		nded for any use or sector of us	e (industr	ial, professional or consu	imer) other than thos	e previously listed as
		<u>ufactur</u>	re, placing on market and use	e, accord	ing to Annex XVII of Re	egulation (EC) No.	<u>1907/2006:</u>
.3	Not restricted.		IER OF THE SAFETY DATA	SHEET			
.0	PINTURAS ISAVAL, S						
			. Casanova - 46394 Ribarroja d 001 - Fax: +34 96 1640002 - wv				
			son responsible for the Safet				
	atencionalcliente@isa						
.4	EMERGENCY TELE +34 96 1640001 8:00-						
			ons Information Service (NPIS)	- In Engla	and, Wales or Scotland: d	lial 111 - In N Ireland:	contact your local GP
			ons Information Service (NPIS) Iring normal hours.	- In Engla	nd, Wales or Scotland: d	lial 111 - In N Ireland:	: contact your local GP
CTIO	DN 2 : HAZARDS IDENTI CLASSIFICATION C Classification of mixtu available, generally is	FICATI	uring normal hours. ON E SUBSTANCE OR MIXTUR arried out in accordance with th out based on these data, b) in	E: e followin the abse	g principles: a) when da nce of data (tests) for mix	ta (tests) for the class	sification of mixtures a
CTIO	Pharma	FICATI FICATI DF THE res is c carried s of ass uld allow compon ordanc 3:H226	Arried normal hours. ON E SUBSTANCE OR MIXTUR arried out in accordance with th l out based on these data, b) in essing the risk, using the availa w to apply interpolation or extrag- nents in the mixture. the with Regulation (EU) No. 1 SISTOT SE (narcosis) 3:H336 A	E: e followin the abse ble data f polation te 272/2000 quatic Ch	g principles: a) when da nce of data (tests) for miz or mixtures similarly clas echniques, methods are u <u>8~2021/849 (CLP):</u> ronic 3:H412 EUH066	ta (tests) for the class stures are generally u sified, and c) in the a used to classify risk a	sification of mixtures a used interpolation or absence of tests and ussessment based on t
CTIO	Pharma	FICATI DF THE res is c carried of asso uld allow compon ordanc 3:H226	Iring normal hours. ON E SUBSTANCE OR MIXTUR arried out in accordance with th I out based on these data, b) in essing the risk, using the availa v to apply interpolation or extrag- nents in the mixture. E with Regulation (EU) No. 1 SISTOT SE (narcosis) 3:H336 A Classification of the mixture	E: e followin the abse ble data f polation te 272/2000 quatic Ch Cat.	g principles: a) when da nce of data (tests) for miz or mixtures similarly clas cchniques, methods are u 8~2021/849 (CLP):	ta (tests) for the class xtures are generally u sified, and c) in the a	sification of mixtures an used interpolation or absence of tests and
CTIO	Pharma Pharma Pharma Pharma CLASSIFICATION C Classification of mixtu available, generally is extrapolation methods information which wou data of the individual c Classification in accc WARNING:Flam. Liq. Danger class Physicochemical:	Acist du FICATI DF THE res is c carried s of asse uld allov compon ordanc 3:H226	Aring normal hours. ON E SUBSTANCE OR MIXTUR arried out in accordance with the out based on these data, b) in essing the risk, using the availa w to apply interpolation or extrag- ments in the mixture. We with Regulation (EU) No. 1 BISTOT SE (narcosis) 3:H336 A Classification of the mixture Flam. Liq. 3:H226 c)	E: e followin the abse ble data f polation te 272/2006 quatic Ch Cat. Cat.3	g principles: a) when da nce of data (tests) for miz or mixtures similarly clas echniques, methods are u <u>8~2021/849 (CLP):</u> ronic 3:H412 EUH066 Routes of exposure	ta (tests) for the class ktures are generally u sified, and c) in the a used to classify risk a Target organs	sification of mixtures a used interpolation or absence of tests and issessment based on the Effects
CTIO	Pharma	Acist du FICATI DF THE res is c carried s of asse uld allov compon ordanc 3:H226 ()) ()) () () () () () ()) ()) () () ()) ()) ()) ()) ()) () ()) ()) ()) ()) ()) ()) ())) ())) ())) ())) ())) ())) ())) ()))))))))))))	Iring normal hours. ON E SUBSTANCE OR MIXTUR arried out in accordance with th I out based on these data, b) in essing the risk, using the availa v to apply interpolation or extrag- nents in the mixture. E with Regulation (EU) No. 1 SISTOT SE (narcosis) 3:H336 A Classification of the mixture	E: e followin the abse ble data f polation te 272/2006 quatic Ch Cat. Cat.3	g principles: a) when da nce of data (tests) for miz or mixtures similarly clas echniques, methods are u <u>8~2021/849 (CLP):</u> ronic 3:H412 EUH066	ta (tests) for the class stures are generally u sified, and c) in the a used to classify risk a	sification of mixtures a used interpolation or absence of tests and ussessment based on th
CTIO	Pharma Pharma Pharma Pharma CLASSIFICATION C Classification of mixtu available, generally is extrapolation methods information which wou data of the individual c Classification in accc WARNING:Flam. Liq. Danger class Physicochemical:	Acist du FICATI DF THE res is c carried s of asse ild allow compone ordance 3:H226 (C C (C (C (C C (C C (C C C (C C C (C C C C C C C C C C C C C	Arried out in accordance with the out in accordance with the out based on these data, b) in essing the risk, using the availa w to apply interpolation or extragations in the mixture. The with Regulation (EU) No. 1 STOT SE (narcosis) 3:H336[A Classification of the mixture Flam. Liq. 3:H226 c) STOT SE (narcosis) 3:H336 c	E: e followin the abse ble data f polation te 272/2006 quatic Ch Cat. Cat.3	g principles: a) when da nce of data (tests) for mix or mixtures similarly class echniques, methods are u <u>8~2021/849 (CLP):</u> ronic 3:H412 EUH066 Routes of exposure	ta (tests) for the class stures are generally u sified, and c) in the a used to classify risk a Target organs - CNS	sification of mixtures a used interpolation or absence of tests and issessment based on t Effects
CTIO	Pharma	Acist du FICATI DF THE res is c carried s of asse id allow compon ordanc 3:H226 ()) ()))) ())) ()))) ())))) ())))) ()))) ())))) ())))))) ()))))) ())))))))))	Arried out in accordance with the out based on these data, b) in essing the risk, using the availa v to apply interpolation or extragations in the mixture. Se with Regulation (EU) No. 1 SISTOT SE (narcosis) 3:H336 A Classification of the mixture Flam. Liq. 3:H226 c) STOT SE (narcosis) 3:H336 of EUH066 c)	E: e followin the abse ble data f polation te 272/2002 quatic Ch Cat. Cat.3 Cat.3 Cat.3	g principles: a) when da nce of data (tests) for mix or mixtures similarly class echniques, methods are u <u>8~2021/849 (CLP):</u> ronic 3:H412 EUH066 Routes of exposure	ta (tests) for the class stures are generally u sified, and c) in the a used to classify risk a Target organs - CNS	sification of mixtures a used interpolation or absence of tests and issessment based on t Effects
CTIO	NPS pharma N 2 : HAZARDS IDENTI CLASSIFICATION C Classification of mixtu available, generally is available, generally is extrapolation methods information which would at of the individual of Classification in accord WARNING:Flam. Liq. Danger class Physicochemical: Human health: Environment: Full text of hazard state Note: When in section Note:	Acist du FICATI DF THE res is c carried s of asse ild allow compone ordance 3:H226 (C F E E E tements 13 a rar	Aquatic Chronic 3:H412 c)	E: e followin the abse ble data f polation te 272/2000 quatic Ch Cat. Cat.3 - Cat.3 - Cat.3 on 16. health an	g principles: a) when da nce of data (tests) for mix or mixtures similarly class echniques, methods are u 8~2021/849 (CLP): ronic 3:H412 EUH066 Routes of exposure - Inhalation Skin -	ta (tests) for the class ktures are generally u sified, and c) in the a used to classify risk a Target organs - CNS Skin -	sification of mixtures a used interpolation or absence of tests and issessment based on t Effects - Narcosis Dryness, Crackin -
CTIO	NPS pharma N 2 : HAZARDS IDENTI CLASSIFICATION C Classification of mixtu available, generally is available, generally is extrapolation methods information which would at of the individual of Classification in accord WARNING:Flam. Liq. Danger class Physicochemical: Human health: Environment: Full text of hazard state Note: When in section Note:	Acist du FICATI DF THE res is c carried s of asse id allow ordance 3:H226 0 0 0 0 0 0 0 0 0 0 0 0 0	Aquatic Chronic 3:H412 c) s mentioned is indicated in section arried out in accordance with the out based on these data, b) in essing the risk, using the availa v to apply interpolation or extrag- nents in the mixture. The with Regulation (EU) No. 1 b)STOT SE (narcosis) 3:H336 A Classification of the mixture Flam. Liq. 3:H226 c) STOT SE (narcosis) 3:H336 c EUH066 c) Aquatic Chronic 3:H412 c) as mentioned is indicated in section	E: e followin the abse ble data f polation te 272/2002 quatic Ch Cat. Cat.3 Cat.3 Cat.3 on 16. health an alue.	g principles: a) when da nce of data (tests) for mix or mixtures similarly class echniques, methods are u 8~2021/849 (CLP): ronic 3:H412 EUH066 Routes of exposure - Inhalation Skin -	ta (tests) for the class attures are generally u sified, and c) in the a used to classify risk a Target organs - CNS Skin -	sification of mixtures a used interpolation or absence of tests and issessment based on t Effects - Narcosis Dryness, Crackir - of the highest
CTIO	Image pharma Image pharma <td>Acist du FICATI DF THE res is c carried s of assi- ald allow compon ordance 3:H226 () () ()) ()) ()) ())) ())) ())) ()))))))))))))</td> <td>Arried out in accordance with the lout based on these data, b) in essing the risk, using the availa v to apply interpolation or extrag- nents in the mixture. We with Regulation (EU) No. 1 STOT SE (narcosis) 3:H336[A Classification of the mixture Flam. Liq. 3:H226 c) STOT SE (narcosis) 3:H336 c EUH066 c) Aquatic Chronic 3:H412 c) is mentioned is indicated in section in the formation of the maximum v This product is lab</td> <td>E: e followin the abse ble data f polation te 272/2002 quatic Ch Cat. Cat.3 Cat.3 Cat.3 on 16. health an alue.</td> <td>g principles: a) when da nce of data (tests) for mix or mixtures similarly class echniques, methods are u 8~2021/849 (CLP): ronic 3:H412 EUH066 Routes of exposure - Inhalation Skin -</td> <td>ta (tests) for the class attures are generally u sified, and c) in the a used to classify risk a Target organs - CNS Skin -</td> <td>sification of mixtures a used interpolation or absence of tests and issessment based on t Effects - Narcosis Dryness, Crackir - of the highest</td>	Acist du FICATI DF THE res is c carried s of assi- ald allow compon ordance 3:H226 () () ()) ()) ()) ())) ())) ())) ()))))))))))))	Arried out in accordance with the lout based on these data, b) in essing the risk, using the availa v to apply interpolation or extrag- nents in the mixture. We with Regulation (EU) No. 1 STOT SE (narcosis) 3:H336[A Classification of the mixture Flam. Liq. 3:H226 c) STOT SE (narcosis) 3:H336 c EUH066 c) Aquatic Chronic 3:H412 c) is mentioned is indicated in section in the formation of the maximum v This product is lab	E: e followin the abse ble data f polation te 272/2002 quatic Ch Cat. Cat.3 Cat.3 Cat.3 on 16. health an alue.	g principles: a) when da nce of data (tests) for mix or mixtures similarly class echniques, methods are u 8~2021/849 (CLP): ronic 3:H412 EUH066 Routes of exposure - Inhalation Skin -	ta (tests) for the class attures are generally u sified, and c) in the a used to classify risk a Target organs - CNS Skin -	sification of mixtures a used interpolation or absence of tests and issessment based on t Effects - Narcosis Dryness, Crackir - of the highest
CTIO	Image pharma Image pharma <td>Acist du FICATI DF THE res is c carried s of assi- ald allow compon ordance 3:H226 () () ()) ()) ()) ())) ())) ()))))))))))))</td> <td>Arried out in accordance with the lout based on these data, b) in essing the risk, using the availa v to apply interpolation or extragaents in the mixture. This product is indicated in section of the mixture of percentages is used, the next of percentages is used, the nent, but below the maximum v This product is lab 1272/2008~2021/8</td> <td>E: e followin ble data f polation te 272/2000 quatic Ch Cat. Cat.3 Cat.3 Cat.3 cat.3 on 16. health an alue. elled with 349 (CLP)</td> <td>g principles: a) when da nce of data (tests) for mix or mixtures similarly class echniques, methods are u 8~2021/849 (CLP): ronic 3:H412 EUH066 Routes of exposure - Inhalation Skin -</td> <td>ta (tests) for the class attures are generally u sified, and c) in the a used to classify risk a Target organs - CNS Skin -</td> <td>sification of mixtures a used interpolation or absence of tests and issessment based on t Effects - Narcosis Dryness, Crackir - of the highest</td>	Acist du FICATI DF THE res is c carried s of assi- ald allow compon ordance 3:H226 () () ()) ()) ()) ())) ())) ()))))))))))))	Arried out in accordance with the lout based on these data, b) in essing the risk, using the availa v to apply interpolation or extragaents in the mixture. This product is indicated in section of the mixture of percentages is used, the next of percentages is used, the nent, but below the maximum v This product is lab 1272/2008~2021/8	E: e followin ble data f polation te 272/2000 quatic Ch Cat. Cat.3 Cat.3 Cat.3 cat.3 on 16. health an alue. elled with 349 (CLP)	g principles: a) when da nce of data (tests) for mix or mixtures similarly class echniques, methods are u 8~2021/849 (CLP): ronic 3:H412 EUH066 Routes of exposure - Inhalation Skin -	ta (tests) for the class attures are generally u sified, and c) in the a used to classify risk a Target organs - CNS Skin -	sification of mixtures a used interpolation or absence of tests and issessment based on t Effects - Narcosis Dryness, Crackir - of the highest
CTIO	Image pharma Image pharma <td>Acist du FICATI DF THE res is c carried of assa- ild allow compon ordance 3:H226 () () () ()) ()) ()) () ())) ())) ())) ())) ())) ()))))))))))))</td> <td>Arried out in accordance with the lout based on these data, b) in essing the risk, using the availa v to apply interpolation or extragaents in the mixture. This product is lab large of percentages is used, the next of percentages is used, the next of percentages is used, the nent, but below the maximum v This product is lab 1272/2008~2021/8</td> <td>E: e followin the abse ble data f polation te 272/2002 quatic Ch Cat. Cat.3 Cat.3 Cat.3 Cat.3 on 16. health an alue. elled with 349 (CLP)</td> <td>g principles: a) when da nce of data (tests) for mix or mixtures similarly class echniques, methods are u 8~2021/849 (CLP): ronic 3:H412 EUH066 Routes of exposure - Inhalation Skin -</td> <td>ta (tests) for the class attures are generally u sified, and c) in the a used to classify risk a Target organs - CNS Skin -</td> <td>sification of mixtures a used interpolation or absence of tests and issessment based on t Effects - Narcosis Dryness, Crackir - of the highest</td>	Acist du FICATI DF THE res is c carried of assa- ild allow compon ordance 3:H226 () () () ()) ()) ()) () ())) ())) ())) ())) ())) ()))))))))))))	Arried out in accordance with the lout based on these data, b) in essing the risk, using the availa v to apply interpolation or extragaents in the mixture. This product is lab large of percentages is used, the next of percentages is used, the next of percentages is used, the nent, but below the maximum v This product is lab 1272/2008~2021/8	E: e followin the abse ble data f polation te 272/2002 quatic Ch Cat. Cat.3 Cat.3 Cat.3 Cat.3 on 16. health an alue. elled with 349 (CLP)	g principles: a) when da nce of data (tests) for mix or mixtures similarly class echniques, methods are u 8~2021/849 (CLP): ronic 3:H412 EUH066 Routes of exposure - Inhalation Skin -	ta (tests) for the class attures are generally u sified, and c) in the a used to classify risk a Target organs - CNS Skin -	sification of mixtures a used interpolation or absence of tests and issessment based on t Effects - Narcosis Dryness, Crackir - of the highest
CTIO	Image pharma Image pharma <td>Acist du FICATI DF THE res is c carried of assa id allow compon ordance 3:H226 (0 0 0 0 0 0 0 0 0 0 0 0 0</td> <td>Arried out in accordance with the lout based on these data, b) in essing the risk, using the availa v to apply interpolation or extragaents in the mixture. This product is indicated in section of the mixture of percentages is used, the next of percentages is used, the nent, but below the maximum v This product is lab 1272/2008~2021/8</td> <td>E: e followin the abse ble data f polation te 272/2000 quatic Ch Cat. Cat.3 Cat.3 Cat.3 Cat.3 on 16. health an alue. elled with 349 (CLP)</td> <td>g principles: a) when da nce of data (tests) for mix or mixtures similarly class echniques, methods are u 8~2021/849 (CLP): ronic 3:H412 EUH066 Routes of exposure - Inhalation Skin -</td> <td>ta (tests) for the class attures are generally u sified, and c) in the a used to classify risk a Target organs - CNS Skin -</td> <td>sification of mixtures a used interpolation or absence of tests and issessment based on t Effects - Narcosis Dryness, Crackir - of the highest</td>	Acist du FICATI DF THE res is c carried of assa id allow compon ordance 3:H226 (0 0 0 0 0 0 0 0 0 0 0 0 0	Arried out in accordance with the lout based on these data, b) in essing the risk, using the availa v to apply interpolation or extragaents in the mixture. This product is indicated in section of the mixture of percentages is used, the next of percentages is used, the nent, but below the maximum v This product is lab 1272/2008~2021/8	E: e followin the abse ble data f polation te 272/2000 quatic Ch Cat. Cat.3 Cat.3 Cat.3 Cat.3 on 16. health an alue. elled with 349 (CLP)	g principles: a) when da nce of data (tests) for mix or mixtures similarly class echniques, methods are u 8~2021/849 (CLP): ronic 3:H412 EUH066 Routes of exposure - Inhalation Skin -	ta (tests) for the class attures are generally u sified, and c) in the a used to classify risk a Target organs - CNS Skin -	sification of mixtures a used interpolation or absence of tests and issessment based on t Effects - Narcosis Dryness, Crackir - of the highest
CTIO	Image pharma DN 2 : HAZARDS IDENTI CLASSIFICATION C Classification of mixtu available, generally is available, generally is extrapolation methods information which wouldata of the individual of Classification in accor WARNING:Flam. Liq. Danger class Physicochemical: Human health: Environment: Full text of hazard state Note: When in section concentration of each LABEL ELEMENTS: - Hazard statements H226 H336 H412 EUH066 - Precautionary state	Acist du FICATI DF THE res is c carried of asse uld allow compon ordanc 3:H226 (Aquatic Chronic 3:H412 c) s mentioned is indicated in section arriage of percentages is used, the nent, but below the maximum v This product is lab 1272/2008~2021/8 mable liquid and vapour. cause drowsiness or dizziness multicause drowsin	E: e followin the abse ble data f polation te 272/2003 quatic Ch Cat. Cat.3 Cat.3 Cat.3 on 16. health an alue. elled with 349 (CLP)	g principles: a) when da nce of data (tests) for mix or mixtures similarly class echniques, methods are u 8~2021/849 (CLP): ronic 3:H412 EUH066 Routes of exposure - Inhalation Skin - d environmental hazards the signal word WARNIN ,	ta (tests) for the class attures are generally u sified, and c) in the a used to classify risk a Target organs - CNS Skin -	sification of mixtures a used interpolation or absence of tests and issessment based on t Effects - Narcosis Dryness, Crackir - of the highest
ECTIO 2.1	Image pharma Image pharma <td>Acist du FICATI DF THE res is c carried of assed ald allow compon ordanc 3:H226 (</td> <td>Aquatic Chronic 3:H412 c) s mentioned is indicated in section arriage of percentages is used, the next but below the maximum v This product is lab 1272/2008~2021/8 mable liquid and vapour. recuse drowsiness or dizziness multiple solution of the mixture of the s mentioned is indicated in section and the solution of the maximum v This product is lab 1272/2008~2021/8 mable liquid and vapour. recuse drowsiness or dizziness multiple solution of the solution s mentioned is indicated in section the solution of the maximum v This product is lab 1272/2008~2021/8 multiple solution of the solution and the solution of the solution to aquatic life with long last recated exposure may cause skir</td> <td>E: e followin the abse ble data f polation te 272/2003 quatic Ch Cat. Cat.3 Cat.3 Cat.3 on 16. health an alue. elled with 349 (CLP) ing effect o dryness</td> <td>g principles: a) when da nce of data (tests) for mix or mixtures similarly class echniques, methods are u 8~2021/849 (CLP): ronic 3:H412 EUH066 Routes of exposure - Inhalation Skin - d environmental hazards the signal word WARNIN ,</td> <td>ta (tests) for the class attures are generally u sified, and c) in the a used to classify risk a Target organs - CNS Skin -</td> <td>sification of mixtures a used interpolation or absence of tests and issessment based on the Effects - Narcosis Dryness, Crackin -</td>	Acist du FICATI DF THE res is c carried of assed ald allow compon ordanc 3:H226 (Aquatic Chronic 3:H412 c) s mentioned is indicated in section arriage of percentages is used, the next but below the maximum v This product is lab 1272/2008~2021/8 mable liquid and vapour. recuse drowsiness or dizziness multiple solution of the mixture of the s mentioned is indicated in section and the solution of the maximum v This product is lab 1272/2008~2021/8 mable liquid and vapour. recuse drowsiness or dizziness multiple solution of the solution s mentioned is indicated in section the solution of the maximum v This product is lab 1272/2008~2021/8 multiple solution of the solution and the solution of the solution to aquatic life with long last recated exposure may cause skir	E: e followin the abse ble data f polation te 272/2003 quatic Ch Cat. Cat.3 Cat.3 Cat.3 on 16. health an alue. elled with 349 (CLP) ing effect o dryness	g principles: a) when da nce of data (tests) for mix or mixtures similarly class echniques, methods are u 8~2021/849 (CLP): ronic 3:H412 EUH066 Routes of exposure - Inhalation Skin - d environmental hazards the signal word WARNIN ,	ta (tests) for the class attures are generally u sified, and c) in the a used to classify risk a Target organs - CNS Skin -	sification of mixtures a used interpolation or absence of tests and issessment based on the Effects - Narcosis Dryness, Crackin -
ECTIO 2.1	Pharma DN 2 : HAZARDS IDENTI CLASSIFICATION C Classification of mixtu available, generally is extrapolation methods information which wou data of the individual of Classification in acco WARNING:Flam. Liq. Danger class Physicochemical: Human health: Environment: Full text of hazard state Note: When in section concentration of each LABEL ELEMENTS: - Hazard statements H226 H336 H412 EUH066 - Precautionary state P260 P262 P301+P310-P331	Acist du FICATI DF THE res is c carried of assed ald allow componential ordance 3:H2266 (Aquatic Chronic 3:H412 c) s mentioned is indicated in section arriage of percentages is used, the next but below the maximum v to apply interpolation or extrag- tents in the mixture. the with Regulation (EU) No. 1 approximation of the mixture Flam. Liq. 3:H226 c) STOT SE (narcosis) 3:H336 c EUH066 c) Aquatic Chronic 3:H412 c) as mentioned is indicated in section and percentages is used, the nent, but below the maximum v This product is lab 1272/2008~2021/8 mable liquid and vapour. to cause drowsiness or dizziness mult to aquatic life with long last eated exposure may cause skir to breathe dust/fume/gas/mist/v ot get in eyes, on skin, or on clow WALLOWED: Immediately call a	E: e followin the abse ble data f polation te 272/2003 quatic Ch Cat. Cat.3 Cat.3 Cat.3 on 16. health an alue. elled with 349 (CLP) ing effect n dryness rapours/s pothing. a POISON	g principles: a) when da nce of data (tests) for mix or mixtures similarly class echniques, methods are u 8~2021/849 (CLP): ronic 3:H412 EUH066 Routes of exposure Inhalation Skin d environmental hazards the signal word WARNIN s. or cracking. pray.	ta (tests) for the class xtures are generally u sified, and c) in the a lsed to classify risk a Target organs - CNS Skin - s describe the effects NG in accordance wit	sification of mixtures a used interpolation or absence of tests and issessment based on t Effects - Narcosis Dryness, Crackir - of the highest th Regulation (EU) No.
ectio	Pharma DN 2 : HAZARDS IDENTI CLASSIFICATION C Classification of mixtu available, generally is extrapolation methods information which wou data of the individual of Classification in acco WARNING:Flam. Liq. Danger class Physicochemical: Human health: Environment: Full text of hazard state Note: When in section concentration of each LABEL ELEMENTS: + Hazard statements H226 H336 H412 EUH066 - Precautionary state P260 P262	Acist du FICATI DF THE res is c carried of assuid allow compon ordance 3:H2266 () () ())) ())) ())) ()))))))))))))	Aquatic Chronic 3:H412 c) s mentioned is indicated in section arriage of percentages is used, the next but below the maximum v to apply interpolation or extrag- tents in the mixture. the with Regulation (EU) No. 1 apply interpolation or extrag- tents in the mixture. This product is lab 1272/2008~2021/8 mable liquid and vapour. to cause drowsiness or dizziness multiple with long last eated exposure may cause skir to breathe dust/fume/gas/mist/v ot get in eyes, on skin, or on clo	E: e followin the abse ble data f polation te 272/2003 quatic Ch Cat. Cat.3 Cat.3 Cat.3 on 16. health an alue. elled with 349 (CLP) ing effect n dryness rapours/s pothing. a POISON	g principles: a) when da nce of data (tests) for mix or mixtures similarly class echniques, methods are u 8~2021/849 (CLP): ronic 3:H412 EUH066 Routes of exposure Inhalation Skin d environmental hazards the signal word WARNIN s. or cracking. pray.	ta (tests) for the class xtures are generally u sified, and c) in the a lsed to classify risk a Target organs - CNS Skin - s describe the effects NG in accordance wit	sification of mixtures a used interpolation or absence of tests and issessment based on t Effects - Narcosis Dryness, Crackir - of the highest th Regulation (EU) No.
	Pharma DN 2 : HAZARDS IDENTI CLASSIFICATION C Classification of mixtu available, generally is extrapolation methods information which wou data of the individual of Classification in acco WARNING:Flam. Liq. Danger class Physicochemical: Human health: Environment: Full text of hazard state Note: When in section concentration of each LABEL ELEMENTS: - Hazard statements H226 H336 H412 EUH066 - Precautionary state P260 P262 P301+P310-P331 P101 P102 P210	Acist du FICATI DF THE res is c carried of assuld allov compon ordance 3:H2266 () () ()) ())) ())) ())))) ()))))))))))))	Aquatic Chronic 3:H412 c) arried of percentages is used, the nent, but below the maximum v This product is lab 1272/2008~2021/8 mable liquid and vapour. cause drowsiness or dizziness must be availed and vapour or extragents in the mixture. This product is lab 1272/2008~2021/8 mable liquid and vapour. cause drowsiness or dizziness must be availed and vapour. to the availed and vapour. to avay from heat, hot surfaces, to ut of reach of children. to away from heat, hot surfaces,	E: e followin the abse ble data f polation te 272/2003 quatic Ch Cat.3 Cat.3 Cat.3 Cat.3 on 16. health an alue. elled with 349 (CLP) ing effect n dryness apours/s othing. a POISON oduct cor sparks, o	g principles: a) when da nce of data (tests) for mix or mixtures similarly class echniques, methods are u 8~2021/849 (CLP): ronic 3:H412 EUH066 Routes of exposure Inhalation Skin d environmental hazards the signal word WARNIN s. or cracking. pray.	ta (tests) for the class xtures are generally u sified, and c) in the a used to classify risk a Target organs - CNS Skin - s describe the effects NG in accordance with NOT induce vomiting ition sources. No sm	sification of mixtures a used interpolation or absence of tests and issessment based on t Effects - Narcosis Dryness, Crackir - of the highest th Regulation (EU) No.
ECTIO 2.1	Phazard statements Hazard statements <	Acist du FICATI DF THE res is c carried of assuld allov compon ordance 3:H226 ()) ()) () ()) ()) () ()) ()) ())) ())) ())) ())) ())) ()) ())) ())) ())))	Aquatic Chronic 3:H412 c) arrent but below the maximum v arriad out in accordance with the lout based on these data, b) in essing the risk, using the availa v to apply interpolation or extrag- tents in the mixture. the with Regulation (EU) No. 1 STOT SE (narcosis) 3:H336[A Classification of the mixture Flam. Liq. 3:H226 c) STOT SE (narcosis) 3:H336 c EUH066 c) Aquatic Chronic 3:H412 c) as mentioned is indicated in section age of percentages is used, the nent, but below the maximum v This product is lab 1272/2008~2021/8 mable liquid and vapour. accuse drowsiness or dizziness mful to aquatic life with long last eated exposure may cause skir to to breathe dust/fume/gas/mist/v ot get in eyes, on skin, or on cla WALLOWED: Immediately call ac adical advice is needed, have pro- po out of reach of children.	E: e followin the abse ble data f polation te 272/2003 quatic Ch Cat. Cat.3 Cat.3 cat.3 cat.3 on 16. health an alue. elled with 349 (CLP)	g principles: a) when da nce of data (tests) for mix or mixtures similarly class echniques, methods are u 8~2021/849 (CLP): ronic 3:H412 EUH066 Routes of exposure Inhalation Skin d environmental hazards the signal word WARNIN s. or cracking. pray. N CENTER or doctor. Do ntainer or label at hand. pen flames and other ign ection. In case of inadequ	ta (tests) for the class attures are generally u sified, and c) in the a used to classify risk a Target organs - CNS Skin - - - - - - - - - - - - -	sification of mixtures a used interpolation or absence of tests and issessment based on t Effects - Narcosis Dryness, Crackir - of the highest th Regulation (EU) No.

SAFETY DATA SHEET (REACH) In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2020/878

	isaval	BRISA_BARNIZ INTERIOR-	EXTERIOR SATINADO	
	pinturas	Code : 12161		
ersion	:6 Re	vision: 14/12/2022	Previous revision: 23/02/2022	Date of printing: 14/12/202
	P273-P501 <u>- Supplementary sta</u>		nent. Dispose of contents/container in accordance	with local regulations.
		ontribute to classification: 1, n-alkanes, isoalkanes, cyclic	s, <2% aromatics	
2.3	OTHER HAZARDS:			
	Hazards which do not	result in classification but which	h may contribute to the overall hazards of the mixtu	ıre:
	- Other physicocher	nical hazards:		
	Vapours may form w	ith air a mixture potentially flamr	mable or explosive.	
	- Other adverse hun		•	
		erse effects are known.		
	- Other negative env			
	· · · · · · · · · · · · · · · · · · ·	stances that fulfil the PBT/vPvB	critoria	
	Endocrine disrupting		cintena.	
			ring diarupting properties identified or under evolue	ation
	•	FORMATION ON INGREDIENT	rine disrupting properties identified or under evalua	
3.1	SUBSTANCES:	FORMATION ON INGREDIENT	5	
5.1	Not applicable (mixtur	(c)		
	MIXTURES:	e).		
3.2				
	This product is a mixt			
	Chemical descriptio			
		esins and additives in organic s	olvents.	
	HAZARDOUS ING			
		rt in a percentage higher than th		
	25 < C < 30 %	CAS: 64742-48-9, EC: 919-85	nes, isoalkanes, cyclics, <2% aromatics 7-5, REACH: 01-2119463258-33 26 STOT SE (narcosis) 3:H336 Asp. Tox.	Autoclassified REACH
F	5 < C < 10 %	CLP: Danger: Flam. Liq. 3:H22	ated heavy 0-3, REACH: 01-2119486659-16 26 Skin Irrit. 2:H315 STOT SE (narcosis) ₁ uatic Chronic 2:H411 EUH066 (Note P)	REACH
Ē	C < 1 %	Zirconium 2-ethylhexanoate		Autoclassified
	*	CAS: 22464-99-9, EC: 245-01 CLP: Warning: Repr. 2:H361	8-1, REACH: 01-2119979088-21	REACH
	Stabilizers:	0.1%.Content of benzene < 0.1	%.Content of benzene < 0.1%.	
	None.			
	Reference to other			
		on hazardous ingredients, see s		
	SUBSTANCES OF	VERY HIGH CONCERN (SV	<u>HC):</u>	
	List updated by ECHA	A on 10/06/2022.		
	Substances SVHC	subject to authorisation, inclu	ded in Annex XIV of Regulation (EC) no. 1907	/2006:
	None.		- · · · ·	
		candidate to be included in A	nnex XIV of Regulation (EC) no. 1907/2006:	
	None. <u>PERSISTENT, BIOA</u> <u>SUBSTANCES:</u>	ACCUMULABLE AND TOXIC	PBT, OR VERY PERSISTENT AND VERY BI	OACCUMULABLE VPVB

Page 2/13

BRISA_BARNIZ INTERIOR- EXTERIOR SATINADO

Page 3/13 (Language:EN)



SECTION 4: FIRST AID MEASURES

Code : 12161

Previous revision: 23/02/2022

Date of printing: 14/12/2022

Version: 6

4.1

Revision: 14/12/2022

DESCRIPTION OF FIRST AID MEASURES:

Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist,

Route of exposure	Symptoms and effects, acute and delayed	Description of first-aid measures
Inhalation:	Inhalation of solvent vapours may produce headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness.	Remove the patient out of the contaminated area fresh air.If breathing is irregular or stops, administ artificial respiration.If the person is unconscious, p appropriate recovery position.Keep the patient wa at rest until medical attention arrives.
Skin:	Prolonged contact may cause skin dryness.	Remove immediately contaminated clothing.Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitabl cleanser.
Eyes:	Contact with the eyes produces redness and pain.	Remove contact lenses.Rinse eyes copiously by irrigation with plenty of clean, fresh water for at lea minutes, holding the eyelids apart, until the irritation reduced.If irritation persists, consult a physician.
Ingestion:	If swallowed, may cause irritation of the throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea.	If swallowed, seek immediate medical attention. D induce vomiting, due to the risk of aspiration.Keep patient at rest.
MOST IMPORTANT	SYMPTOMS AND EFFECTS, BOTH ACUTE AND D	ELAYED:
	and effects are indicated in sections 4.1 and 11.1	
INDICATION OF AN	NY IMMEDIATE MEDICAL ATTENTION AND SPECIAL	<u>L TREATMENT NEEDED:</u>
Notes to physician:		
	directed at the control of symptoms and the clinical condition	n of the patient
Antidotes and contra		
Specific antidote not		
N 5: FIREFIGHTING ME		
EXTINGUISHING M	<u>IEDIA:)</u>	
Extinguishing powder	or CO2.	
	S ARISING FROM THE SUBSTANCE OR MIXTURE:	
dioxide.Exposure to c	ombustion or thermal decomposition, hazardous products m ombustion or decomposition products may be a hazard to h	
ADVICE FOR FIRE		
Special protective e		
protective glasses or	ude of fire, heat-proof protective clothing may be required, a face masks and boots.If the fire-proof protective equipment rom a safe distance.The standard EN469 provides a basic I	is not available or is not being used, combat fire from
Other recommendat	tions:	
<u>Other recommendation</u>	nks, cisterns or containers close to sources of heat or fire.B	ear in mind the direction of the wind.Do not allow fir
Cool with water the ta	er drains, sewers or water courses.	
Cool with water the ta	er drains, sewers or water courses.	

isaval

Version: 6

BRISA_BARNIZ INTERIOR- EXTERIOR SATINADO Ċ Code : 12161 Previous revision: 23/02/2022 Revision: 14/12/2022 Date of printing: 14/12/2022

DENTAL RELEASE MEASURES DNAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES: te opssible sources of ignition and when appropriate, ventilate the area. Do not smoke Avoid direct contact with this product. Avoid grapours, Keep people without protection in opposition to the wind direction. ONMENTAL PRECAUTIONS; ONMENTAL PRECAUTIONS; DNALIPRECAUTIONS; DNALIPRECAUTIONS; DNATERIAL FOR CONTAINMENT AND CLEANING UP; and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc). Clean preferably iodegradable detergent. Keep the remains in a closed container. ENCE TO OTHER SECTIONS; tact information in case of emergency, see section 1. rmation on safe handling, see section 7. csure controls and personal protection measures, see section 8. te disposal, follow the recommendations in section 13. DLING AND STORAGE UTIONS FOR SAFE HANDLING; with the existing legislation on health and safety at work. raf recommendations; ny type of leakage or escape. Keep the container tightly closed. mmendations for the prevention of fire and explosion risks; are heavier than ali, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reac gnition sources of ignition have been excluded and away from other heat or electrical sources.Switch mobile phones off and do no No tools with a potential for sparks should be used. int 38* °C CLP 2.6.4.3. tion temperature: Not applicable. mmendations for the prevention of fixe and explosion risks; as, ewise section 8. mmendations for the prevention of toxicological risks; as, ewise excline 8. mmendations for the prevention of toxicological risks; as the havier than ali, may should be used. int 38* °C CLP 2.6.4.3. tion temperature: Not applicable. mmendations for the prevention of toxicological risks; as, ewise excline 8. mmendations for the prevention of toxicological risks; as, ewise excline 8. mmendations for the prevention of toxicological risks; as, ewise excline 8. mmendations for the preve
e possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product. Avoid grapours. Keep people without protection in opposition to the wind direction. ONMENTAL PRECAUTIONS: ONMENTAL PRECAUTIONS: DDS AND MATERIAL FOR CONTAINMENT AND CLEANING UP: and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc). Clean preferably iodegradable detergent. Keep the remains in a closed container. RENCE TO OTHER SECTIONS: tact information in case of emergency, see section 1. rmation on safe handling, see section 7. oscure controls and personal protection measures, see section 8. te disposal, follow the recommendations in section 13. DLING AND STORAGE AUTIONS FOR SAFE HANDLING: with the existing legislation on health and safety at work. rail recommendations for the prevention of fire and explosion risks: as are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reac grittion sources of ginition have been excluded and away from other heat or electrical sources.Switch mobile phones off and on or bo tools with a potential for sparks should be used. int 38* °C CLP 2.6.4.3. tot applicable. mmendations for the prevention of toxicological risks: as a election 8. ted, drink or smoke while handling, After handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. ted, drink or smoke while handling, After handling, wash hands with soap and water. For exposure controls and personal protection text is see as a cleaner to the prevention of for xicological risks: as a election for the prevention of toxicological risks: as at, drink or smoke while handling, After handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. mmendations for the prevention of environmental contamination: considered a danger to the environment. In the casse of accidental spillage, follow
Ig vapours.Keep people without protection in opposition to the wind direction. ONMENTAL PRECAUTIONS: ontamination of drains, surface or subterranean water and soil.In the case of large scale spills or when the product contaminates vers or sewages, inform the appropriate authorities in accordance with local regulations. DDS AND MATERIAL FOR CONTAINMENT AND CLEANING UP: and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc). Clean preferably iodegradable detergent. Keep the remains in a closed container. RENCE TO OTHER SECTIONS: tact information in case of emergency, see section 1. mation on safe handling, see section 7. oscure controls and personal protection measures, see section 8. te disposal, follow the recommendations in section 73. DLING AND STORAGE MUTIONS FOR SAFE HANDLING: with the existing legislation on health and safety at work. ral recommendations: ny type of leakage or escape.Keep the container tightly closed. mmendations for the prevention of fine and explosion risks: are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reac gnition sources and flame up or explode.Due to its flammability, this material should only be used in areas from which all naked d other sources of ignition have been excluded and away from other heat or electrical sources.Switch mobile phones off and on ov to tools with a potential for sparks should be used. int 38* °C CLP 2.6.4.3. tion temperature: Not applicable. mmendations for the prevention of nexicological risks: as d, drink or smoke while handling.After handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. mmendations for the prevention of environmental contamination: considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6. TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES;
ONNENTAL PRECAUTIONS: ontamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates vers or sewages, inform the appropriate authorities in accordance with local regulations. DDS AND MATERIAL FOR CONTAINMENT AND CLEANING UP: and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc). Clean preferably iodegradable detergent. Keep the remains in a closed container. RENCE TO OTHER SECTIONS: tact information in case of emergency, see section 1. transition on safe handling, see section 7. osure controls and personal protection measures, see section 8. te disposal, follow the recommendations in section 13. DLING AND STORAGE AUTIONS FOR SAFE HANDLING: with the existing legislation on health and safety at work. call recommendations: ny type of leakage or escape.Keep the container tightly closed. mmendations for the prevention of fire and explosion risks: as are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reac gnition sources of ignition have been excluded and away from other heat or electrical sources.Switch mobile phones off and do no to tools with a potential for sparks should be used. int 38* °C CLP 2.6.4.3. ition temperature: Not applicable. m
nontamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates vers or sewages, inform the appropriate authorities in accordance with local regulations. DDS AND MATERIAL FOR CONTAINMENT AND CLEANING UP: and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc). Clean preferably iodegradable detergent. Keep the remains in a closed container. EENCE TO OTHER SECTIONS: tact information in case of emergency, see section 1. mation on safe handling, see section 7. osure controls and personal protection measures, see section 8. te disposal, follow the recommendations in section 13. DLING AND STORAGE UTIONS FOR SAFE HANDLING: with the existing legislation on health and safety at work. ral recommendations: ny type of leakage or escape.Keep the container tightly closed. mmendations for the prevention of fire and explosion risks: a are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reac gnition sources and flame up or explode.Due to its flammability, this material should only be used in areas from which all naked id other sources of ignition have been excluded and away from other heat or electrical sources.Switch mobile phones off and do no vo tools with a potential for sparks should be used. int
vers or sewages, inform the appropriate authorities in accordance with local regulations. DDS AND MATERIAL FOR CONTAINMENT AND CLEANING UP: and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc). Clean preferably iodegradable detergent. Keep the remains in a closed container. RENCE TO OTHER SECTIONS: tact information in case of emergency, see section 1. rmation on safe handling, see section 7. osure controls and personal protection measures, see section 8. te disposal, follow the recommendations in section 13. DLING AND STORAGE UUTIONS FOR SAFE HANDLING: with the existing legislation on health and safety at work. ral recommendations: ny type of leakage or escape. Keep the container tightly closed. mmendations for the prevention of fire and explosion risks: a are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reac gnition sources of ignition have been excluded and away from other heat or electrical sources.Switch mobile phones off and do no No tools with a potential for sparks should be used. int 38* °C CLP 2.6.4.3. tion temperature: Not applicable. mmendations for the prevention of fixe handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. mmendations for the prevention of environmental contamination: considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6. TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
DDS AND MATERIAL FOR CONTAINMENT AND CLEANING UP: and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc). Clean preferably iodegradable detergent. Keep the remains in a closed container. ENCE TO OTHER SECTIONS: tact information in case of emergency, see section 1. rmation on safe handling, see section 7. osure controls and personal protection measures, see section 8. te disposal, follow the recommendations in section 13. DLING AND STORAGE AUTIONS FOR SAFE HANDLING: with the existing legislation on health and safety at work. ral recommendations: ny type of leakage or escape. Keep the container tightly closed. mmendations for the prevention of fire and explosion risks: s are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reac griltion sources of ingition have been excluded and away from other heat or electrical sources. Switch mobile phones off and do no No tools with a potential for sparks should be used. int 38* °C mendations for the prevention of toxicological risks: eat, drink or smoke while handling. After handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. mendations for the prevention of environmental contami
and mop up spills with non-combustible absorbent materials (earth, sand, verniculite, diatomaceous earth, etc). Clean preferably iodegradable detergent. Keep the remains in a closed container. RENCE TO OTHER SECTIONS: tact information in case of emergency, see section 1. mation on safe handling, see section 7. osure controls and personal protection measures, see section 8. te disposal, follow the recommendations in section 13. DLING AND STORAGE AUTIONS FOR SAFE HANDLING: with the existing legislation on health and safety at work. ral recommendations in success and fine and explosion risks: e are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reac grition sources and finame up or explode. Due to its flammability, this material should only be used in areas from which all naked ad other sources of ignition have been excluded and away from other heat or electrical sources.Switch mobile phones off and do no No tools with a potential for sparks should be used. int
iodegradable detergent. Keep the remains in a closed container. EENCE TO OTHER SECTIONS: tact information in case of emergency, see section 1. rmation on safe handling, see section 7. osure controls and personal protection measures, see section 8. te disposal, follow the recommendations in section 13. DLING AND STORAGE AUTIONS FOR SAFE HANDLING: with the existing legislation on health and safety at work. ral recommendations: ny type of leakage or escape.Keep the container tightly closed. mmendations for the prevention of fire and explosion risks: a are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reac gnition sources and flame up or explode.Due to its flammability, this material should only be used in areas from which all naked rd other sources of ignition have been excluded and away from other heat or electrical sources.Switch mobile phones off and do no No tools with a potential for sparks should be used. int
Render To OTHER SECTIONS: tact information in case of emergency, see section 1. rmation on safe handling, see section 7. osure controls and personal protection measures, see section 8. te disposal, follow the recommendations in section 13. DLING AND STORAGE AUTIONS FOR SAFE HANDLING: with the existing legislation on health and safety at work. ral recommendations: ny type of leakage or escape. Keep the container tightly closed. mmendations for the prevention of fire and explosion risks: a are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reac gnition sources and flame up or explode.Due to its flammability, this material should only be used in areas from which all naked do ther sources of ignition have been excluded and away from other heat or electrical sources.Switch mobile phones off and do no No tools with a potential for sparks should be used. int 38* °C mmendations for the prevention of toxicological risks: aat, drink or smoke while handling.After handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. mmendations for the prevention of environmental contamination: considered a danger to the environment. In the case of accidental spillage, follow the instructions indicat
tact information in case of emergency, see section 1. rmation on safe handling, see section 7. osure controls and personal protection measures, see section 8. te disposal, follow the recommendations in section 13. DLING AND STORAGE AUTIONS FOR SAFE HANDLING: with the existing legislation on health and safety at work. ral recommendations: ny type of leakage or escape.Keep the container tightly closed. mmendations for the prevention of fire and explosion risks: a are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reac gnition sources and flame up or explode.Due to its flammability, this material should only be used in areas from which all naked do ther sources of ignition have been excluded and away from other heat or electrical sources.Switch mobile phones off and do no No tools with a potential for sparks should be used. int
rmation on safe handling, see section 7. osure controls and personal protection measures, see section 8. te disposal, follow the recommendations in section 13. DLING AND STORAGE AUTIONS FOR SAFE HANDLING: with the existing legislation on health and safety at work. ral recommendations: ny type of leakage or escape. Keep the container tightly closed. mmendations for the prevention of fire and explosion risks: s are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reac gnition sources and flame up or explode.Due to its flammability, this material should only be used in areas from which all naked nd other sources of ignition have been excluded and away from other heat or electrical sources.Switch mobile phones off and do no to tools with a potential for sparks should be used. int 38* °C CLP 2.6.4.3. tion temperature: Not applicable. mmendations for the prevention of toxicological risks: eat, drink or smoke while handling.After handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. mmendations for the prevention of environmental contamination: considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6. TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
te disposal, follow the recommendations in section 13.
DLING AND STORAGE AUTIONS FOR SAFE HANDLING: with the existing legislation on health and safety at work. ral recommendations: ny type of leakage or escape.Keep the container tightly closed. mmendations for the prevention of fire and explosion risks: are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reace gnition sources and flame up or explode.Due to its flammability, this material should only be used in areas from which all naked d other sources of ignition have been excluded and away from other heat or electrical sources.Switch mobile phones off and do no to tools with a potential for sparks should be used. int
AUTIONS FOR SAFE HANDLING: with the existing legislation on health and safety at work. ral recommendations: my type of leakage or escape.Keep the container tightly closed. mmendations for the prevention of fire and explosion risks: a re heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reac gnition sources and flame up or explode.Due to its flammability, this material should only be used in areas from which all naked nd other sources of ignition have been excluded and away from other heat or electrical sources.Switch mobile phones off and do no No tools with a potential for sparks should be used. int 38* °C CLP 2.6.4.3. ition temperature: Not applicable. mmendations for the prevention of toxicological risks: eat, drink or smoke while handling.After handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. mmendations for the prevention of environmental contamination: considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6. TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
with the existing legislation on health and safety at work. ral recommendations: my type of leakage or escape.Keep the container tightly closed. mmendations for the prevention of fire and explosion risks: a are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reac gnition sources and flame up or explode.Due to its flammability, this material should only be used in areas from which all naked a other sources of ignition have been excluded and away from other heat or electrical sources.Switch mobile phones off and do no No tools with a potential for sparks should be used. int 38* °C CLP 2.6.4.3. ition temperature: Not applicable. mmendations for the prevention of toxicological risks: eat, drink or smoke while handling.After handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. mmendations for the prevention of environmental contamination: considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6. TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
ral recommendations: my type of leakage or escape.Keep the container tightly closed. mmendations for the prevention of fire and explosion risks: as are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to read gnition sources and flame up or explode.Due to its flammability, this material should only be used in areas from which all naked and other sources of ignition have been excluded and away from other heat or electrical sources.Switch mobile phones off and do not No tools with a potential for sparks should be used. int 38* °C CLP 2.6.4.3. ition temperature: Not applicable. mmendations for the prevention of toxicological risks: eat, drink or smoke while handling.After handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. mmendations for the prevention of environmental contamination: considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6. <u>TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES</u> :
ny type of leakage or escape.Keep the container tightly closed. mmendations for the prevention of fire and explosion risks: a are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reac gnition sources and flame up or explode.Due to its flammability, this material should only be used in areas from which all naked ad other sources of ignition have been excluded and away from other heat or electrical sources.Switch mobile phones off and do no No tools with a potential for sparks should be used. int 38* °C CLP 2.6.4.3. ition temperature: Not applicable. mmendations for the prevention of toxicological risks: eat, drink or smoke while handling.After handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. mmendations for the prevention of environmental contamination: considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6. <u>TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:</u>
mmendations for the prevention of fire and explosion risks: a are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reac gnition sources and flame up or explode.Due to its flammability, this material should only be used in areas from which all naked no other sources of ignition have been excluded and away from other heat or electrical sources.Switch mobile phones off and do no No tools with a potential for sparks should be used. int 38* °C CLP 2.6.4.3. ition temperature: Not applicable. mmendations for the prevention of toxicological risks: eat, drink or smoke while handling.After handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. mmendations for the prevention of environmental contamination: considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6. TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
s are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reac gnition sources and flame up or explode.Due to its flammability, this material should only be used in areas from which all naked no other sources of ignition have been excluded and away from other heat or electrical sources.Switch mobile phones off and do no No tools with a potential for sparks should be used. int 38* °C CLP 2.6.4.3. ition temperature: Not applicable. mmendations for the prevention of toxicological risks: eat, drink or smoke while handling.After handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. mmendations for the prevention of environmental contamination: considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6. <u>TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:</u>
gnition sources and flame up or explode.Due to its flammability, this material should only be used in areas from which all naked other sources of ignition have been excluded and away from other heat or electrical sources.Switch mobile phones off and do no No tools with a potential for sparks should be used. int 38* °C CLP 2.6.4.3. ition temperature: Not applicable. <u>mmendations for the prevention of toxicological risks:</u> eat, drink or smoke while handling.After handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. <u>mmendations for the prevention of environmental contamination:</u> considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6. <u>TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:</u>
nd other sources of ignition have been excluded and away from other heat or electrical sources.Switch mobile phones off and do not not tools with a potential for sparks should be used. int 38* °C CLP 2.6.4.3. ition temperature: Not applicable. <u>mmendations for the prevention of toxicological risks:</u> eat, drink or smoke while handling.After handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. <u>mmendations for the prevention of environmental contamination:</u> considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6. <u>TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:</u>
No tools with a potential for sparks should be used. int 38* °C CLP 2.6.4.3. ition temperature: Not applicable. mmendations for the prevention of toxicological risks: eat, drink or smoke while handling. After handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. mmendations for the prevention of environmental contamination: considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6. <u>TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:</u>
int 38* °C CLP 2.6.4.3. ition temperature: Not applicable. mmendations for the prevention of toxicological risks: eat, drink or smoke while handling.After handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. mmendations for the prevention of environmental contamination: considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6. TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
Not applicable. <u>mmendations for the prevention of toxicological risks:</u> eat, drink or smoke while handling.After handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. <u>mmendations for the prevention of environmental contamination:</u> considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6. <u>TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:</u>
mmendations for the prevention of toxicological risks: eat, drink or smoke while handling.After handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. mmendations for the prevention of environmental contamination: considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6. <u>TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:</u>
eat, drink or smoke while handling. After handling, wash hands with soap and water. For exposure controls and personal protection es, see section 8. <u>mmendations for the prevention of environmental contamination:</u> considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6. <u>TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:</u>
es, see section 8. <u>mmendations for the prevention of environmental contamination:</u> considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6. <u>TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:</u>
mmendations for the prevention of environmental contamination: considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6. TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6. TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
TIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
. Do not smoke in storage area. If possible, avoid direct contact with sunlight. Avoid extreme humidity conditions. In order to avoid s, the containers, after use, should be closed carefully and placed in a vertical position. For more information, see section 10.
of store:
ng to current legislation.
num storage period:
ths
erature interval:
C, max:40 ℃ (recommended).
ipatible materials:
vay from oxidizing agents, acids, peroxides. of packaging:
<u>or packaging.</u> ng to current legislation.
guantity (Seveso III): Directive 2012/18/EU:
licable (product for non industrial use).
FIC END USE(S):
use of this product particular recommendations apart from that already indicated are not available.

	aval	BRISA_BARNIZ INTE Code : 12161	ERIOR- E	EXTERIOR SAT	TINADO				•	
rsion: 6	Revi	sion: 14/12/2022		F	Previous revisi	on: 23/02/2022			Date of prin	ting: 14/12/20
CTION 8: EXP	OSURE CONTRO	OLS/PERSONAL PRO	TECTIC	N						
	ROL PARAMET	TERS:								
effective made to exposu determi	eness of the vent o EN689, EN140 re to chemical ar ination of danger		measur d conce eference	es and/or the n rning methods e should be als	lecessity to ι for assesing	ise respiratory the exposure	protectiv by inhala	/e equij ation to	pment. Refere chemical agei	nce should nts, and
	UPATIONAL EX 2005 WELs (Unite			WEL) WEL-TWA		WEL-STEL			Remarks	
	m) 2018	54	1 Cai	ppm	mg/m3			mg/m3		
	arbons, C9-C11,		-	-	300	-		1370		
	nes, cyclics, <2% a (petroleum), hy		_	100	525			_	 R	ecommend
heavy	a (perolean), ny		_	100	020					coomment
Zirconiu	um 2-ethylhexand	oate	1996	-	5	-		10		
- BIOL	OGICAL LIMIT	VALUES:	-				-			
where t dose ar	there is a reasonand target organ b	bintestinal tract uptake f ably well-defined relation ody burden which is rel	onship b lated to	etween biologi toxicity.	cal monitorin	ig and effect, o	r where			
- <u>- DERI</u> Derived included	VED NO-EFFE d no-effect level (l d in REACH. DN	is the following substan <u>CT LEVEL (DNEL):</u> DNEL) is a level of exp L values may differ fro	oosure th om a oc	nat is considere cupational exp	ed safe, deriv osure limit (C	ved from toxicit DEL) for the sa	y data a me cher	nical. O	EL values may	y come
- Derived include recomm health,	VED NO-EFFE d no-effect level (l d in REACH. DN nended by a part the OEL values a	CT LEVEL (DNEL): DNEL) is a level of exp EL values may differ fro icular company, a gove are derived by a proces	oosure th om a oc ernment ss differe	nat is considere cupational exp regulatory age ent of REACH. DNEL Inhalation	ed safe, deriv osure limit (C ncy or an org	red from toxicit DEL) for the sa ganization of ex	y data a me cher xperts. A	nical. O	EL values may n considered p	y come
- Derivec includer recomm health, - DERIV Systemi	VED NO-EFFE d no-effect level (d in REACH. DN nended by a part the OEL values a 'ED NO-EFFECT L c effects, acute and	CT LEVEL (DNEL): DNEL) is a level of exp EL values may differ fro icular company, a gove are derived by a proces EVEL, WORKERS:- d chronic:	oosure th om a oc ernment ss differe	nat is considered cupational exp regulatory age ent of REACH. <u>DNEL Inhalation</u> mg/m3	ed safe, deriv osure limit (C ncy or an org	ved from toxicit DEL) for the same ganization of e: DNEL Cutaneou mg/kg bw/d	y data a me cher xperts. A <u>Is</u>	nical. C Ithough	EL values may considered p	y come rotective of
- Derivec includer recomm health, - DERIV Systemin Hydroca	VED NO-EFFE d no-effect level (d in REACH. DN nended by a part the OEL values a 'ED NO-EFFECT L c effects, acute and rbons, C9-C11, n-a	CT LEVEL (DNEL): DNEL) is a level of exp EL values may differ fro icular company, a gove are derived by a proces EVEL, WORKERS:-	oosure th om a oc ernment ss differe	nat is considere cupational exp regulatory age ent of REACH. DNEL Inhalation	ed safe, deriv osure limit (C ncy or an org	red from toxicit DEL) for the sa ganization of ex	y data a me cher xperts. A	nical. C Ithough	EL values may n considered p	y come rotective of
- Derivect includer recomm health, - DERIV Systemic Hydroca <2% aro	VED NO-EFFE d no-effect level (d in REACH. DN nended by a parti the OEL values a /ED NO-EFFECT L c effects, acute and arbons, C9-C11, n-a matics	CT LEVEL (DNEL): DNEL) is a level of exp EL values may differ fro icular company, a gove are derived by a proces EVEL, WORKERS:- d chronic: alkanes, isoalkanes, cyclic	oosure th om a oc ernment ss differe	nat is considered cupational exp regulatory age ent of REACH. <u>DNEL Inhalation</u> mg/m3	ed safe, deriv osure limit (C ncy or an org	ved from toxicit DEL) for the same ganization of e: DNEL Cutaneou mg/kg bw/d	y data a me cher xperts. A <u>Is</u>	nical. C Ithough (c)	EL values may considered p	y come rotective of - (c)
- Derivec includer recomm health, - DERIV Systemin Hydroca <2% aro Zirconiu	VED NO-EFFE d no-effect level (d in REACH. DN nended by a parti the OEL values a 'ED NO-EFFECT L c effects, acute and rbons, C9-C11, n-a	CT LEVEL (DNEL): DNEL) is a level of exp EL values may differ fro icular company, a gove are derived by a proces EVEL, WORKERS:- d chronic: alkanes, isoalkanes, cyclic e	oosure th om a oc ernment ss differe	nat is considere cupational exp regulatory age ent of REACH. <u>DNEL Inhalation</u> mg/m3 s/r (a)	ed safe, deriv osure limit (C ncy or an org 1500 (c)	ved from toxicit DEL) for the sai ganization of ex DNEL Cutaneou mg/kg bw/d s/r (a)	y data a me cher kperts. A <u>s</u> 300 15,75	nical. C Ithough (c)	EL values main n considered p DNEL Oral mg/kg bw/d – (a)	y come rotective of - (c) - (c)
- Derivec includer recomm health, - DERIV Systemin Hydroca <2% aro Zirconiun Naphtha - DERIV	VED NO-EFFE d no-effect level (i d in REACH. DN nended by a parti the OEL values a ZED NO-EFFECT L c effects, acute and rbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro ZED NO-EFFECT L	CT LEVEL (DNEL): DNEL) is a level of exp EL values may differ fro icular company, a gove are derived by a proces EVEL, WORKERS:- d chronic: alkanes, isoalkanes, cyclic e	oosure tr om a oc ernment ss differe cs,	nat is considered cupational exp regulatory age ent of REACH. <u>DNEL Inhalation</u> mg/m3 s/r (a) s/r (a)	ed safe, deriv osure limit (C ncy or an org 1500 (c) 5 (c)	ved from toxicit DEL) for the sar ganization of ex DNEL Cutaneou mg/kg bw/d s/r (a) - (a)	y data a me cher kperts. A <u>s</u> 300 15,75 -	nical. C Ithough (c) (c)	EL values main n considered p DNEL Oral mg/kg bw/d - (a) - (a)	y come rotective of - (c) - (c)
- Derivectincluder recomm health, - DERIV Systemin Hydroca <2% aro Zirconiuu Naphtha - DERIV effects, a Hydroca	VED NO-EFFE d no-effect level (i d in REACH. DN nended by a part the OEL values a ZED NO-EFFECT L c effects, acute and arbons, C9-C11, n-a matics m 2-ethylhexanoata a (petroleum), hydro ZED NO-EFFECT L acute and chronic: arbons, C9-C11, n-a	CT LEVEL (DNEL): DNEL) is a level of exp EL values may differ fro icular company, a gove are derived by a proces EVEL, WORKERS:- d chronic: alkanes, isoalkanes, cyclic e otreated heavy	bosure the om a ocernment ss differences cs,	nat is considered cupational exp regulatory age ent of REACH. <u>DNEL Inhalation</u> mg/m3 s/r (a) s/r (a) - (a) <u>DNEL Inhalation</u>	ed safe, deriv osure limit (C ncy or an org 1500 (c) 5 (c)	ved from toxicit DEL) for the sar ganization of ex DNEL Cutaneou mg/kg bw/d s/r (a) - (a) DNEL Cutaneou	y data a me cher kperts. A <u>s</u> 300 15,75 -	nical. C Ithough (c) (c) (c)	EL values main considered p DNEL Oral mg/kg bw/d - (a) - (a) DNEL Eyes	y come rotective of - (c) - (c) - (c)
- - DERI Derivect includer recomm health, - DERIV Systemic Hydroca <2% aro Zirconiuu Naphtha - DERIV effects, a Hydroca <2% aro	VED NO-EFFE d no-effect level (i d in REACH. DN nended by a part the OEL values a ZED NO-EFFECT L c effects, acute and arbons, C9-C11, n-a matics m 2-ethylhexanoata a (petroleum), hydro ZED NO-EFFECT L acute and chronic: arbons, C9-C11, n-a	CT LEVEL (DNEL): DNEL) is a level of exp EL values may differ fro icular company, a gove are derived by a proces EVEL, WORKERS:- d chronic: alkanes, isoalkanes, cyclic e botreated heavy EVEL, WORKERS:- Loca alkanes, isoalkanes, cyclic	oosure th om a oc ernment ss differe cs,	nat is considered cupational exp regulatory age ent of REACH. <u>DNEL Inhalation</u> mg/m3 s/r (a) (a) <u>DNEL Inhalation</u> mg/m3	ed safe, deriv osure limit (C ncy or an org 1500 (c) 5 (c) - (c)	bed from toxicit DEL) for the sal ganization of ex DNEL Cutaneou mg/kg bw/d s/r (a) - (a) - (a) DNEL Cutaneou mg/cm2	y data a me cher kperts. A 300 15,75 - <u>s</u> s/r	nical. C Ithough (c) (c) (c)	EL values main considered p DNEL Oral mg/kg bw/d - (a) - (a) - (a) <u>DNEL Eyes</u> mg/cm2	y come rotective of - (c) - (c) - (c)
- - DERIV Derivect includer recomm health, - DERIV Systemin Hydroca <2% aro Zirconiut Naphtha - DERIV effects, a Hydroca <2% aro Zirconiut Naphtha	VED NO-EFFE d no-effect level (d in REACH. DN nended by a parti the OEL values a TED NO-EFFECT L c effects, acute and arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro TED NO-EFFECT L acute and chronic: arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro	CT LEVEL (DNEL): DNEL) is a level of exp EL values may differ fro icular company, a gove are derived by a proces EVEL, WORKERS:- d chronic: alkanes, isoalkanes, cyclic e botreated heavy EVEL, WORKERS:- Loca alkanes, isoalkanes, cyclic e botreated heavy	bosure tr om a oc ernment cs, differe cs, al	nat is considered cupational exp regulatory age ent of REACH. <u>DNEL Inhalation</u> mg/m3 s/r (a) <u>- (a)</u> <u>DNEL Inhalation</u> mg/m3 s/r (a) s/r (a) - (a)	ed safe, derivosure limit (Concy or an orgon 1500 (c) 5 (c) - (c) s/r (c)	ved from toxicit DEL) for the sar ganization of ex <u>DNEL Cutaneou</u> mg/kg bw/d s/r (a) - (a) <u>DNEL Cutaneou</u> mg/cm2 s/r (a) - (a) - (a) - (a)	y data a me cher kperts. A 300 15,75 - <u>s</u> /r - -	nical. C Ithough (c) (c) (c) (c)	EL values main considered p DNEL Oral mg/kg bw/d - (a) - (a) DNEL Eyes mg/cm2 s / r (a) - (a) - (a)	y come rotective of - (c) - (c) - (c) - (c) - (c)
- - DERIV Derivect includer recomm health, - DERIV Systemin Hydroca <2% aro Zirconiu Naphtha - DERIV effects, a Hydroca <2% aro Zirconiu Naphtha - DERIV aroca	VED NO-EFFE d no-effect level (d in REACH. DN nended by a parti the OEL values a TED NO-EFFECT L c effects, acute and arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro TED NO-EFFECT L acute and chronic: arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro TED NO-EFFECT L	CT LEVEL (DNEL): DNEL) is a level of exp EL values may differ fro icular company, a gove are derived by a proces EVEL, WORKERS:- d chronic: alkanes, isoalkanes, cyclic e btreated heavy EVEL, WORKERS:- Loca alkanes, isoalkanes, cyclic e btreated heavy EVEL, GENERAL	bosure the om a ocernment as differences of the other of the other of the other othe	nat is considered cupational exp regulatory age ent of REACH. DNEL Inhalation mg/m3 s/r (a) (a) DNEL Inhalation mg/m3 s/r (a) s/r (a) s/r (a)	ed safe, deriv osure limit (C ncy or an or 1500 (c) 5 (c) - (c) s/r (c) s/r (c)	ved from toxicit DEL) for the sar ganization of ex DNEL Cutaneou mg/kg bw/d s/r (a) - (a) DNEL Cutaneou mg/cm2 s/r (a) - (a)	y data a me cher kperts. A 300 15,75 - <u>s</u> /r - -	nical. C Ithough (c) (c) (c) (c) (c)	EL values main considered p DNEL Oral mg/kg bw/d - (a) - (a) DNEL Eyes mg/cm2 s/r (a) - (a)	y come rotective of - (c) - (c) - (c) - (c) - (c)
- - DERIV Derivect includer recomm health, - DERIV Systemin Hydroca <2% aro Zirconiuu Naphtha - DERIV effects, a Hydroca <2% aro Zirconiuu Naphtha - DERIV POPULA Hydroca	VED NO-EFFE d no-effect level (i d in REACH. DN nended by a part the OEL values a ED NO-EFFECT L c effects, acute and arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro ED NO-EFFECT L acute and chronic: arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro ED NO-EFFECT L ATION:- Systemic e arbons, C9-C11, n-a	CT LEVEL (DNEL): DNEL) is a level of exp EL values may differ fro icular company, a gove are derived by a proces EVEL, WORKERS:- d chronic: alkanes, isoalkanes, cyclic e botreated heavy EVEL, WORKERS:- Loca alkanes, isoalkanes, cyclic e botreated heavy	bosure the om a ocernment as differences, all cs,	nat is considered cupational exp regulatory age ent of REACH. DNEL Inhalation mg/m3 s/r (a) - (a) DNEL Inhalation mg/m3 s/r (a) s/r (a) - (a) DNEL Inhalation	ed safe, deriv osure limit (C ncy or an or 1500 (c) 5 (c) - (c) s/r (c) s/r (c)	ved from toxicit DEL) for the sar ganization of ex <u>DNEL Cutaneou</u> mg/kg bw/d s/r (a) - (a) <u>DNEL Cutaneou</u> mg/cm2 s/r (a) - (a) - (a) <u>DNEL Cutaneou</u>	y data a me cher kperts. A 300 15,75 - <u>s</u> /r - -	nical. C Ithough (c) (c) (c) (c) (c) (c)	EL values main considered p DNEL Oral mg/kg bw/d - (a) - (a) DNEL Eyes mg/cm2 s/r (a) - (a) - (a) DNEL Eyes	y come rotective of - (c) - (c) - (c) - (c) - (c) - (c)
- - DERIV Derivect includer recomm health, - DERIV Systemin Hydroca <2% aro Zirconiuu Naphtha - DERIV effects, a Hydroca <2% aro Zirconiuu Naphtha - DERIV POPULA Hydroca <2% aro Zirconiuu	VED NO-EFFE d no-effect level (i d in REACH. DN nended by a part the OEL values a ED NO-EFFECT L c effects, acute and arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro ED NO-EFFECT L acute and chronic: arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro ED NO-EFFECT L ATION:- Systemic e arbons, C9-C11, n-a	CT LEVEL (DNEL): DNEL) is a level of exp EL values may differ fro icular company, a gove are derived by a proces EVEL, WORKERS:- d chronic: alkanes, isoalkanes, cyclic e botreated heavy EVEL, WORKERS:- Loca alkanes, isoalkanes, cyclic e botreated heavy EVEL, GENERAL effects, acute and chronic: alkanes, isoalkanes, cyclic	bosure the om a ocernment as differences, all cs,	nat is considered cupational exp regulatory age ent of REACH. <u>DNEL Inhalation</u> mg/m3 s/r (a) - (a) <u>DNEL Inhalation</u> mg/m3 s/r (a) - (a) <u>DNEL Inhalation</u> mg/m3 s/r (a) - (a) <u>DNEL Inhalation</u> mg/m3 s/r (a)	ed safe, derivosure limit (C ncy or an org 1500 (c) 5 (c) - (c) s/r (c) s/r (c) - (c)	ved from toxicit DEL) for the sai ganization of ex <u>DNEL Cutaneou</u> mg/kg bw/d s/r (a) - (a) <u>DNEL Cutaneou</u> mg/cm2 s/r (a) - (a) <u>DNEL Cutaneou</u> mg/kg bw/d s/r (a) - (a)	y data a me cher xperts. A 300 15,75 - - s/r - - - - - - - - - - - - - - - - - - -	nical. C Ithough (c) (c) (c) (c) (c) (c) (c) (c) (c)	EL values main considered p DNEL Oral mg/kg bw/d - (a) - (a) DNEL Eyes mg/cm2 s / r (a) - (a) - (a) DNEL Eyes mg/kg bw/d	y come rotective of - (c) - (c) - (c) - (c) - (c) 300 (c) 7,9 (c)
- - DERIV Derivect includer recomm health, - DERIV Systemin Hydroca <2% aro Zirconiuu Naphtha - DERIV effects, a Hydroca <2% aro Zirconiuu Naphtha - DERIV POPULA Hydroca <2% aro Zirconiuu Naphtha	VED NO-EFFE d no-effect level (d in REACH. DN nended by a parti the OEL values a TED NO-EFFECT L c effects, acute and arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro TED NO-EFFECT L acute and chronic: arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro TED NO-EFFECT L ATION:- Systemic e arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro	CT LEVEL (DNEL): DNEL) is a level of exp EL values may differ fro icular company, a gove are derived by a proces EVEL, WORKERS:- d chronic: alkanes, isoalkanes, cyclic e botreated heavy EVEL, WORKERS:- Loca alkanes, isoalkanes, cyclic e botreated heavy EVEL, GENERAL effects, acute and chronic: alkanes, isoalkanes, cyclic e botreated heavy	bosure the om a ocernment as differences of the other sectors of the oth	nat is considered cupational exp regulatory age ent of REACH. <u>DNEL Inhalation</u> mg/m3 s/r (a) - (a) <u>DNEL Inhalation</u> mg/m3 s/r (a) - (a) <u>DNEL Inhalation</u> mg/m3 s/r (a) - (a) <u>DNEL Inhalation</u> mg/m3 s/r (a) - (a)	ed safe, derivosure limit (C ncy or an org 1500 (c) 5 (c) - (c) s/r (c) s/r (c) - (c) 900 (c)	ved from toxicit DEL) for the sar ganization of ex mg/kg bw/d s/r (a) - (a) - (a) DNEL Cutaneou mg/cm2 s/r (a) - (a) DNEL Cutaneou mg/kg bw/d s/r (a) - (a) - (a) - (a) - (a)	y data a me cher xperts. A 300 15,75 - .s/r - .s/r -	nical. C Ithough (c) (c) (c) (c) (c) (c) (c)	Diversion Diversion <thdiversion< th=""> <thdiversion< th=""> <thd< td=""><td>y come rotective of - (c) - (c) - (c) - (c) - (c) 300 (c) 7,9 (c)</td></thd<></thdiversion<></thdiversion<>	y come rotective of - (c) - (c) - (c) - (c) - (c) 300 (c) 7,9 (c)
- - DERIV Derivect includer recomm health, - DERIV Systemin Hydroca <2% aro Zirconiuu Naphtha - DERIV effects, a Hydroca <2% aro Zirconiuu Naphtha - DERIV POPUL/ Hydroca <2% aro Zirconiuu Naphtha - LOCAL effects, a	VED NO-EFFE d no-effect level (i d in REACH. DN nended by a parti the OEL values a TED NO-EFFECT L c effects, acute and arbons, C9-C11, n-a omatics m 2-ethylhexanoatra (petroleum), hydro TED NO-EFFECT L acute and chronic: arbons, C9-C11, n-a omatics m 2-ethylhexanoatra (petroleum), hydro TED NO-EFFECT L ATION:- Systemic e arbons, C9-C11, n-a omatics m 2-ethylhexanoatra (petroleum), hydro EFFECTS, ACUT acute and chronic:	CT LEVEL (DNEL): DNEL) is a level of exp EL values may differ fro icular company, a gove are derived by a process EVEL, WORKERS:- d chronic: alkanes, isoalkanes, cyclic e btreated heavy EVEL, WORKERS:- Loca alkanes, isoalkanes, cyclic e btreated heavy EVEL, GENERAL effects, acute and chronic: alkanes, isoalkanes, cyclic e btreated heavy EVEL, GENERAL effects, acute and chronic: alkanes, isoalkanes, cyclic e btreated heavy EVEL, CENERAL	bosure the om a ocernment as differences of the original sector of t	nat is considered cupational exp regulatory age ent of REACH. <u>DNEL Inhalation</u> mg/m3 s/r (a) (a) <u>DNEL Inhalation</u> mg/m3 s/r (a) (a) <u>DNEL Inhalation</u> mg/m3 s/r (a) (a) <u>DNEL Inhalation</u> mg/m3	ed safe, derivosure limit (C ncy or an org 1500 (c) 5 (c) - (c) s/r (c) - (c) 900 (c) 2,5 (c) - (c)	ved from toxicit DEL) for the sar ganization of ex mg/kg bw/d s/r (a) - (a) - (a) DNEL Cutaneou mg/cm2 s/r (a) - (a) DNEL Cutaneou mg/kg bw/d s/r (a) - (a)	y data a me cher kperts. A 300 15,75 - - - - - - - - - - - - - - - - - - -	nical. C Ithough (c) (c) (c) (c) (c) (c) (c) (c) (c) (c)	EL values main considered p DNEL Oral mg/kg bw/d - (a) - (a) DNEL Eyes mg/cm2 s/r (a) - (a) DNEL Eyes mg/kg bw/d s/r (a) s/r (a) s/r (a) s/r (a) c (a)	y come rotective of - (c) - (c) - (c) - (c) - (c) 300 (c) 7, 9 (c) - (c)
- - DERIV Derivect includer recomm health, - DERIV Systemin Hydroca <2% aro Zirconiuu Naphtha - DERIV effects, a Hydroca <2% aro Zirconiuu Naphtha - DERIV POPUL/ Hydroca <2% aro Zirconiuu Naphtha - LOCAL effects, a	VED NO-EFFE d no-effect level (i d in REACH. DN nended by a parti the OEL values a TED NO-EFFECT L c effects, acute and arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro TED NO-EFFECT L acute and chronic: arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro TED NO-EFFECT L ATION:- Systemic e arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro EFFECTS, ACUT acute and chronic: arbons, C9-C11, n-a omatics	CT LEVEL (DNEL): DNEL) is a level of exp EL values may differ fro icular company, a gove are derived by a proces EVEL, WORKERS:- d chronic: alkanes, isoalkanes, cyclic e botreated heavy EVEL, WORKERS:- Loca alkanes, isoalkanes, cyclic e botreated heavy EVEL, GENERAL effects, acute and chronic: alkanes, isoalkanes, cyclic e botreated heavy	bosure the om a ocernment as differences of the original sector of t	nat is considered cupational exp regulatory age ent of REACH. <u>DNEL Inhalation</u> mg/m3 s/r (a) c (a) <u>DNEL Inhalation</u> mg/m3 s/r (a) c (a) <u>DNEL Inhalation</u> mg/m3 s/r (a) c (a) <u>DNEL Inhalation</u> mg/m3	ed safe, derivosure limit (C ncy or an org 1500 (c) 5 (c) - (c) s/r (c) s/r (c) - (c) 900 (c) 2,5 (c)	ved from toxicit DEL) for the sal ganization of ex <u>DNEL Cutaneou</u> mg/kg bw/d s/r (a) - (a) <u>DNEL Cutaneou</u> mg/cm2 s/r (a) - (a) <u>DNEL Cutaneou</u> mg/kg bw/d s/r (a) - (a) <u>- (a)</u> <u>- (a)</u>	y data a me cher xperts. A 300 15,75 - .s/r - .s/r -	nical. C Ithough (c) (c) (c) (c) (c) (c) (c) (c) (c) (c)	Diversion Diversion <t< td=""><td>y come rotective of - (c) - (c) - (c)</td></t<>	y come rotective of - (c) - (c) - (c)
- - DERIV Derivect includer recomm health, - DERIV Systemin Hydroca <2% aro Zirconiuu Naphtha - DERIV effects, a Hydroca <2% aro Zirconiuu Naphtha - DERIV POPULA Hydroca <2% aro Zirconiuu Naphtha - DERIV POPULA Hydroca <2% aro Zirconiuu Naphtha - DERIV POPULA Hydroca <2% aro Zirconiuu Naphtha - DERIV POPULA	VED NO-EFFE d no-effect level (i d in REACH. DN nended by a parti the OEL values a TED NO-EFFECT L c effects, acute and arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro TED NO-EFFECT L acute and chronic: arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro TED NO-EFFECT L ATION:- Systemic e arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro EFFECTS, ACUT acute and chronic: arbons, C9-C11, n-a omatics	CT LEVEL (DNEL): DNEL) is a level of exp EL values may differ fro icular company, a gove are derived by a proces EVEL, WORKERS:- d chronic: alkanes, isoalkanes, cyclic e botreated heavy EVEL, WORKERS:- Loca alkanes, isoalkanes, cyclic e botreated heavy EVEL, GENERAL effects, acute and chronic: alkanes, isoalkanes, cyclic e botreated heavy E AND CHRONIC:- Local alkanes, isoalkanes, cyclic	bosure the om a ocernment as differences of the original sector of t	nat is considered cupational exp regulatory age ent of REACH. <u>DNEL Inhalation</u> mg/m3 s/r (a) (a) <u>DNEL Inhalation</u> mg/m3 s/r (a) (a) <u>DNEL Inhalation</u> mg/m3 s/r (a) (a) <u>DNEL Inhalation</u> mg/m3	ed safe, derivosure limit (C ncy or an org 1500 (c) 5 (c) - (c) s/r (c) - (c) 900 (c) 2,5 (c) - (c)	ved from toxicit DEL) for the sar ganization of ex mg/kg bw/d s/r (a) - (a) - (a) DNEL Cutaneou mg/cm2 s/r (a) - (a) DNEL Cutaneou mg/kg bw/d s/r (a) - (a)	y data a me cher kperts. A 300 15,75 - - s/r - - - - - - - - - - - - - - - - - - -	nical. C Ithough (c) (c) (c) (c) (c) (c) (c) (c) (c) (c)	EL values main considered p DNEL Oral mg/kg bw/d - (a) - (a) DNEL Eyes mg/cm2 s/r (a) - (a) DNEL Eyes mg/kg bw/d s/r (a) s/r (a) s/r (a) s/r (a) c (a)	y come rotective of - (c) - (c) - (c) - (c) 300 (c) 7, 9 (c) - (c) - (c) - (c)
 - DERIV Derivectincluder recommendation DERIV Systemin Hydroca 2% aro Zirconiuu Naphtha DERIV effects, a Hydroca 2% aro Zirconiuu Naphtha DERIV POPULA Hydroca 2% aro Zirconiuu Naphtha DERIV POPULA Hydroca 2% aro Zirconiuu Naphtha LOCAL effects, a Hydroca 2% aro Zirconiuu Naphtha 	VED NO-EFFE d no-effect level (i d in REACH. DN nended by a parti the OEL values a ED NO-EFFECT L c effects, acute and rbons, C9-C11, n-a omatics m 2-ethylhexanoatu a (petroleum), hydro ED NO-EFFECT L acute and chronic: arbons, C9-C11, n-a omatics m 2-ethylhexanoatu a (petroleum), hydro ED NO-EFFECT L ATION:- Systemic e arbons, C9-C11, n-a omatics m 2-ethylhexanoatu a (petroleum), hydro - EFFECTS, ACUT acute and chronic: arbons, C9-C11, n-a omatics m 2-ethylhexanoatu a (petroleum), hydro - EFFECTS, ACUT acute and chronic: arbons, C9-C11, n-a omatics m 2-ethylhexanoatu a (petroleum), hydro	CT LEVEL (DNEL): DNEL) is a level of exp EL values may differ fro icular company, a gove are derived by a process EVEL, WORKERS:- d chronic: alkanes, isoalkanes, cyclic e botreated heavy EVEL, WORKERS:- Loca alkanes, isoalkanes, cyclic e botreated heavy EVEL, GENERAL effects, acute and chronic: alkanes, isoalkanes, cyclic e botreated heavy E AND CHRONIC:- Local alkanes, isoalkanes, cyclic e	bosure the om a ocernment ss difference cs, all cs,	nat is considered cupational exp regulatory age ent of REACH. DNEL Inhalation mg/m3 s/r (a) - (a) DNEL Inhalation mg/m3 s/r (a) - (a) DNEL Inhalation mg/m3 s/r (a) - (a) DNEL Inhalation mg/m3 s/r (a) - (a) DNEL Inhalation mg/m3 s/r (a) - (a)	ed safe, derivosure limit (C ncy or an org 1500 (c) 5 (c) - (c) s/r (c) s/r (c) - (c) 900 (c) 2,5 (c) - (c) s/r (c) s/r (c) s/r (c) - (c)	ved from toxicit DEL) for the sai ganization of ex- mg/kg bw/d s/r (a) - (a) - (a) DNEL Cutaneou mg/cm2 s/r (a) - (a) DNEL Cutaneou mg/kg bw/d s/r (a) - (a)	y data a me cher xperts. A 300 15,75 - - s/r - - - - - - - - - - - - - - - - - - -	nical. C Ithough (c) (c) (c) (c) (c) (c) (c) (c) (c) (c)	EL values main considered p DNEL Oral mg/kg bw/d - (a) - (a) DNEL Eyes mg/cm2 s/r (a) - (a) DNEL Eyes mg/kg bw/d s/r (a) s/r (a) - (a) DNEL Eyes mg/cm2 s/r (a) s/r (a) - (a)	y come rotective of - (c) - (c) - (c) - (c) - (c) 300 (c) 7, 9 (c) - (c) - (c) - (c) - (c) - (c)
 - DERIV Derivectincluder recomminealth, - DERIV Systeminic Hydroca - 2% aroding Zirconium Naphthai - DERIV effects, at Hydroca - 2% aroding Zirconium Naphthai - DERIV POPULA Hydroca - 2% aroding Zirconium Naphthai - DERIV POPULA Hydroca - 2% aroding Zirconium Naphthai - DERIV POPULA Hydroca - LOCAL effects, at Hydroca - 2% aroding Zirconium Naphthai - LOCAL effects, at Hydroca - 2% aroding Zirconium Naphthai - LOCAL effects, at - DA - C(-) - DN s/r - DN 	VED NO-EFFE d no-effect level (i d in REACH. DN nended by a parti the OEL values a ZED NO-EFFECT L c effects, acute and rbons, C9-C11, n-a omatics m 2-ethylhexanoatu a (petroleum), hydro ZED NO-EFFECT L acute and chronic: arbons, C9-C11, n-a omatics m 2-ethylhexanoatu a (petroleum), hydro ZED NO-EFFECT L ATION:- Systemic e arbons, C9-C11, n-a omatics m 2-ethylhexanoatu a (petroleum), hydro EFFECTS, ACUT acute and chronic: arbons, C9-C11, n-a omatics m 2-ethylhexanoatu a (petroleum), hydro c EFFECTS, ACUT acute and chronic: arbons, C9-C11, n-a omatics m 2-ethylhexanoatu a (petroleum), hydro cute, short-term NEL not availabl NEL not derived	CT LEVEL (DNEL): DNEL) is a level of exp EL values may differ fro icular company, a gove are derived by a process EVEL, WORKERS:- d chronic: alkanes, isoalkanes, cyclic e botreated heavy EVEL, WORKERS:- Loca alkanes, isoalkanes, cyclic e botreated heavy EVEL, GENERAL effects, acute and chronic: alkanes, isoalkanes, cyclic e botreated heavy E AND CHRONIC:- Local alkanes, isoalkanes, cyclic e	bosure the om a ocernment ss difference cs, and cs, and cs,	nat is considered cupational exp regulatory age ent of REACH. <u>DNEL Inhalation</u> mg/m3 s/r (a) - (a) <u>DNEL Inhalation</u> mg/m3	ed safe, derivosure limit (C ncy or an org 1500 (c) 5 (c) - (c) s/r (c) s/r (c) - (c) 900 (c) 2,5 (c) - (c) s/r (c) s/r (c) s/r (c) - (c)	ved from toxicit DEL) for the sai ganization of ex- mg/kg bw/d s/r (a) - (a) - (a) DNEL Cutaneou mg/cm2 s/r (a) - (a) DNEL Cutaneou mg/kg bw/d s/r (a) - (a)	y data a me cher xperts. A 300 15,75 - - s/r - - - - - - - - - - - - - - - - - - -	nical. C Ithough (c) (c) (c) (c) (c) (c) (c) (c) (c) (c)	DNEL Oral mg/kg bw/d - (a) - (a) - (a) - (a) - (a) - (a) DNEL Eyes mg/cm2 s/r (a) - (a) S/r (a) - (a) DNEL Eyes mg/cm2 s/r (a) - (a) DNEL Eyes mg/cm2 s/r (a) - (a)	y come rotective of - (c) - (c) - (c) - (c) - (c) 300 (c) 7, 9 (c) - (c) - (c) - (c) - (c) - (c)
- - DERIV Derivection includer recomminealth, - DERIV Systemin Hydroca <2% aro Zirconiuu Naphtha - DERIV effects, a Hydroca <2% aro Zirconiuu Naphtha - DERIV POPUL/ Hydroca <2% aro Zirconiuu Naphtha - DERIV POPUL/ Hydroca <2% aro Zirconiuu Naphtha - LOCAL effects, a Hydroca <2% aro Zirconiuu Naphtha - LOCAL effects, a Hydroca <2% aro Zirconiuu Naphtha - LOCAL effects, a Hydroca <2% aro Zirconiuu Naphtha (a) - Ac (-) - DN s/r - DF	VED NO-EFFE d no-effect level (i d in REACH. DN nended by a part the OEL values a ED NO-EFFECT L c effects, acute and arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro TED NO-EFFECT L acute and chronic: arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro TED NO-EFFECT L ATION:- Systemic e arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro L EFFECTS, ACUT acute and chronic: arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro L EFFECTS, ACUT acute and chronic: arbons, C9-C11, n-a omatics m 2-ethylhexanoate a (petroleum), hydro cute, short-term NEL not availabl NEL not derived DICTED NO-EF	CT LEVEL (DNEL): DNEL) is a level of exp EL values may differ fro icular company, a gove are derived by a process EVEL, WORKERS:- d chronic: alkanes, isoalkanes, cyclic e botreated heavy EVEL, WORKERS:- Loca alkanes, isoalkanes, cyclic e botreated heavy EVEL, GENERAL effects, acute and chronic: alkanes, isoalkanes, cyclic e botreated heavy E AND CHRONIC:- Local alkanes, isoalkanes, cyclic e botreated heavy E AND CHRONIC:- Local alkanes, isoalkanes, cyclic e botreated heavy	bosure the om a oc ernment ss differe cs, al cs, cs, cs, l cs l cs	nat is considered cupational exp regulatory age ent of REACH. <u>DNEL Inhalation</u> mg/m3 s/r (a) - (a) <u>DNEL Inhalation</u> mg/m3	ed safe, derivosure limit (C ncy or an org 1500 (c) 5 (c) - (c) s/r (c) s/r (c) - (c) 900 (c) 2,5 (c) - (c) s/r (c) s/r (c) s/r (c) s/r (c) - (c) eated expose	ved from toxicit DEL) for the sai ganization of ex- mg/kg bw/d s/r (a) - (a) - (a) DNEL Cutaneou mg/cm2 s/r (a) - (a) DNEL Cutaneou mg/kg bw/d s/r (a) - (a)	y data a me cher xperts. A 300 15,75 - - s/r - - - - - - - - - - - - - - - - - - -	nical. C Ithough (c) (c) (c) (c) (c) (c) (c) (c) (c) (c)	DNEL Oral mg/kg bw/d - (a) - (a) - (a) - (a) - (a) - (a) DNEL Eyes mg/cm2 s/r (a) - (a) S/r (a) - (a) DNEL Eyes mg/cm2 s/r (a) - (a) DNEL Eyes mg/cm2 s/r (a) - (a)	y come rotective of - (c) - (c) - (c) - (c) - (c) 300 (c) 7, 9 (c) - (c) - (c) - (c) - (c) - (c) - (c)

Page 5/13 (Language:EN)

SAFETY DATA SHEET (REACH) In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2020/878

BRISA_BARNIZ INTERIOR- EXTERIOR SATINADO

Code : 12161

Revision: 14/12/2022

Version: 6

isaval

pinturas

2161

Date of printing: 14/12/2022

Hydrocarbons, C9-C		-7	-7	-7							
isoalkanes, cyclics,											
Zirconium 2-ethylhe		0.36	0.036	0.493							
1 0	i), hydrotreated heavy	-7	-7	-7							
	<u>EATMENT PLANTS (STP)</u>	PNEC STP	PNEC Sediments	PNEC Sediments							
	FRESH- AND MARINE	mg/l	mg/kg dw/d	mg/kg dw/d							
WATER:				-							
Hydrocarbons, C9-C		-7	-7	-7							
isoalkanes, cyclics,											
Zirconium 2-ethylhe		71.7	6.37	0.637							
	n), hydrotreated heavy	-7	-7	-7							
	FECT CONCENTRATION,	PNEC Air	PNEC Soil	PNEC Oral							
	ANISMS:- Air, soil and	mg/m3	mg/kg dw/d	mg/kg dw/d							
effects for predators a		-7	-7	-7							
Hydrocarbons, C9-C isoalkanes, cyclics,		-7	-/	-1							
			1.06								
Zirconium 2-ethylhe				-							
	n), hydrotreated heavy	-7	-7	-7							
	able (without data of registrati	ion REACH).									
EXPOSURE CONT	ROLS:										
Т	by the are not	use of local exhaust ventil sufficient to maintain con	ere reasonably practicable ation and good general ex centrations of particulates uitable respiratory protecti	traction.If these measure and vapours below the							
- Protection of respined Avoid the inhalation of	•	•	, , , , , , , , , , , , , , , , , , ,								
- Protection of eyes	•										
		h clean water close to the w	orking area								
-			It is recommended to install water taps or sources with clean water close to the working area Protection of hands and skin:								
Lift is recommended to	install water taps or sources with	h clean water close to the w	orking area Barrier creams n	nay help to protect the							
	install water taps or sources with skin.Barrier creams should not be			nay help to protect the							
exposed areas of the OCCUPATIONAL E	skin Barrier creams should not b XPOSURE CONTROLS: RE	be applied once exposure has GULATION (EU) NO. 201	as occurred. <u>6/425:</u>								
exposed areas of the OCCUPATIONAL E As a general measure with the corresponding	skin.Barrier creams should not b <u>XPOSURE CONTROLS: REC</u> e on prevention and safety in the g marking. For more information PPE, protection class, marking,	be applied once exposure ha <u>GULATION (EU) NO. 201</u> work place, we recomment n on personal protective equ	as occurred. <u>6/425:</u> I the use of a basic personal ipment (storage, use, cleani	protection equipment (PPE							
exposed areas of the OCCUPATIONAL E As a general measure with the corresponding characteristics of the	skin.Barrier creams should not b XPOSURE CONTROLS: REC e on prevention and safety in the g marking. For more information PPE, protection class, marking, PPE. A-type filter mask (brow 65°C (EN14387).Class Class 3: high capacity of must be selected dependent accordance with the sp filters does not work sa	be applied once exposure ha <u>GULATION (EU) NO. 201</u> work place, we recommend n on personal protective equi- category, CEN norm, etc), wn) for gases and vapours 1: low capacity up to 100 up to 10000 ppm.In order nding on the type and con- difications supplied by the tisfactorily when the air con-	as occurred. <u>6/425:</u> I the use of a basic personal ipment (storage, use, cleani	protection equipment (PPE ng, maintenance, type and mative brochures provided th a boiling point higher t apacity up to 5000 ppm, tion level, the filter class nating agents present, in piratory equipment with s of vapour or oxygen							
exposed areas of the OCCUPATIONAL E As a general measure with the corresponding characteristics of the the manufacturers of the Mask:	skin.Barrier creams should not b XPOSURE CONTROLS: REG e on prevention and safety in the g marking. For more information PPE, protection class, marking, PPE. A-type filter mask (brow 65°C (EN14387).Class Class 3: high capacity of must be selected dependent accordance with the sp filters does not work sa content less than 18% breathing apparatus. Safety goggles designed	be applied once exposure ha <u>GULATION (EU) NO. 201</u> work place, we recommend n on personal protective equi- category, CEN norm, etc), wn) for gases and vapours 1: low capacity up to 100 up to 10000 ppm.In order nding on the type and con- necifications supplied by the tisfactorily when the air con- in volume.In presence of laged to protect against liquid	as occurred. 6/425: 1 the use of a basic personal ipment (storage, use, cleani you should consult the infor of organic compounds wi 0 ppm, Class 2: medium of to obtain a suitable protect icentration of the contamir e filter producers. The respontains high concentration nigh concentrations of vap	protection equipment (PPE ng, maintenance, type and mative brochures provided th a boiling point higher t apacity up to 5000 ppm, tion level, the filter class nating agents present, in biratory equipment with s of vapour or oxygen our, use independent teral protection							
exposed areas of the OCCUPATIONAL E As a general measure with the corresponding characteristics of the I the manufacturers of I	skin.Barrier creams should not b XPOSURE CONTROLS: REG e on prevention and safety in the g marking. For more information PPE, protection class, marking, PPE. A-type filter mask (brow 65°C (EN14387).Class Class 3: high capacity of must be selected dependent accordance with the sp filters does not work sa content less than 18% breathing apparatus. Safety goggles designed (EN166).Clean daily ar	be applied once exposure ha <u>GULATION (EU) NO. 201</u> work place, we recommend n on personal protective equi- category, CEN norm, etc), wn) for gases and vapours 1: low capacity up to 100 up to 10000 ppm.In order nding on the type and con- necifications supplied by the tisfactorily when the air con- in volume.In presence of laged to protect against liquid	as occurred. 6/425: 1 the use of a basic personal ipment (storage, use, cleani you should consult the infor of organic compounds wi 0 ppm, Class 2: medium c to obtain a suitable protect icentration of the contamir ne filter producers. The respontains high concentrations nigh concentrations of vap	protection equipment (PPE ng, maintenance, type and mative brochures provided th a boiling point higher t apacity up to 5000 ppm, tion level, the filter class nating agents present, in biratory equipment with s of vapour or oxygen our, use independent teral protection							
exposed areas of the OCCUPATIONAL E As a general measure with the corresponding characteristics of the I the manufacturers of I	skin.Barrier creams should not b XPOSURE CONTROLS: REG e on prevention and safety in the g marking. For more information PPE, protection class, marking, PPE. A-type filter mask (brow 65°C (EN14387).Class Class 3: high capacity of must be selected dependent accordance with the sp filters does not work sa content less than 18% breathing apparatus. Safety goggles designed	be applied once exposure ha <u>GULATION (EU) NO. 201</u> work place, we recommend n on personal protective equi- category, CEN norm, etc), wn) for gases and vapours 1: low capacity up to 100 up to 10000 ppm.In order nding on the type and con- necifications supplied by the tisfactorily when the air con- in volume.In presence of laged to protect against liquid	as occurred. 6/425: 1 the use of a basic personal ipment (storage, use, cleani you should consult the infor of organic compounds wi 0 ppm, Class 2: medium of to obtain a suitable protect icentration of the contamir e filter producers. The respontains high concentration nigh concentrations of vap	protection equipment (PPE ng, maintenance, type and mative brochures provided th a boiling point higher t apacity up to 5000 ppm, tion level, the filter class nating agents present, in biratory equipment with s of vapour or oxygen our, use independent teral protection							
exposed areas of the OCCUPATIONAL E As a general measure with the corresponding characteristics of the I the manufacturers of I	skin.Barrier creams should not b XPOSURE CONTROLS: REG e on prevention and safety in the g marking. For more information PPE, protection class, marking, PPE. A-type filter mask (brow 65°C (EN14387).Class Class 3: high capacity of must be selected dependent accordance with the sp filters does not work sa content less than 18% breathing apparatus. Safety goggles designed (EN166).Clean daily ar	be applied once exposure ha <u>GULATION (EU) NO. 201</u> work place, we recommend n on personal protective equi- category, CEN norm, etc), wn) for gases and vapours 1: low capacity up to 100 up to 10000 ppm.In order nding on the type and con- necifications supplied by the tisfactorily when the air con- in volume.In presence of laged to protect against liquid	as occurred. 6/425: 1 the use of a basic personal ipment (storage, use, cleani you should consult the infor of organic compounds wi 0 ppm, Class 2: medium of to obtain a suitable protect icentration of the contamir e filter producers. The respontains high concentration nigh concentrations of vap	protection equipment (PPE ng, maintenance, type and mative brochures provided th a boiling point higher t apacity up to 5000 ppm, tion level, the filter class nating agents present, in biratory equipment with s of vapour or oxygen our, use independent teral protection							
exposed areas of the OCCUPATIONAL E As a general measure with the corresponding characteristics of the the manufacturers of I Mask:	skin.Barrier creams should not the XPOSURE CONTROLS: REC a on prevention and safety in the g marking. For more information PPE, protection class, marking, PPE. A-type filter mask (brow 55°C (EN14387).Class Class 3: high capacity of must be selected dependent accordance with the sp filters does not work sa content less than 18% breathing apparatus. Safety goggles designed (EN166).Clean daily ar manufacturer. No. Gloves resistant agains expected, gloves of pro- min.When short contacor should be used, with a material should be in an accordance with a material should be in an or an	be applied once exposure ha <u>GULATION (EU) NO. 201</u> work place, we recommend n on personal protective equi- category, CEN norm, etc), who for gases and vapours 1: low capacity up to 100 up to 10000 ppm.In order nding on the type and con- decifications supplied by the tisfactorily when the air con- in volume.In presence of low disinfect at regular inter- ted to protect against liquid ad disinfect at regular inter- set chemicals (EN374).When breakthrough time >30 m ccordance with the preten-	as occurred. 6/425: I the use of a basic personal ipment (storage, use, cleani you should consult the infor of organic compounds wi 0 ppm, Class 2: medium c to obtain a suitable protect centration of the contamir be filter producers. The respontains high concentrations ontains high concentration high concentrations of vap splashes, with suitable la vals in accordance with the en repeated or prolonged of hould be used, with a breac cted, use gloves with a pro- in. The breakthrough time of ded period of use. There a	protection equipment (PPE ng, maintenance, type and mative brochures provided th a boiling point higher t apacity up to 5000 ppm, tion level, the filter class nating agents present, in biratory equipment with s of vapour or oxygen our, use independent teral protection he instructions of the contact with the product is akthrough time of >240 bit of the selected glove re several factors (for							
exposed areas of the OCCUPATIONAL E As a general measure with the corresponding characteristics of the the manufacturers of the Mask: Safety goggles: Face shield: Gloves:	skin.Barrier creams should not t EXPOSURE CONTROLS: RE(a on prevention and safety in the g marking. For more information PPE, protection class, marking, PPE. A-type filter mask (brow ✓ 65°C (EN14387).Class Class 3: high capacity of must be selected dependent accordance with the sp filters does not work sat content less than 18% breathing apparatus. Safety goggles designed (EN166).Clean daily ar manufacturer. No. Gloves resistant against expected, gloves of pro- min.When short contact should be used, with a material should be in an example, temperature) chemicals is clearly low circumstances and post taken into account.The	be applied once exposure ha <u>GULATION (EU) NO. 201</u> work place, we recommend n on personal protective equi- category, CEN norm, etc), who for gases and vapours 1: low capacity up to 100 up to 10000 ppm.In order nding on the type and con- decifications supplied by the tisfactorily when the air con- in volume.In presence of low disinfect at regular inter- test chemicals (EN374).When be the product is expen- breakthrough time >30 m ccordance with the preten- , they do in practice the per- ver than the established sizesibilities, the instructions/size sizesibilities, the instructions/sizesibilities, the instructions/sizesibilities/size	as occurred. 6/425: If the use of a basic personal ipment (storage, use, cleani you should consult the infor of organic compounds wi 0 ppm, Class 2: medium c to obtain a suitable protect centration of the contamir be filter producers. The respontains high concentrations ontains high concentration high concentrations of vap splashes, with suitable la vals in accordance with the en repeated or prolonged of hould be used, with a breac cted, use gloves with a pro-	protection equipment (PPE ng, maintenance, type and mative brochures provided th a boiling point higher t apacity up to 5000 ppm, tion level, the filter class nating agents present, in biratory equipment with s of vapour or oxygen our, use independent teral protection re instructions of the contact with the product i akthrough time of >240 btection level 2 or higher of the selected glove re several factors (for gloves resistant against wide variety of the glove supplier should							
exposed areas of the OCCUPATIONAL E As a general measure with the corresponding characteristics of the the manufacturers of the Mask: Safety goggles: Face shield: Gloves:	skin.Barrier creams should not the XPOSURE CONTROLS: REC a on prevention and safety in the g marking. For more information PPE, protection class, marking, PPE. A-type filter mask (brow 50°C (EN14387).Class Class 3: high capacity of must be selected dependent accordance with the sp filters does not work sa content less than 18% breathing apparatus. Safety goggles designed (EN166).Clean daily are manufacturer. No. Gloves resistant agains expected, gloves of pro- min.When short contact should be used, with a material should be in an example, temperature) chemicals is clearly low circumstances and pos	be applied once exposure ha <u>GULATION (EU) NO. 201</u> work place, we recommend n on personal protective equi- category, CEN norm, etc), who for gases and vapours 1: low capacity up to 100 up to 10000 ppm.In order nding on the type and con- decifications supplied by the tisfactorily when the air con- in volume.In presence of low disinfect at regular inter- test chemicals (EN374).When be the product is expen- breakthrough time >30 m ccordance with the preten- , they do in practice the per- ver than the established sizesibilities, the instructions/size sizesibilities, the instructions/sizesibilities, the instructions/sizesibilities/size	as occurred. 6/425: I the use of a basic personal ipment (storage, use, cleani you should consult the infor of organic compounds wi 0 ppm, Class 2: medium of to obtain a suitable protect centration of the contamir pe filter producers. The respontains high concentrations ingh concentrations of vap splashes, with suitable la vals in accordance with the en repeated or prolonged of hould be used, with a breacted, use gloves with a pro- tion. The breakthrough time of ded period of use. There a eriod of use of a protective candard EN374. Due to the specifications provided by	protection equipment (PPE ng, maintenance, type and mative brochures provided th a boiling point higher t apacity up to 5000 ppm, tion level, the filter class nating agents present, in biratory equipment with s of vapour or oxygen our, use independent teral protection re instructions of the contact with the product i akthrough time of >240 btection level 2 or higher of the selected glove re several factors (for gloves resistant against wide variety of the glove supplier should							
exposed areas of the OCCUPATIONAL E As a general measure with the corresponding characteristics of the the manufacturers of I Mask: Safety goggles: Face shield: Gloves:	skin.Barrier creams should not t EXPOSURE CONTROLS: RE(a on prevention and safety in the g marking. For more information PPE, protection class, marking, PPE. A-type filter mask (brow ✓ 65°C (EN14387).Class Class 3: high capacity of must be selected dependent accordance with the sp filters does not work sat content less than 18% breathing apparatus. Safety goggles designed (EN166).Clean daily ar manufacturer. No. Gloves resistant against expected, gloves of pro- min.When short contact should be used, with a material should be in an example, temperature) chemicals is clearly low circumstances and post taken into account.The	be applied once exposure ha <u>GULATION (EU) NO. 201</u> work place, we recommend n on personal protective equi- category, CEN norm, etc), who for gases and vapours 1: low capacity up to 100 up to 10000 ppm.In order nding on the type and con- decifications supplied by the tisfactorily when the air con- in volume.In presence of low disinfect at regular inter- test chemicals (EN374).When be the product is expen- breakthrough time >30 m ccordance with the preten- , they do in practice the per- ver than the established sizesibilities, the instructions/size sizesibilities, the instructions/sizesibilities, the instructions/sizesibilities/size	as occurred. 6/425: I the use of a basic personal ipment (storage, use, cleani you should consult the infor of organic compounds wi 0 ppm, Class 2: medium of to obtain a suitable protect centration of the contamir pe filter producers. The respontains high concentrations ingh concentrations of vap splashes, with suitable la vals in accordance with the en repeated or prolonged of hould be used, with a breacted, use gloves with a pro- tion. The breakthrough time of ded period of use. There a eriod of use of a protective candard EN374. Due to the specifications provided by	protection equipment (PPE ng, maintenance, type and mative brochures provided th a boiling point higher t apacity up to 5000 ppm, tion level, the filter class nating agents present, in biratory equipment with s of vapour or oxygen our, use independent teral protection re instructions of the contact with the product i akthrough time of >240 btection level 2 or higher of the selected glove re several factors (for gloves resistant against wide variety of the glove supplier should							
exposed areas of the OCCUPATIONAL E As a general measure with the corresponding characteristics of the I the manufacturers of I Mask: Safety goggles: Face shield: Gloves: Boots:	skin.Barrier creams should not be XPOSURE CONTROLS: REG on prevention and safety in the g marking. For more information PPE, protection class, marking, PPE. A-type filter mask (brow 65°C (EN14387).Class Class 3: high capacity of must be selected depen- accordance with the sp filters does not work sa content less than 18% breathing apparatus. Safety goggles designed (EN166).Clean daily ar manufacturer. No. Gloves resistant agains expected, gloves of pro- min.When short contact should be used, with a material should be in ar example, temperature) chemicals is clearly low circumstances and pos- taken into account.The No.	be applied once exposure ha <u>GULATION (EU) NO. 201</u> work place, we recommend n on personal protective equi- category, CEN norm, etc), who for gases and vapours 1: low capacity up to 100 up to 10000 ppm.In order nding on the type and con- decifications supplied by the tisfactorily when the air con- in volume.In presence of low disinfect at regular inter- test chemicals (EN374).When be the product is expen- breakthrough time >30 m ccordance with the preten- , they do in practice the per- ver than the established sizesibilities, the instructions/size sizesibilities, the instructions/sizesibilities, the instructions/sizesibilities/size	as occurred. 6/425: I the use of a basic personal ipment (storage, use, cleani you should consult the infor of organic compounds wi 0 ppm, Class 2: medium of to obtain a suitable protect centration of the contamir pe filter producers. The respontains high concentrations ingh concentrations of vap splashes, with suitable la vals in accordance with the en repeated or prolonged of hould be used, with a breacted, use gloves with a pro- tion. The breakthrough time of ded period of use. There a eriod of use of a protective candard EN374. Due to the specifications provided by	protection equipment (PPE ng, maintenance, type and mative brochures provided th a boiling point higher t apacity up to 5000 ppm, tion level, the filter class nating agents present, in biratory equipment with s of vapour or oxygen our, use independent teral protection re instructions of the contact with the product i akthrough time of >240 btection level 2 or higher of the selected glove re several factors (for gloves resistant against wide variety of the glove supplier should							

Version: 6

Y DATA SHEET ance with Regulation ((REACH) (EC) No. 1907/2006 and Regulation (EU	Page 7/13 (Language:EN)	
isava		XTERIOR SATINADO	
n: 6	Revision: 14/12/2022	Previous revision: 23/02/2022	Date of printing: 14/12/2022
ENVIRONMENT/ Avoid any spillage - Spills on the soi Prevent contamina - Spills in water:	product is handled at room temperat AL EXPOSURE CONTROLS: in the environment. Avoid any release i: tion of soil. cape into drains, sewers or water cou	e into the atmosphere.	
This product does 2000/60/EC~2013/		n the list of priority substances in the field	of water policy under Directive
VOC (product real It is applicable the	y, emissions to the atmosphere while ady for use*): Directive 2004/42/EC, on the limitatio	handling and use may result. Avoid any r	to the use of organic solvents: PAINTS

It is applicable the Directive 2004/42/EC, on the limitation AND VARNISHES (defined in the Directive 2004/42/EC, Annex I.1): Emission subcategory e) Trim varnish for wood, solvent-borne. VOC (product ready for use*): (BRISA BARNIZ INTERIOR- Cod. 12161 = 100 in volume): 372,8 (VOC max.400 g/l* starting from 01.01.2010) VOC (industrial installations):

If this product is used in an industrial installation, it must be verified if it is applicable the Directive 2010/75/CE (DL.127/2013, on the limitation of emissions of volatile compounds due to the use of organic solvents in certain activities and installations: Solvents: 38,68 % Weight, VOC (supply): 39,09 % Weight, VOC: 32,88 % C (expressed as carbon), Molecular weight (average): 145,29 , Number C atoms (average): 10,18

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES: 91

9.1	INFORMATION ON DASIC PHYSICAL AND CHEMICAL PR	<u>OPENTIES.</u>	
	Appearance		
	Physical state:	Liquid	
	Colour:	Colourless	
	Odour:	Characteristic	
	Odour threshold:	Not available (mixture).	
	Change of state		
	Melting point:	Not available (mixture).	
	Initial boiling point:	120,1* ⁰C at 760 mmHg	
	- Flammability:		
	Flashpoint	38* °C	CLP 2.6.4.3.
	Lower/upper flammability or explosive limits:	Not available - Not available	
	Autoignition temperature:	Not applicable.	
	Stability		
	Decomposition temperature:	Not available (technical impossibility to obtain the	
		data).	
	<u>pH-value</u>		
	pH:	Not applicable (non-aqueous media).	
	- Viscosity:		
	Dynamic viscosity:	470* cps at 20°C	
	Kinematic viscosity:	160* mm2/s at 40°C	
	Viscosity (flow time):	130* sec. CF4 at 20°C	
	- Solubility(ies):		
	Solubility in water	Inmiscible	
	Liposolubility:	Not applicable (inorganic product).	
	Partition coefficient: n-octanol/water:	Not applicable (mixture).	
	- Volatility:	······································	
	Vapour pressure:	1,5* mmHg at 20⁰C	
	Vapour pressure:	1,3012* kPa at 50°C	
	Evaporation rate:	Not available (lack of data).	
	Density		
	Relative density:	0,954* at 20/4°C	Relative water
	Relative vapour density:	4,69* at 20°C 1 atm.	Relative air
	Particle characteristics		
	Particle size:	Not applicable.	
	- Explosive properties:		
	Vapours can form explosive mixtures with air and are able to flam	e up or explode in presence of an ignition source	
	- Oxidizing properties:	e up or explore in presence of an ignition source.	
	Not classified as oxidizing product.		
	*Estimated values based on the substances composing the mixture	8.	
9.2	OTHER INFORMATION:		
0.2	Information regarding physical hazard classes		
	Flammable liquids: Combustibility:	Combustible.	

	isaval	BRISA_BARNIZ INTERIOF Code : 12161	R- EXTERIOR SATINADO		
Version:	6 Revi	sion: 14/12/2022	Previous revision	1: 23/02/2022	Date of printing: 14/12/20
	Other security features VOC (supply): VOC (supply): Nonvolatile:	<u>s:</u>	39,1 % Weig 372,8 g/l 60,91 *% We		1h. 60°C
		data sheet. For additional ir	oduct specifications. The data for formation concerning physical		
ECTION [•]	10: STABILITY AND RE	ACTIVITY			
1	REACTIVITY: - Corrosivity to metals It is not corrosive to met - Pyrophorical proper It is not pyrophoric.	als.			
	CHEMICAL STABILIT Stable under recommen	<u>Y:</u> ded storage and handling co	onditions.		
10.3 <u> </u>	POSSIBILITY OF HAZ	CARDOUS REACTIONS: ction with oxidizing agents, a			
10.5 J	- Humidity: Avoid extreme humidity - Pressure: Not relevant. - Shock: The product is not sensi dents and breakage of p INCOMPATIBLE MAT Keep away from oxidizir HAZARDOUS DECOM	contact with sunlight. ed by exposure to air, but si conditions. tive to shocks, but as a reco packaging, especially when <u>ERIALS:</u> ng agents, acids, peroxides.	hould not be left the containers mmendation of a general natur the product is handled in large	e should be avoided bumps a quantities, and during loading	and rough handling to avoi g and download operations
1	carried out by using th	ological data on the prepa e conventional calculatior	ration is available. The toxic n method of the Regulation (I FFINED IN REGULATION (I	EU) No. 1272/2008~2021/8	nese mixture has been 849 (CLP).
11.1 _ [[No experimental toxico carried out by using th <u>INFORMATION ON F</u> <u>ACUTE TOXICITY:</u> Dose and lethal conce	blogical data on the prepa e conventional calculatior IAZARD CLASSES AS D ntrations	n method of the Regulation (I EFINED IN REGULATION (I DL50 (OECD401)	EU) No. 1272/2008~2021/8 EC) NO 1272/2008 : DL50 (OECD402)	849 (CLP). CL50 (OECD40
11.1 - 11.1 - [[No experimental toxica carried out by using th <u>INFORMATION ON F</u> <u>ACUTE TOXICITY:</u> Dose and lethal conce for individual ingredier Hydrocarbons, C9-C1 ²	blogical data on the prepa e conventional calculation AZARD CLASSES AS D ntrations ts: I, n-alkanes, isoalkanes,	n method of the Regulation (I EFINED IN REGULATION (I	EU) No. 1272/2008~2021/8 EC) NO 1272/2008 :	849 (CLP). CL50 (OECD40 mg/m3·4h Inhalati
1.1 - 1	No experimental toxica carried out by using th <u>INFORMATION ON F</u> <u>ACUTE TOXICITY:</u> Dose and lethal conce for individual ingredier	blogical data on the prepa e conventional calculatior IAZARD CLASSES AS D Intrations Its: I, n-alkanes, isoalkanes, s noate	n method of the Regulation (I EFINED IN REGULATION (I DL50 (OECD401) mg/kg bw Oral	EU) No. 1272/2008~2021/8 EC) NO 1272/2008 : DL50 (OECD402) mg/kg bw Cutaneous	849 (CLP). CL50 (OECD40 mg/m3·4h Inhalati > 9300 F > 4300 F
1.1	No experimental toxico carried out by using th <u>INFORMATION ON F</u> <u>ACUTE TOXICITY:</u> Dose and lethal conce for individual ingredier Hydrocarbons, C9-C1 ² cyclics, <2% aromatics Zirconium 2-ethylhexa	blogical data on the prepa e conventional calculation IAZARD CLASSES AS D Intrations Its: I, n-alkanes, isoalkanes, s noate nydrotreated heavy icity (ATE)	n method of the Regulation (B EFINED IN REGULATION (B DL50 (OECD401) mg/kg bw Oral > 5000 Rat > 5000 Rat	EU) No. 1272/2008~2021/8 EC) NO 1272/2008 : DL50 (OECD402) mg/kg bw Cutaneous 3160 Rabbit > 2000 Rat	849 (CLP). CL50 (OECD40 mg/m3·4h Inhalati > 9300 F > 4300 F > 7630 F
1.1 - 1.1 -	No experimental toxica carried out by using th <u>INFORMATION ON F</u> <u>ACUTE TOXICITY:</u> Dose and lethal conce for individual ingredien Hydrocarbons, C9-C1 ⁷ cyclics, <2% aromatics Zirconium 2-ethylhexa Naphtha (petroleum), I Estimates of acute tox for individual ingredien	blogical data on the prepa e conventional calculation AZARD CLASSES AS D Intrations its: I, n-alkanes, isoalkanes, moate hydrotreated heavy icity (ATE) its: I, n-alkanes, isoalkanes, s noate	n method of the Regulation (f EFINED IN REGULATION (f DL50 (OECD401) mg/kg bw Oral > 5000 Rat > 5000 Rat > 5000 Rat ATE	EU) No. 1272/2008~2021/8 EC) NO 1272/2008 : DL50 (OECD402) mg/kg bw Cutaneous 3160 Rabbit > 2000 Rat > 2000 Rabbit ATE	849 (CLP). CL50 (OECD4(mg/m3·4h Inhalati > 9300 F > 4300 F > 7630 F
	No experimental toxica carried out by using the <u>INFORMATION ON F</u> <u>ACUTE TOXICITY:</u> Dose and lethal conce for individual ingredien Hydrocarbons, C9-C1 ² cyclics, <2% aromatics Zirconium 2-ethylhexa Naphtha (petroleum), I Estimates of acute tox for individual ingredien Hydrocarbons, C9-C1 ² cyclics, <2% aromatics Zirconium 2-ethylhexa Naphtha (petroleum), I (*) - Point estimates of a be used in the calculatio (-) - The components that are ignored.	blogical data on the prepa e conventional calculation AZARD CLASSES AS D Intrations its: I, n-alkanes, isoalkanes, onoate hydrotreated heavy icity (ATE) its: I, n-alkanes, isoalkanes, onoate hydrotreated heavy cute toxicity corresponding n of the ATE for classification at are assumed to have no a	n method of the Regulation (f EFINED IN REGULATION (f DL50 (OECD401) mg/kg bw Oral > 5000 Rat > 5000 Rat > 5000 Rat ATE	EU) No. 1272/2008~2021/8 EC) NO 1272/2008 : DL50 (OECD402) mg/kg bw Cutaneous 3160 Rabbit > 2000 Rat > 2000 Rabbit ATE mg/kg bw Cutaneous - ee GHS/CLP Table 3.1.2). The ponents and do not represent	CL50 (OECD40 mg/m3·4h Inhalati > 9300 F > 4300 F > 7630 F > 7630 F A mg/m3·4h Inhalati
11.1 11.1 1 1 1 1 1 1 1 1 1 1 1 1 1	No experimental toxica carried out by using th <u>INFORMATION ON F</u> <u>ACUTE TOXICITY:</u> Dose and lethal conce for individual ingredien Hydrocarbons, C9-C1 ² cyclics, <2% aromatics Zirconium 2-ethylhexa Naphtha (petroleum), I Estimates of acute tox for individual ingredien Hydrocarbons, C9-C1 ² cyclics, <2% aromatics Zirconium 2-ethylhexa Naphtha (petroleum), I (*) - Point estimates of a be used in the calculatio (-) - The components tha are ignored. - <u>No observed adverse</u> Not available	blogical data on the prepa e conventional calculation AZARD CLASSES AS D Intrations its: I, n-alkanes, isoalkanes, onoate nydrotreated heavy icity (ATE) its: I, n-alkanes, isoalkanes, onoate nydrotreated heavy cute toxicity corresponding n of the ATE for classification at are assumed to have no a	n method of the Regulation (I EFINED IN REGULATION (I DL50 (OECD401)) mg/kg bw Oral > 5000 Rat > 5000 Rat > 5000 Rat ATE mg/kg bw Oral - - - - - - - - - - - - -	EU) No. 1272/2008~2021/8 EC) NO 1272/2008 : DL50 (OECD402) mg/kg bw Cutaneous 3160 Rabbit > 2000 Rat > 2000 Rabbit ATE mg/kg bw Cutaneous - ee GHS/CLP Table 3.1.2). The ponents and do not represent	849 (CLP). CL50 (OECD40 mg/m3·4h Inhalati > 9300 F > 4300 F > 7630 F A' mg/m3·4h Inhalati mg/m3·4h Inhalati
	No experimental toxica carried out by using the <u>INFORMATION ON F</u> <u>ACUTE TOXICITY:</u> Dose and lethal conce for individual ingredien Hydrocarbons, C9-C1 ² cyclics, <2% aromatics Zirconium 2-ethylhexa Naphtha (petroleum), I Estimates of acute tox for individual ingredien Hydrocarbons, C9-C1 ² cyclics, <2% aromatics Zirconium 2-ethylhexa Naphtha (petroleum), I (*) - Point estimates of a be used in the calculatio (-) - The components that are ignored. - <u>No observed adverse</u> Not available - <u>Lowest observed adverse</u>	blogical data on the prepa e conventional calculation IAZARD CLASSES AS D Intrations its: I, n-alkanes, isoalkanes, sonoate hydrotreated heavy icity (ATE) its: I, n-alkanes, isoalkanes, sonoate hydrotreated heavy cute toxicity corresponding n of the ATE for classificatio at are assumed to have no a e effect level	n method of the Regulation (I EFINED IN REGULATION (I DL50 (OECD401)) mg/kg bw Oral > 5000 Rat > 5000 Rat > 5000 Rat ATE mg/kg bw Oral - - - - - - - - - - - - -	EU) No. 1272/2008~2021/8 EC) NO 1272/2008 : DL50 (OECD402) mg/kg bw Cutaneous 3160 Rabbit > 2000 Rat > 2000 Rabbit ATE mg/kg bw Cutaneous - ee GHS/CLP Table 3.1.2). The ponents and do not represent	CL50 (OECD40 mg/m3·4h Inhalati > 9300 R > 4300 R > 7630 R > 7630 R Mg/m3·4h Inhalati

Page 8/13 (Language:EN)



BRISA_BARNIZ INTERIOR- EXTERIOR SATINADO

Code: 12161

Previous revision: 23/02/2022



Version: 6

Revision: 14/12/2022

Date of printing: 14/12/2022

Inhalation: Not classified	ATE > 20000 mg/m3	-	Not classified as a product with acute toxicity GHS if inhaled (based on available data, the 3.1.3 classification criteria are not met).	
Skin: Not classified	ATE > 5000 mg/kg bw	-	Not classified as a product with acute toxicity GHS in contact with skin (based on available data, 3.1.3 the classification criteria are not met).	
Eyes: Not classified	Not available.	-	Not classified as a product with acute toxicity GHS by eye contact (lack of data).	
Ingestion: Not classified	ATE > 5000 mg/kg bw	-	Not classified as a product with acute toxicity GHS if swallowed (based on available data, the classification criteria are not met).	

GHS/CLP 3.1.3.6: Classification of mixtures based on ingredients of the mixture (additivity formula).

CORROSION / IRRITATION / SENSITISATION :

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
 Respiratory corrosion/irritation: Not classified 	-	-	Not classified as a product corrosive or irritant by inhalation (based on available data the classification criteria are not met).	GHS/CLP ,1.2.6. 3.8.3.4.
- Skin corrosion/irritation: Not classified	-	-	Not classified as a product corrosive or irritant in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.2.3.3.
- Serious eye damage/irritation: Not classified		-	Not classified as a product corrosive or irritant in contact with eyes (based on available data, the classification criteria are not met).	GHS/CLP 3.3.3.3.
- Respiratory sensitisation: Not classified	-	-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.
- Skin sensitisation: Not classified	-	-	Not classified as a product sensitising by skir contact (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.

GHS/CLP 3.2.3.3: Classification of the mixture when data are available for all components or only for some components. GHS/CLP 3.3.3.3: Classification of the mixture when data are available for all components or only for some components. GHS/CLP 3.4.3.3: Classification of the mixture when data are available for all components or only for some components. GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

- ASPIRATION HAZARD:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Aspiration hazard: Not classified	-		, , , , , , , , , , , , , , , , , , , ,	GHS/CLP 3.10.3.3.

GHS/CLP 3.10.3.3: Classification of the mixture when data are available for all components or only for some components.

SPECIFIC TARGET ORGANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Effects	SE/RE	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Cutaneous:	RE	Skin		- 1 1 5	GHS/CLP 1.2.4.
 Neurological effects: 	SE (1)	CNS		,	GHS/CLP 3.8.3.4.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

CMR EFFECTS:

- Carcinogenic effects:

It is not considered as a carcinogenic product.

- Genotoxicity:

It is not considered as a mutagenic product.

Toxicity for reproduction:

Does not harm fertility. Does not harm the unborn child.

Effects via lactation:

Not classified as a hazardous product for children breast-fed.

SAFETY DATA SHEET (REACH)

	isaval	BRISA RA		RIOR- EXTERIOR SATINADO					
\checkmark	ISAVAI pinturas	Code : 121							
ersion	n: 6 Revi	sion: 14/12/	2022	Previous revision	: 23/02/2022	Date of printing: 14/12/20			
	DELAYED AND IMME	EDIATE EFF	ECTS AS	WELL AS CHRONIC EFFECTS	FROM SHORT AND LON	NG-TERM EXPOSURE:			
	Routes of exposure May be absorbed by inhalation of vapour, through the skin and by ingestion.								
	May be absorbed by inh - Short-term exposure		bour, throug	h the skin and by ingestion.					
	Exposure to solvent vap mucous membrane and eyes may cause irritatio described in the exposu - Long-term or repeate	our concentra respiratory s n and reversil re to vapours ed exposure	ystem irrita ble damage . May caus <u>:</u>	cess of the stated occupational exp tion and adverse effects on kidneys e.If swallowed, may cause irritation of e drowsiness or dizziness.	, liver and central nervous s of the throat; other effects m	ystem.Liquid splashes in t ay be the same as			
				eval of natural fat from the skin, resu skin dryness or cracking.	liting in non-allergic contact	dermatitis and absorption			
	INTERACTIVE EFFEC	<u>CTS:</u>							
	Not available.								
	INFORMATION ABOU	JT TOXICO	CINETICS	, METABOLISM AND DISTRIBU	ITION:				
	- Dermal absorption:								
	Not available. - Basic toxicokinetics:								
	Not available.	-							
	ADDITIONAL INFORM	<u>VIATION:</u>							
.2	INFORMATION ON O	THER HAZ	ARDS:						
	Endocrine disrupting p	oroperties:							
	This product does not contain substances with endocrine disrupting properties identified or under evaluation.								
	Other information: No additional informatio	n available							
		in available.							
CTION	12: ECOLOGICAL INFO								
	No experimental ecoto mixture has been carr (CLP).	oxicological (e preparation as such is available prventional calculation method of					
	No experimental ecoto mixture has been carr	oxicological d ied out by us atic environm	sing the co			1272/2008~2021/849			
.1	No experimental ecoto mixture has been carr (CLP). <u>TOXICITY:</u> - Acute toxicity in aqua for individual ingredier Hydrocarbons, C9-C1 ⁻ cyclics, <2% aromatics	oxicological o ied out by us atic environm nts 1, n-alkanes s	sing the co	CL50 (OECD 203) mg/l·96hours 28, 1000 - Fishes	f the Regulation (EU) No. CE50 (OECD 202) mg/l·48hours 1000 - Daphniae	1272/2008~2021/849 CE50 (OECD 2 mg/l·72hc 1000 - Alg			
.1	No experimental ecoto mixture has been carr (CLP). <u>TOXICITY:</u> - Acute toxicity in aqua for individual ingredier Hydrocarbons, C9-C1 ⁻	oxicological o ied out by us atic environm nts 1, n-alkanes s unoate	nent , isoalkane	CL50 (OECD 203)	f the Regulation (EU) No. CE50 (OECD 202) mg/l·48hours	1272/2008~2021/849 CE50 (OECD 2 mg/l·72hc 1000 - Alg 500 - Alg			
.1	No experimental ecoto mixture has been carr (CLP). <u>TOXICITY:</u> - Acute toxicity in aqua for individual ingredier Hydrocarbons, C9-C1 ⁻ cyclics, <2% aromatics Zirconium 2-ethylhexa Naphtha (petroleum), <u>- No observed effect conditional Not available</u> <u>- Lowest observed effect</u>	exicological o ied out by us atic environm nts 1, n-alkanes s inoate hydrotreated concentration	nent , isoalkane d heavy	CL50 (OECD 203) mg/l·96hours es, 1000 - Fishes 100 - Fishes	f the Regulation (EU) No. CE50 (OECD 202) mg/l·48hours 1000 - Daphniae 100 - Daphniae	1272/2008~2021/849 CE50 (OECD 2 mg/l·72hc 1000 - Alg 500 - Alg			
.1	No experimental ecoto mixture has been carr (CLP). <u>TOXICITY:</u> - Acute toxicity in aqua for individual ingredier Hydrocarbons, C9-C1 ⁻ cyclics, <2% aromatics Zirconium 2-ethylhexa Naphtha (petroleum), I <u>- No observed effect of</u> Not available <u>- Lowest observed effect</u>	ect concentration	nent , isoalkane d heavy <u>n</u> <u>ation</u>	CL50 (OECD 203) mg/l·96hours es, 1000 - Fishes 100 - Fishes 8.2 - Fishes	f the Regulation (EU) No. CE50 (OECD 202) mg/l·48hours 1000 - Daphniae 100 - Daphniae 4.5 - Daphniae	1272/2008~2021/849 CE50 (OECD 2 mg/l·72hc 1000 - Alg 500 - Alg			
.1	No experimental ecoto mixture has been carr (CLP). <u>TOXICITY:</u> - Acute toxicity in aqua for individual ingredier Hydrocarbons, C9-C1 ⁻ cyclics, <2% aromatics Zirconium 2-ethylhexa Naphtha (petroleum), - <u>No observed effect of</u> Not available - <u>Lowest observed effect</u> Not available <u>ASSESSMENT OF AC</u> Aquatic toxicity	ect concentration	nent isoalkane heavy heavy <u>heavy</u> <u>heavy</u> <u>heavy</u>	CL50 (OECD 203) mg/l·96hours es, 1000 - Fishes 100 - Fishes 8.2 - Fishes	f the Regulation (EU) No. CE50 (OECD 202) mg/l·48hours 1000 - Daphniae 100 - Daphniae 4.5 - Daphniae	1272/2008~2021/849 CE50 (OECD 2 mg/l·72hc 1000 - Alg 500 - Alg 3.1 - Alg			
.1	No experimental ecoto mixture has been carr (CLP). <u>TOXICITY:</u> - Acute toxicity in aqua for individual ingredier Hydrocarbons, C9-C1 ⁻ cyclics, <2% aromatics Zirconium 2-ethylhexa Naphtha (petroleum), - <u>No observed effect of</u> Not available - <u>Lowest observed effect of</u> Not available <u>ASSESSMENT OF AC</u> Aquatic toxicity - Acute aquatic toxicity	ect concentration	sing the co nent , isoalkane d heavy <u>n</u> ation <u>XICITY:</u> Cat.	CL50 (OECD 203) mg/I·96hours es, 1000 - Fishes 100 - Fishes 8.2 - Fishes 8.2 - Fishes	f the Regulation (EU) No. CE50 (OECD 202) mg/l·48hours 1000 - Daphniae 100 - Daphniae 4.5 - Daphniae ment	1272/2008~2021/849 CE50 (OECD 2 mg/l·72hc 1000 - Alg 500 - Alg 3.1 - Alg Criteria			
.1	No experimental ecoto mixture has been carr (CLP). <u>TOXICITY:</u> - Acute toxicity in aqua for individual ingredier Hydrocarbons, C9-C1 ⁻ cyclics, <2% aromatics Zirconium 2-ethylhexa Naphtha (petroleum), - <u>No observed effect of</u> Not available - <u>Lowest observed effect</u> Not available <u>ASSESSMENT OF AC</u> Aquatic toxicity	ect concentration	sing the co nent , isoalkane d heavy <u>n</u> ation <u>XICITY:</u> Cat.	CL50 (OECD 203) mg/l·96hours es, 1000 - Fishes 100 - Fishes 8.2 - Fishes	f the Regulation (EU) No. CE50 (OECD 202) mg/l·48hours 1000 - Daphniae 100 - Daphniae 4.5 - Daphniae t.5 - Daphniae	1272/2008~2021/849 CE50 (OECD 2 mg/l·72hc 1000 - Al 500 - Al 3.1 - Al 3.1 - Al Criteria Atic life GHS/CLP 4.1.3.5.5.3. GHS/CLP			
.1	No experimental ecoto mixture has been carr (CLP). <u>TOXICITY:</u> - Acute toxicity in aqua for individual ingredier Hydrocarbons, C9-C1 ⁻ cyclics, <2% aromatics Zirconium 2-ethylhexa Naphtha (petroleum), - <u>No observed effect of</u> Not available <u>- Lowest observed effect</u> Not available <u>ASSESSMENT OF AC</u> Aquatic toxicity - Acute aquatic toxicity Not classified	ect concentration	sing the co nent , isoalkane d heavy <u>n</u> ation <u>XICITY:</u> Cat.	CL50 (OECD 203) mg/l·96hours es, 1000 - Fishes 100 - Fishes 8.2 - Fishes Not classified as a hazardous produ based on available data, the classif	f the Regulation (EU) No. CE50 (OECD 202) mg/l·48hours 1000 - Daphniae 100 - Daphniae 4.5 - Daphniae t.5 - Daphniae	1272/2008~2021/849 CE50 (OECD 2 mg/l·72hc 1000 - Alg 500 - Alg 500 - Alg 3.1 - Alg Criteria Atic life GHS/CLP 4.1.3.5.5.3.			
1	No experimental ecoto mixture has been carr (CLP). <u>TOXICITY:</u> - Acute toxicity in aqua for individual ingredier Hydrocarbons, C9-C1 ⁻ cyclics, <2% aromatics Zirconium 2-ethylhexa Naphtha (petroleum), - <u>No observed effect of</u> Not available <u>- Lowest observed effect of</u> Not available <u>ASSESSMENT OF AC</u> Aquatic toxicity - Acute aquatic toxicity Not classified - Chronic aquatic toxicit CLP 4.1.3.5.5.3: Classifi CLP 4.1.3.5.5.4: Classifi	atic environments 1, n-alkanes 1, n-alkane	sing the connent nent , isoalkane d heavy 1 ation XICITY: Cat. Cat. Cat. Cat. Cat. Cat. Cat. Cat.	CL50 (OECD 203) mg/l·96hours es, 1000 - Fishes 100 - Fishes 8.2 - Fishes Not classified as a hazardous produ based on available data, the classif	f the Regulation (EU) No. CE50 (OECD 202) mg/l·48hours 1000 - Daphniae 100 - Daphniae 4.5 - Daphniae ct with acute toxicity to aqua ication criteria are not met). <i>i</i> th long lasting effects.	1272/2008~2021/849 CE50 (OECD 2 mg/l·72hc 1000 - Alg 500 - Alg 3.1 - Alg Criteria atic life GHS/CLP 4.1.3.5.5.3. GHS/CLP 4.1.3.5.5.4.			
2.1	No experimental ecoto mixture has been carr (CLP). TOXICITY: - Acute toxicity in aqua for individual ingredier Hydrocarbons, C9-C1 ⁻ cyclics, <2% aromatics Zirconium 2-ethylhexa Naphtha (petroleum), - No observed effect of Not available - Lowest observed effect Not available ASSESSMENT OF AC Aquatic toxicity - Acute aquatic toxicity Not classified - Chronic aquatic toxicit CLP 4.1.3.5.5.3: Classif CLP 4.1.3.5.5.4: Classif PERSISTENCE AND - Biodegradability:	atic environm ts 1, n-alkanes s unoate hydrotreated concentration ect concentr QUATIC TO ity:	sing the connent nent , isoalkane d heavy 1 ation XICITY: Cat. Cat. Cat. Cat. Cat. Cat. Cat. Cat.	CL50 (OECD 203) mg/l·96hours es, 1000 - Fishes 100 - Fishes 8.2 - Fishes 8.2 - Fishes 8.2 - Fishes Not classified as a hazardous produ based on available data, the classified as a hazardous produ based on available data, the classified as a hazardous produ based on available data, the classified as a hazardous produ based on available data, the classified as a hazardous produ based on available data, the classified as a hazardous produ based on available data, the classified as a hazardous produ based on available data, the classified as a hazardous produ based on available data, the classified as a hazardous produ based on available data, the classified as a hazardous produ based on available data, the classified as a hazardous produ based on available data, the classified as a hazardous produ based on available data, the classified as a hazardous produ based on available data, the classified as a hazardous produ based on available data, the classified as a hazardous produ based on available data, the classified as a hazardous produ based on available data, the classified as a hazardous produ based on available data, the classified as a hazardous produ based on available data, based on summation based on summation	f the Regulation (EU) No. CE50 (OECD 202) mg/l·48hours 1000 - Daphniae 100 - Daphniae 4.5 - Daphniae ct with acute toxicity to aqua ication criteria are not met). <i>i</i> th long lasting effects.	1272/2008~2021/849 CE50 (OECD 2 mg/l·72hc 1000 - Alg 500 - Alg 3.1 - Alg Criteria atic life GHS/CLP 4.1.3.5.5.3. GHS/CLP 4.1.3.5.5.4.			
2.1	No experimental ecoto mixture has been carr (CLP). <u>TOXICITY:</u> - Acute toxicity in aqua for individual ingredier Hydrocarbons, C9-C1 ⁻ cyclics, <2% aromatics Zirconium 2-ethylhexa Naphtha (petroleum), I - No observed effect of Not available - Lowest observed effect of Not available <u>ASSESSMENT OF AC</u> Aquatic toxicity - Acute aquatic toxicity Not classified - Chronic aquatic toxici CLP 4.1.3.5.5.3: Classifi CLP 4.1.3.5.5.4: Classifi PERSISTENCE AND - Biodegradability: Not readily biodegradabi Aerobic biodegradatio	atic environments atic environments 1, n-alkanes s noate hydrotreated concentration ect concentration QUATIC TO : ity: ity: ication of a mention DEGRADAE ole. n	sing the connent nent , isoalkane d heavy 1 ation XICITY: Cat. Cat. Cat. Cat. Cat. Cat. Cat. Cat.	CL50 (OECD 203) mg/l·96hours es, 1000 - Fishes 100 - Fishes 8.2 - Fishes Not classified as a hazardous produ based on available data, the classif HARMFUL: Harmful to aquatic life w cute hazards, based on summation hronic (long term) hazards, based o	f the Regulation (EU) No. CE50 (OECD 202) mg/l·48hours 1000 - Daphniae 100 - Daphniae 4.5 - Daphniae 4.5 - Daphniae ct with acute toxicity to aqua ication criteria are not met). /ith long lasting effects. of classified components. n summation of classified com- %DBO/DQC	1272/2008~2021/849 CE50 (OECD 2 mg/l·72ho 1000 - Alg 500 - Alg 3.1 - Alg atic life GHS/CLP 4.1.3.5.5.3. GHS/CLP 4.1.3.5.5.4.			
2.1	No experimental ecoto mixture has been carr (CLP). TOXICITY: - Acute toxicity in aqua for individual ingredier Hydrocarbons, C9-C1 ⁻ cyclics, <2% aromatics Zirconium 2-ethylhexa Naphtha (petroleum), 1 - No observed effect of Not available - Lowest observed effect of Not available ASSESSMENT OF AC Aquatic toxicity - Acute aquatic toxicity Not classified - Chronic aquatic toxicit CLP 4.1.3.5.5.4: Classifi CLP 4.1.3.5.5.4: Classifi PERSISTENCE AND - Biodegradability: Not readily biodegradab Aerobic biodegradatio for individual ingredier	atic environments atic environments 1, n-alkanes s noate hydrotreated concentration ect concentration QUATIC TO: ity: ication of a mention DEGRADAE ole. n nts	sing the content of the second	CL50 (OECD 203) mg/l·96hours 28, 1000 - Fishes 100 - Fishes 8.2 - Fishes Not classified as a hazardous produ based on available data, the classif HARMFUL: Harmful to aquatic life w cute hazards, based on summation hronic (long term) hazards, based o mg02/g	f the Regulation (EU) No. CE50 (OECD 202) mg/l-48hours 1000 - Daphniae 100 - Daphniae 4.5 - Daphniae 4.5 - Daphniae ct with acute toxicity to aqua ication criteria are not met). ith long lasting effects. of classified components. n summation of classified co %DBO/DQC 5 days 14 days 28 days	1272/2008~2021/849 CE50 (OECD 2 mg/l·72ho 1000 - Alg 500 - Alg 3.1 - Alg atic life GHS/CLP 4.1.3.5.5.3. GHS/CLP 4.1.3.5.5.4. omponents.			
2.1	No experimental ecoto mixture has been carr (CLP). <u>TOXICITY:</u> - Acute toxicity in aqua for individual ingredier Hydrocarbons, C9-C1 ⁻ cyclics, <2% aromatics Zirconium 2-ethylhexa Naphtha (petroleum), I - <u>No observed effect of</u> Not available <u>- Lowest observed effect of</u> Not available <u>Assessment of Ad</u> <u>Aquatic toxicity</u> - Acute aquatic toxicity Not classified - Chronic aquatic toxicit <u>CLP 4.1.3.5.5.3</u> : Classiff <u>CLP 4.1.3.5.5.4</u> : Classiff <u>CLP 4.1.3.5.5.4</u> : Classiff <u>PERSISTENCE AND</u> <u>- Biodegradability:</u> Not readily biodegradabi <u>Aerobic biodegradatio</u> for individual ingredier Hydrocarbons, C9-C1 ⁻	atic environments atic environments 1, n-alkanes s noate hydrotreated concentration ect concentration ect concentration ication of a mentication of a mentication DEGRADAE ole. n nts 1, n-alkanes	sing the content of the second	CL50 (OECD 203) mg/l·96hours 28, 1000 - Fishes 100 - Fishes 8.2 - Fishes Not classified as a hazardous produ based on available data, the classif HARMFUL: Harmful to aquatic life w cute hazards, based on summation hronic (long term) hazards, based o mg02/g	f the Regulation (EU) No. CE50 (OECD 202) mg/l·48hours 1000 - Daphniae 100 - Daphniae 4.5 - Daphniae 4.5 - Daphniae ct with acute toxicity to aqua ication criteria are not met). /ith long lasting effects. of classified components. n summation of classified com- %DBO/DQC	1272/2008~2021/849 CE50 (OECD 2) mg/l·72ho 1000 - Alg 500 - Alg 3.1 - Alg atic life GHS/CLP 4.1.3.5.5.3. GHS/CLP 4.1.3.5.5.4. omponents.			
2.1	No experimental ecoto mixture has been carr (CLP). TOXICITY: - Acute toxicity in aqua for individual ingredier Hydrocarbons, C9-C1 ⁻ cyclics, <2% aromatics Zirconium 2-ethylhexa Naphtha (petroleum), 1 - No observed effect of Not available - Lowest observed effect of Not available ASSESSMENT OF AC Aquatic toxicity - Acute aquatic toxicity Not classified - Chronic aquatic toxicit CLP 4.1.3.5.5.4: Classifi CLP 4.1.3.5.5.4: Classifi PERSISTENCE AND - Biodegradability: Not readily biodegradab Aerobic biodegradatio for individual ingredier	atic environments atic environments 1, n-alkanes s anoate hydrotreated concentration <u>ect concentration</u> <u>ect concentration</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u> <u>ity:</u>	sing the content of the second	CL50 (OECD 203) mg/l·96hours 28, 1000 - Fishes 100 - Fishes 8.2 - Fishes Not classified as a hazardous produ based on available data, the classif HARMFUL: Harmful to aquatic life w cute hazards, based on summation hronic (long term) hazards, based o mg02/g	f the Regulation (EU) No. CE50 (OECD 202) mg/l-48hours 1000 - Daphniae 100 - Daphniae 4.5 - Daphniae 4.5 - Daphniae ct with acute toxicity to aqua ication criteria are not met). ith long lasting effects. of classified components. n summation of classified co %DBO/DQC 5 days 14 days 28 days	1272/2008~2021/849 CE50 (OECD 2 mg/l·72hc 1000 - Alg 500 - Alg 3.1 - Alg atic life GHS/CLP 4.1.3.5.5.3. GHS/CLP 4.1.3.5.5.4. omponents. D Biodegradability D E			

 Naphtha (petroleum), hydrotreated heavy

 Note: Biodegradability data correspond to an average of data from various bibliographic sources.

isaval

BRISA_BARNIZ INTERIOR- EXTERIOR SATINADO Code : 12161	

	n: 6 Revision: 14/12/2022	Previous revision: 23	3/02/2022	Date of printing: 14/12/2022			
	- Hydrolysis:						
	Not available.						
	- Photodegradability:						
	Not available.						
2.3	BIOACCUMULATIVE POTENTIAL:						
	Not available.						
	Bioaccumulation	logPow	BCF	Potentia			
	for individual ingredients	logi ow	L/kg	T Otoria			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes,	5.65	100 (calculated)	Lo			
	cyclics, <2% aromatics	5.05	Too (calculated)	LU			
				NI 1.			
	Zirconium 2-ethylhexanoate	1.9	8.3 (calculated)	No bioaccumulab			
	Naphtha (petroleum), hydrotreated heavy	5.65	100 (calculated)	Lo			
2.4	MOBILITY IN SOIL:						
	Not available						
	Mobility	log Poc	Constant of Henry	Potenti			
	for individual ingredients	Ũ	Pa⋅m3/mol 20ºC				
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes,	4,9		Lov			
	cyclics, <2% aromatics	.,-					
	Zirconium 2-ethylhexanoate	1,75		No bioaccumulab			
	Naphtha (petroleum), hydrotreated heavy	4,91		Lo			
0.5	RESULTS OF PBT AND VPVB ASSESMENT:(A	•	a 1007/2006;)				
2.5			<u>0. 1907/2008.)</u>				
	Does not contain substances that fulfil the PBT/vPvB	criteria.					
2.6	ENDOCRINE DISRUPTING PROPERTIES:						
	This product does not contain substances with endoc	rine disrupting properties identifie	ed or under evaluation.				
2.7	OTHER ADVERSE EFFECTS:						
	- Ozone depletion potential:						
	Not available.						
	- Photochemical ozone creation potential:						
	- <u>Photochemical ozone creation potential:</u> Not available.						
	 <u>Photochemical ozone creation potential:</u> Not available. <u>Earth global warming potential:</u> 						
	- <u>Photochemical ozone creation potential:</u> Not available.						
	 <u>Photochemical ozone creation potential:</u> Not available. <u>Earth global warming potential:</u> 						
	- <u>Photochemical ozone creation potential:</u> Not available. - <u>Earth global warming potential:</u> In case of fire or incineration liberates CO2. 13: DISPOSAL CONSIDERATIONS	8/98/EC~Regulation (EU) no. 1	1357/2014:				
	- Photochemical ozone creation potential: Not available. - Earth global warming potential: In case of fire or incineration liberates CO2. 13: DISPOSAL CONSIDERATIONS WASTE TREATMENT METHODS:Directive 2005			r revaluation or recycling			
	- Photochemical ozone creation potential: Not available. - Earth global warming potential: In case of fire or incineration liberates CO2. 13: DISPOSAL CONSIDERATIONS WASTE TREATMENT METHODS:Directive 2000 Take all necessary measures to prevent the production	on of waste whenever possible. A	nalyse possible methods fo				
	- Photochemical ozone creation potential: Not available. - Earth global warming potential: In case of fire or incineration liberates CO2. 13: DISPOSAL CONSIDERATIONS WASTE TREATMENT METHODS:Directive 2005	on of waste whenever possible. A ose at an authorised waste collec	nalyse possible methods fo ction point. Waste should be	handled and disposed ir			
	- Photochemical ozone creation potential: Not available. - Earth global warming potential: In case of fire or incineration liberates CO2. 13: DISPOSAL CONSIDERATIONS WASTE TREATMENT METHODS:Directive 2000 Take all necessary measures to prevent the production Do not discharge into drains or the environment, disp	on of waste whenever possible. A ose at an authorised waste collec s. For exposure controls and pers	nalyse possible methods fo ction point. Waste should be conal protection measures,	e handled and disposed ir			
	- Photochemical ozone creation potential: Not available. - Earth global warming potential: In case of fire or incineration liberates CO2. 13: DISPOSAL CONSIDERATIONS WASTE TREATMENT METHODS:Directive 2000 Take all necessary measures to prevent the production Do not discharge into drains or the environment, disp accordance with current local and national regulation	on of waste whenever possible. A ose at an authorised waste collec s. For exposure controls and pers ~2015/720/EU, Decision 2000	nalyse possible methods fo stion point. Waste should be sonal protection measures, / <u>532/EC~2014/955/EU:</u>	handled and disposed ir see section 8.			
	- Photochemical ozone creation potential: Not available. - Earth global warming potential: In case of fire or incineration liberates CO2. 13: DISPOSAL CONSIDERATIONS WASTE TREATMENT METHODS:Directive 2000 Take all necessary measures to prevent the production Do not discharge into drains or the environment, disp accordance with current local and national regulation Disposal of empty containers:Directive 94/62/EC Emptied containers and packaging should be disposed packaging as hazardous waste will depend on the de	on of waste whenever possible. A ose at an authorised waste collect s. For exposure controls and pers ~2015/720/EU, Decision 2000 ed in accordance with currently loo gree of empting of the same, beir	nalyse possible methods fo stion point. Waste should be sonal protection measures, <u>/532/EC~2014/955/EU:</u> cal and national regulations ng the holder of the residue	handled and disposed in see section 8. .The classification of responsible for their			
	- Photochemical ozone creation potential: Not available. - Earth global warming potential: In case of fire or incineration liberates CO2. 13: DISPOSAL CONSIDERATIONS WASTE TREATMENT METHODS:Directive 2003 Take all necessary measures to prevent the production Do not discharge into drains or the environment, disp accordance with current local and national regulation Disposal of empty containers:Directive 94/62/EC Emptied containers and packaging should be disposed packaging as hazardous waste will depend on the de classification, in accordance with Chapter 15 01 of De	on of waste whenever possible. A ose at an authorised waste collect s. For exposure controls and pers ~2015/720/EU, Decision 2000/ ed in accordance with currently loo gree of empting of the same, beir ecision 2000/532/EC, and forward	nalyse possible methods fo ction point. Waste should be conal protection measures, / <u>532/EC~2014/955/EU:</u> cal and national regulations ng the holder of the residue ling to the appropriate final	handled and disposed in see section 8. .The classification of responsible for their			
<u>ECTION</u> 13.1	- Photochemical ozone creation potential: Not available. - Earth global warming potential: In case of fire or incineration liberates CO2. 13: DISPOSAL CONSIDERATIONS WASTE TREATMENT METHODS:Directive 2000 Take all necessary measures to prevent the production Do not discharge into drains or the environment, disp accordance with current local and national regulation Disposal of empty containers:Directive 94/62/EC Emptied containers and packaging should be disposed packaging as hazardous waste will depend on the ded classification, in accordance with Chapter 15 01 of Decontaminated containers and packaging, adopt the sate	on of waste whenever possible. A ose at an authorised waste collect s. For exposure controls and pers ~2015/720/EU, Decision 2000, ed in accordance with currently lo- gree of empting of the same, beir ecision 2000/532/EC, and forward ame measures as for the product	nalyse possible methods fo ction point. Waste should be conal protection measures, / <u>532/EC~2014/955/EU:</u> cal and national regulations ng the holder of the residue ling to the appropriate final	handled and disposed in see section 8. .The classification of responsible for their			
	- Photochemical ozone creation potential: Not available. - Earth global warming potential: In case of fire or incineration liberates CO2. 13: DISPOSAL CONSIDERATIONS WASTE TREATMENT METHODS:Directive 2003 Take all necessary measures to prevent the production Do not discharge into drains or the environment, disp accordance with current local and national regulation Disposal of empty containers:Directive 94/62/EC Emptied containers and packaging should be disposed packaging as hazardous waste will depend on the de classification, in accordance with Chapter 15 01 of De	on of waste whenever possible. A ose at an authorised waste colled s. For exposure controls and pers ~2015/720/EU, Decision 2000, ed in accordance with currently loo gree of empting of the same, beir ecision 2000/532/EC, and forward ame measures as for the product duct:	nalyse possible methods fo ction point. Waste should be conal protection measures, (532/EC~2014/955/EU: cal and national regulations ing the holder of the residue ling to the appropriate final in itself.	handled and disposed in see section 8. .The classification of responsible for their			

	İSAVA	Code : 121		RIOR SATINADO		
/ersior	n: 6 Revis	sion: 14/12	/2022	Previous revision: 23/02/202	22 Date of printing: 14/12/20	
	N 14: TRANSPORT INFO	RMATION				
14.1	UN NUMBER OR ID N	NUMBER:				
	1263					
14.2	UN PROPER SHIPPIN PAINT	<u>NG NAME:</u>				
14.3	TRANSPORT HAZAR	D CLASS(E	ES):			
	Transport by road (AD					
	Transport by rail (RID	<u>2021):</u> ´				
	Good not submitted to A	DR.				
					ort for viscous liquids in packages with capac D L according to 2.2.3.1.5. (ADR) or under 30 according to 2.3.2.5. (IMDO	
	Transport by sea (IMD)G <u>39-18):</u>				
	- Class:		3			
	- Packing group:	C).				
	- Emergency Sheet (Em - First Aid Guide (MFAG		F-E,S_E 310,313	3		
	- Marine pollutant:		No.			
	- Transport document:		Shipping Bill of lading].		
	Transport by air (ICAC	<u>)/IATA 2021</u>				
	- Class: - Packing group:		3 			
	- Transport document:		Air Bill of lading.			
				3		
	Transport by inland wa	aterways (A	<u>DN):</u>			
	Not available					
4.4	PACKING GROUP:					
	See section 14.3					
4.5	ENVIRONMENTAL H/ Not applicable (not class		ardous for the environm	ent)		
4.6	SPECIAL PRECAUTIO			entj.		
4.0				to in case of accident or spill. Alw	ays transport in closed containers that are	
	upright and secure. Ens			·		
4.7	MARITIME TRANSPO	ORT IN BUL	K ACCORDING TO I	MO INSTRUMENTS:		
	Not available.					
CTION	N 15: REGULATORY INFO	ORMATION				
5.1					IC FOR THE SUBSTANCE OR MIXTUR	
				d throughout this Safety Data She	eet.	
	Restrictions on manufactorial See section 1.2	acture, plac	ing on market and use	<u>e:</u>		
	Tactile warning of dan	der.				
		•	eria are not met)			
	Not applicable (the classification criteria are not met). Child safety protection:					
	Not applicable (the classification criteria are not met).					
	VOC information on the label:					
	Contains VOC max. 372,8 for the product ready for use - The limit value 2004/42/EC-IIA cat. e) Trim varnish for wood, solvent-borne. is					
	VOC max. 400 g/l (2010)					
	OTHER REGULATIONS: Control of the risks inherent in major accidents (Seveso III):					
	See section 7.2	<u>ierent in ma</u>	ijor accidents (Seveso	<u>5 III):</u>		
	Other local legislations	s.				
			le existence of local rec	gulations applicable to the chemic	al.	
5.2	CHEMICAL SAFETY					
	A chemical safety asses			his mixture.		

isava

pintu

BRISA_BARNIZ INTERIOR- EXTERIOR SATINADO

Code : 12161

Version	6 Revision: 14/12/2022	Previous revision: 23/02/2022	Date of printing: 14/12/2022				
SECTION	16 : OTHER INFORMATION						
16.1	TEXT OF THE PHRASES AND NOTES REFERENCE	ED IN SECTIONS 2 AND/OR 3:					
	Hazard statements according the Regulation (EU) No	. 1272/2008~2021/849 (CLP), Annex III:					
	H226 Flammable liquid and vapour. H304 May be fatal if s drowsiness or dizziness. H411 Toxic to aquatic life with lon Repeated exposure may cause skin dryness or cracking. I	wallowed and enters airways. H315 Causes sk g lasting effects. H412 Harmful to aquatic life v	vith long lasting effects. EUH066				
	Notes related to the identification, classification and la	belling of the substances or mixtures:					
	Note P : The harmonised classification as a carcinogen or 0,1 % w/w benzene (Einecs No 200-753-7), in which case also for those hazard classes. Where the substance is not (P102-)P260-P262-P301 + P310- P331 shall apply.	a classification in accordance with Title II of thi	s Regulation shall be performed				
	EVALUATION OF THE INFORMATION ON THE DAM	NGER OF MIXTURES:					
	See sections 9.1, 11.1 and 12.1.						
	ADVICES ON ANY TRAINING APPROPRIATE FOR						
	It is recommended for all staff that will handle this product provide understanding and interpretation of Safety Data SI MAIN LITERATURE REFERENCES AND SOURCES	neets and labelling of products as well.	and prevention, in order to				
	· European Chemicals Agency: ECHA, http://echa.europa.						
	· Access to European Union Law, http://eur-lex.europa.eu/						
	· Industrial Solvents Handbook, Ibert Mellan (Noyes Data (Co., 1970).					
	Threshold Limit Values, (AGCIH, 2017).	name and by mand (ADD 2021)					
	European agreement on the international carriage of dan International Maritime Dangerous Goods Code IMDG inc						
	· International Maritime Dangerous Goods Code IMDG including Amendment 39-18 (IMO, 2018). ABBREVIATIONS AND ACRONYMS:						
	List of abbreviations and acronyms that can be used (but not necessarily used) in this Safety Data Sheet:						
	 REACH: Regulation concerning the Registration, Evaluat GHS: Globally Harmonized System of Classification and CLP: European regularion on Classificatin, Labelling amo EINECS: European Inventory of Existing Commercial Ch ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (Division of the Americ: UVCB: Substances of Unknown or Variable composition, SVHC: Substances of Very High Concern. PBT: Persistent, bioaccumulable and toxic substances. vPvB: Very persistent and very bioaccumulable substance VOC: Volatile Organic Compounds. DNEL: Derived No-Effect Level (REACH). PNEC: Predicted No-Effect Concentration (REACH). LC50: Lethal concentration, 50 percent. LD50: Lethal dose, 50 percent. UN: United Nations Organisation. ADR: European agreement concerning the international of RID: Regulations concerning the international transport of IMDG: International Maritime code for Dangerous Goods IATA: International Air Transport Association. 	Labelling of Chemicals of the United Nations. I Packaging of substances and chemical mixtu emical Substances. an Chemical Society). complex reaction products or biological materi es. es.	res.				
	SAFETY DATA SHEET REGULATIONS:						
	Safety Data Sheet in accordance with Article 31 of Regula HISTORIC: REVISION:	tion (EC) No. 1907/2006 (REACH) and Annex	of Regulation (EU) No. 2020/878.				
	Version: 5 23/02/2022						
	Version: 6 14/12/2022						
	Changes since previous Safety Data Sheet:						
	Changes that have been introduced with respect to the pressure of the Regulation (EU) No. 2020/878: All sections.		· ·				
I he inforn	nation of this Safety Data Sheet, is based on the present st	ate of knowledge and on current UE and nation	al laws, as the users" working				

conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product"s properties.