



Previous revision: 11/02/2022 Version: 5 Revision: 12/12/2022 Date of printing: 12/12/2022

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

PRODUCT IDENTIFIER:

BD-BLANCO

Code: 12191 UFI: 1PR2-61UA-H00R-1SHX

RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST: 1.2

Intended uses (main technical functions): [] Industrial [X] Professional [X] Consumers

Dye.

Sectors of use:

Consumer uses (SU21), Professional uses (SU22),

Types of PCN use:

Dyes.

Uses advised against:

This product is not recommended for any use or sector of use (industrial, professional or consumer) other than those previously listed as "Intended or identified uses".

Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006:

Not restricted.

DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET: 1.3

PINTURAS ISAVAL, S.L.

c/Velluters, Parcela 2-14- P.I. Casanova - 46394 Ribarroja del Turia (Valencia) ESPAÑA

Phone number: +34 96 1640001 - Fax: +34 96 1640002 - www.isaval.es - E-mail address of the person responsible for the Safety Data Sheet:

atencionalcliente@isaval.es

EMERGENCY TELEPHONE NUMBER: 1.4

+34 96 1640001 8:00-18:00 h.



National Poisons Information Service (NPIS) - In England, Wales or Scotland: dial 111 - In N Ireland: contact your local GP or pharmacist during normal hours.

SECTION 2: HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE: 2.1

Classification of mixtures is carried out in accordance with the following principles: a) when data (tests) for the classification of mixtures are available, generally is carried out based on these data, b) in the absence of data (tests) for mixtures are generally used interpolation or extrapolation methods of assessing the risk, using the available data for mixtures similarly classified, and c) in the absence of tests and information which would allow to apply interpolation or extrapolation techniques, methods are used to classify risk assessment based on the data of the individual components in the mixture.

Classification in accordance with Regulation (EU) No. 1272/2008~2021/849 (CLP):

WARNING:Flam. Liq. 3:H226|STOT SE (narcosis) 3:H336

Danger class		Classification of the mixture	Cat.	Routes of exposure	Target organs	Effects
Physicochemical:	(b)	Flam. Liq. 3:H226 c)	Cat.3	-	-	-
Human health:	\Diamond	STOT SE (narcosis) 3:H336 c)	Cat.3	Inhalation	CNS	Narcosis
Environment: Not classified						

Full text of hazard statements mentioned is indicated in section 16.

Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.

2.2 LABEL ELEMENTS:



This product is labelled with the signal word WARNING in accordance with Regulation (EU) No. 1272/2008~2021/849 (CLP)

- Hazard statements:

H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.

- Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves, clothing and eye protection. In case of inadequate ventilation wear respiratory protection. P304+P340-P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if

you feel unwell.

Dispose of contents/container to hazardous or special waste collection point.

- Supplementary statements:

- Substances that contribute to classification:

2-methoxy-1-methylethyl acetate





REACH

Previous revision: 11/02/2022 Version: 5 Revision: 12/12/2022 Date of printing: 12/12/2022

2.3 **OTHER HAZARDS:**

Hazards which do not result in classification but which may contribute to the overall hazards of the mixture:

- Other physicochemical hazards:

Vapours may form with air a mixture potentially flammable or explosive.

- Other adverse human health effects:

Prolonged contact may cause skin dryness.

- Other negative environmental effects:

Does not contain substances that fulfil the PBT/vPvB criteria.

Endocrine disrupting properties:

This product does not contain substances with endocrine disrupting properties identified or under evaluation.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCES: 3.1

Not applicable (mixture).

MIXTURES: 3.2

This product is a mixture.

Chemical description:

Mixture of pigments, resins and additives in organic solvents.

HAZARDOUS INGREDIENTS

Substances taking part in a percentage higher than the exemption limit:

15 < C < 20 %

2-methoxy-1-methylethyl acetate

CAS: 108-65-6, EC: 203-603-9, REACH: 01-2119475791-29

CLP: Warning: Flam. Liq. 3:H226 | STOT SE (narcosis) 3:H336

Does not contain other components or impurities which will influence the classification of the product.

Stabilizers:

None.

Reference to other sections:

For more information on hazardous ingredients, see sections 8, 11, 12 and 16.

SUBSTANCES OF VERY HIGH CONCERN (SVHC):

List updated by ECHA on 10/06/2022.

Substances SVHC subject to authorisation, included in Annex XIV of Regulation (EC) no. 1907/2006:

Substances SVHC candidate to be included in Annex XIV of Regulation (EC) no. 1907/2006:

None.

PERSISTENT, BIOACCUMULABLE AND TOXIC PBT, OR VERY PERSISTENT AND VERY BIOACCUMULABLE VPVB

SUBSTANCES:

Does not contain substances that fulfil the PBT/vPvB criteria.





Previous revision: 11/02/2022 Version: 5 Revision: 12/12/2022 Date of printing: 12/12/2022

SECTION 4: FIRST AID MEASURES

DESCRIPTION OF FIRST AID MEASURES:



Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Lifeguards should pay attention to self-protection and use the recommended protective equipment if there is a possibility of exposure. Wear protective gloves when administering first aid.

Route of exposure	Symptoms and effects, acute and delayed	Description of first-aid measures
Inhalation:	Inhalation of solvent vapours may produce headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness.	Remove the patient out of the contaminated area into the fresh air.If breathing is irregular or stops, administer artificial respiration.If the person is unconscious, place in appropriate recovery position.Keep the patient warm and at rest until medical attention arrives.
Skin:	Prolonged contact may cause skin dryness.	Remove immediately contaminated clothing.Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser.
Eyes:	Contact with the eyes produces redness and pain.	Remove contact lenses.Rinse eyes copiously by irrigation with plenty of clean, fresh water, holding the eyelids apart.If irritation persists, consult a physician.
Ingestion:	If swallowed, may cause irritation of the throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea.	If swallowed, seek medical advice immediately and show container or label. Do not induce vomiting, due to the risk of aspiration.Keep the patient at rest.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

The main symptoms and effects are indicated in sections 4.1 and 11.1

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Notes to physician:

4.3

Treatment should be directed at the control of symptoms and the clinical condition of the patient...

Antidotes and contraindications:

Specific antidote not known.

SECTION 5: FIREFIGHTING MEASURES

EXTINGUISHING MEDIA:)

Extinguishing powder or CO2

SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE: 5.2

As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, Carbon dioxide. Exposure to combustion or decomposition products may be a hazard to health.

ADVICE FOR FIREFIGHTERS: 5.3

Special protective equipment:

Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or is not being used, combat fire from a sheltered position or from a safe distance. The standard EN469 provides a basic level of protection for chemical incidents.

Other recommendations:

Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow firefighting residue to enter drains, sewers or water courses.





Previous revision: 11/02/2022 Version: 5 Revision: 12/12/2022 Date of printing: 12/12/2022

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product. Avoid breathing vapours. Keep people without protection in opposition to the wind direction.

ENVIRONMENTAL PRECAUTIONS 6.2

> Avoid contamination of drains, surface or subterranean water and soil.In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP: 6.3

Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc..). Clean preferably with a biodegradable detergent. Keep the remains in a closed container.

REFERENCE TO OTHER SECTIONS: 6.4

For contact information in case of emergency, see section 1.

For information on safe handling, see section 7.

For exposure controls and personal protection measures, see section 8.

For waste disposal, follow the recommendations in section 13.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: 7.1

Comply with the existing legislation on health and safety at work.

- General recommendations:

Avoid any type of leakage or escape. Keep the container tightly closed.

- Recommendations for the prevention of fire and explosion risks:

Vapours are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reach distant ignition sources and flame up or explode. Due to its flammability, this material should only be used in areas from which all naked lights and other sources of ignition have been excluded and away from other heat or electrical sources. Switch mobile phones off and do not smoke. No tools with a potential for sparks should be used.

42* °C CLP 2.6.4.3. Flashpoint

Autoignition temperature: Not applicable.

Lower/upper flammability or explosive limits: 1,5* - 10,9* % Volume 25°C

- Recommendations for the prevention of toxicological risks:

Do not eat, drink or smoke while handling. After handling, wash hands with soap and water. For exposure controls and personal protection measures, see section 8.

- Recommendations for the prevention of environmental contamination:

It is not considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES: 7.2

Forbid the entry to unauthorized persons. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area. If possible, avoid direct contact with sunlight. Avoid extreme humidity conditions. In order to avoid leakages, the containers, after use, should be closed carefully and placed in a vertical position. For more information, see section 10.

- Class of store:

According to current legislation.

- Maximum storage period:

12 Months

- Temperature interval:

min:5 °C, max:40 °C (recommended).

- Incompatible materials:

Keep away from oxidizing agents, acids, metals.

- Type of packaging:

According to current legislation.

- Limit quantity (Seveso III): Directive 2012/18/EU:

Not applicable (product for non industrial use).

SPECIFIC END USE(S): 7.3

For the use of this product particular recommendations apart from that already indicated are not available.





Version: 5 Revision: 12/12/2022 Previous revision: 11/02/2022 Date of printing: 12/12/2022

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS:

If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

- OCCUPATIONAL EXPOSURE LIMIT VALUES (WEL)

EH40/2005 WELs (United	Year	WEL-TWA		WEL-STEL		Remarks
Kingdom) 2018		ppm	mg/m3	ppm	mg/m3	
2-methoxy-1-methylethyl acetate	-	50	275	100	550	Sk, Recommended

WEL - Workplace Exposure Limit, TWA - Time Weighted Average (8 hours), STEL - Short Term Exposure Limit (15 min).

Sk - Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

- Dermal (Sk):

Means that, in exposures to this substance, the contribution by the cutaneous route, including the mucous membranes and eyes, may result significant for the overall body content if no measures are taken to prevent absorption. There are some chemicals for which dermal absorption, both in liquid and vapour phases, can be very high, and this route of entry may be or equal or greater importance even that inhalation pathway. In these situations, the use of a biological control is essential in order to quantify the overall amount of contaminant absorbed.

- BIOLOGICAL LIMIT VALUES:

Not established

- DERIVED NO-EFFECT LEVEL (DNEL):

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from a occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

····································						
- DERIVED NO-EFFECT LEVEL, WORKERS:- Systemic effects, acute and chronic:	DNEL Inhalation mg/m3		DNEL Cutaneous mg/kg bw/d		DNEL Oral mg/kg bw/d	
2-methoxy-1-methylethyl acetate	- (a)	275 (c)	- (a) 15	53,5 (c)	- (a)	- (c)
- DERIVED NO-EFFECT LEVEL, WORKERS:- Local effects, acute and chronic:	DNEL Inhalation mg/m3		DNEL Cutaneous mg/cm2		DNEL Eyes mg/cm2	
2-methoxy-1-methylethyl acetate	- (a)	- (c)	- (a)	- (c)	- (a)	- (c)
- DERIVED NO-EFFECT LEVEL, GENERAL POPULATION:- Systemic effects, acute and chronic:	DNEL Inhalation mg/m3		DNEL Cutaneous mg/kg bw/d		DNEL Eyes mg/kg bw/d	
2-methoxy-1-methylethyl acetate	- (a)	33 (c)	- (a) 5	54,8 (c)	- (a)	1,67 (c)
- LOCAL EFFECTS, ACUTE AND CHRONIC:- Local effects, acute and chronic:	DNEL Inhalation mg/m3		DNEL Cutaneous mg/cm2		DNEL Eyes mg/cm2	
2-methoxy-1-methylethyl acetate	- (a)	- (c)	- (a)	- (c)	- (a)	- (c)

- (a) Acute, short-term exposure, (c) Chronic, long-term or repeated exposure.
- (-) DNEL not available (without data of registration REACH).

- PREDICTED NO-EFFECT CONCENTRATION (PNEC):

PNEC Fresh water	PNEC Marine	PNEC Intermittent
mg/l	mg/l	mg/l
0.635	0.0635	6.35
PNEC STP	PNEC Sediments	PNEC Sediments
mg/l	mg/kg dw/d	mg/kg dw/d
100	3.29	0.329
PNEC Air	PNEC Soil	PNEC Oral
mg/m3	mg/kg dw/d	mg/kg dw/d
-	0.29	-
	mg/l 0.635 PNEC STP mg/l 100 PNEC Air	mg/l mg/l mg/l

(-) - PNEC not available (without data of registration REACH).

8.2 EXPOSURE CONTROLS: ENGINEERING MEASURES:







Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.

<u>- Protection of respiratory system:</u> Avoid the inhalation of vapours.

- Protection of eyes and face:





Version: 5 Revision: 12/12/2022 Previous revision: 11/02/2022 Date of printing: 12/12/2022

It is recommended to install water taps or sources with clean water close to the working area.

- Protection of hands and skin:

It is recommended to install water taps or sources with clean water close to the working area. Barrier creams may help to protect the exposed areas of the skin.Barrier creams should not be applied once exposure has occurred.

OCCUPATIONAL EXPOSURE CONTROLS: REGULATION (EU) NO. 2016/425:

As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding marking. For more information on personal protective equipment (storage, use, cleaning, maintenance, type and characteristics of the PPE, protection class, marking, category, CEN norm, etc..), you should consult the informative brochures provided by the manufacturers of PPE.

Mask:	A-type filter mask (brown) for gases and vapours of organic compounds with a boiling point higher than 65°C (EN14387). Class 1: low capacity up to 1000 ppm, Class 2: medium capacity up to 5000 ppm, Class 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. The respiratory equipment with filters does not work satisfactorily when the air contains high concentrations of vapour or oxygen content less than 18% in volume. In presence of high concentrations of vapour, use independent breathing apparatus.
Safety goggles:	Safety goggles designed to protect against liquid splashes, with suitable lateral protection (EN166).Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.
Face shield:	No.
Gloves:	Gloves resistant against chemicals (EN374). When repeated or prolonged contact with the product is expected, gloves of protection level 5 or higher should be used, with a breakthrough time of >240 min. When short contact with the product is expected, use gloves with a protection level 2 or higher should be used, with a breakthrough time >30 min. The breakthrough time of the selected glove material should be in accordance with the pretended period of use. There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, the instructions/specifications provided by the glove supplier should be taken into account. Use the proper technique of removing gloves (without touching glove's outer surface) to avoid contact of the product with the skin. The gloves should be immediately replaced when any sign of degradation is noted.
Boots:	No.
Apron:	No.
Clothing:	Advisable.

- Thermal hazards:

Not applicable (the product is handled at room temperature).

ENVIRONMENTAL EXPOSURE CONTROLS:

Avoid any spillage in the environment. Avoid any release into the atmosphere.

- Spills on the soil:

Prevent contamination of soil.

Spills in water:

Do not allow to escape into drains, sewers or water courses.

-Water Management Act:

This product does not contain any substance included in the list of priority substances in the field of water policy under Directive 2000/60/EC~2013/39/EU.

- Emissions to the atmosphere:

Because of volatility, emissions to the atmosphere while handling and use may result. Avoid any release into the atmosphere.





Previous revision: 11/02/2022 Version: 5 Revision: 12/12/2022 Date of printing: 12/12/2022

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:

Appearance

Physical state: Liquid Colour: White

Odour: Characteristic

Odour threshold: Not available (mixture).

Change of state

Melting point: Not available (mixture). Initial boiling point: 145,8* °C at 760 mmHg

- Flammability:

Flashpoint 42* °C CLP 2.6.4.3.

Lower/upper flammability or explosive limits: 1,49 - 10,86 Autoignition temperature: Not applicable.

Stability

Decomposition temperature: Not available (technical impossibility to obtain the

pH-value

pH: Not applicable (non-aqueous media).

Viscosity:

Dynamic viscosity: 30 Poise at 20°C Kinematic viscosity: 504,63* mm2/s at 40°C

Solubility(ies):

Solubility in water Inmiscible

Liposolubility: Not applicable (inorganic product).

Partition coefficient: n-octanol/water: Not applicable (mixture).

Volatility:

Vapour pressure: 3,2* mmHg at 20°C Vapour pressure: 2,4324* kPa at 50°C Evaporation rate: Not available (lack of data).

Density

Relative density: 2,038* at 20/4°C Relative water Relative vapour density: 4,56* at 20°C 1 atm. Relative air

Particle characteristics

Particle size: Not applicable.

Explosive properties:

Vapours can form explosive mixtures with air and are able to flame up or explode in presence of an ignition source.

Oxidizing properties:

Not classified as oxidizing product.

*Estimated values based on the substances composing the mixture.

OTHER INFORMATION: 9.2

Information regarding physical hazard classes

Flammable liquids: Combustibility: Combustible.

Other security features:

Heat of combustion: 1445 Kcal/kg 17,9 % Weight VOC (supply): VOC (supply): 363,7 g/l Nonvolatile: 82,15 * % Weight

1h. 60°C

The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the corresponding technical data sheet. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.





Previous revision: 11/02/2022 Version: 5 **Revision: 12/12/2022** Date of printing: 12/12/2022

SECTION	N 10: STABILITY AND REACTIVITY							
10.1	REACTIVITY:							
	- Corrosivity to metals:							
	It is not corrosive to metals.							
	- Pyrophorical properties:							
	It is not pyrophoric.							
10.2	CHEMICAL STABILITY:							
	Stable under recommended storage and handling	conditions.						
10.3	POSSIBILITY OF HAZARDOUS REACTIONS	<u>.</u>						
	Possible dangerous reaction with oxidizing agents,	acids, metals.						
10.4	CONDITIONS TO AVOID:							
	- Heat:							
	Keep away from sources of heat.							
	- Light:							
	If possible, avoid direct contact with sunlight.							
	- Air:							
	The product is not affected by exposure to air, but	should not be left the containers	s open.					
	- Humidity:							
	Avoid extreme humidity conditions.							
	- Pressure:							
	Not relevant.							
	- Shock:							
	The product is not sensitive to shocks, but as a rec	commendation of a general natu	re should be avoided bumps a	and rough handling to avoid				
	dents and breakage of packaging, especially when	n the product is handled in large	quantities, and during loading	g and download operations.				
10.5	INCOMPATIBLE MATERIALS:							
	Keep away from oxidizing agents, acids, metals.							
10.6	HAZARDOUS DECOMPOSITION PRODUCTS							
	As consequence of thermal decomposition, hazard	ous products may be produced	: carbon monoxide.					
SECTION	N 11: TOXICOLOGICAL INFORMATION							
	No experimental toxicological data on the prep							
	carried out by using the conventional calculation			349 (CLP).				
11.1	INFORMATION ON HAZARD CLASSES AS I	DEFINED IN REGULATION (EC) NO 1272/2008 :					
	ACUTE TOXICITY:							
ĺ	Dose and lethal concentrations	DL50 (OECD401)	DL50 (OECD402)	CL50 (OECD403)				
	for individual ingredients:	mgÌkg bw Oral	mg/kg bw`Cutaneous	mg/m3·4h Inhalation				
	2-methoxy-1-methylethyl acetate	8532 Rat	> 5000 Rat	> 35700 Rat				
	Estimates of acute toxicity (ATE)	ATE	ATE	ATE				
	for individual ingredients:	mg/kg bw Oral		mg/m3·4h Inhalation				
	<u> </u>	3. 3	5 5	3				

- 2-methoxy-1-methylethyl acetate 35700 Vapours (*) - Point estimates of acute toxicity corresponding to the classification category (see GHS/CLP Table 3.1.2). These values are designed to be used in the calculation of the ATE for classification of a mixture based on its components and do not represent test results.
- (-) The components that are assumed to have no acute toxicity at the upper threshold of category 4 for the corresponding exposure route are ignored.

- No observed adverse effect level

Not available

- Lowest observed adverse effect level

Not available

INFORMATION ON LIKELY ROUTES OF EXPOSURE: ACUTE TOXICITY:

Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed	Criteria
Inhalation: Not classified	ATE > 5000 mg/m3	Not available.	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
Skin: Not classified	ATE > 2000 mg/kg bw	Not available.	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).	
Eyes: Not classified	Not available.	-	Not classified as a product with acute toxicity by eye contact (lack of data).	GHS/CLP 1.2.5.
Ingestion: Not classified	ATE > 2000 mg/kg bw	Not available.	Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.

GHS/CLP 3.1.3.6: Classification of mixtures based on ingredients of the mixture (additivity formula).





Version: 5 Revision: 12/12/2022 Previous revision: 11/02/2022 Date of printing: 12/12/2022

CORROSION / IRRITATION / SENSITISATION :

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
 Respiratory corrosion/irrita Not classified 	ation: -	-	irritant by inhalation (based on available data	GHS/CLP 1.2.6. 3.8.3.4.
- Skin corrosion/irritation: Not classified	-	-	Not classified as a product corrosive or irritant in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.2.3.3.
- Serious eye damage/irrita Not classified	tion: -		Not classified as a product corrosive or irritant in contact with eyes (based on available data, the classification criteria are not met).	GHS/CLP 3.3.3.3.
- Respiratory sensitisation: Not classified	-	-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.
- Skin sensitisation: Not classified	-	-	Not classified as a product sensitising by skin contact (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.

GHS/CLP 3.2.3.3: Classification of the mixture when data are available for all components or only for some components. GHS/CLP 3.3.3.3: Classification of the mixture when data are available for all components or only for some components. GHS/CLP 3.4.3.3: Classification of the mixture when data are available for all components or only for some components. GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

- ASPIRATION HAZARD:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Aspiration hazard: Not classified	-		'	GHS/CLP 3.10.3.3.

GHS/CLP 3.10.3.3: Classification of the mixture when data are available for all components or only for some components.

SPECIFIC TARGET ORGANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Effects	SE/RE	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
- Neurological effects:	SE (!)	CNS		dizzinaca if inhalad	GHS/CLP 3.8.3.4.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

CMR EFFECTS:

- Carcinogenic effects:

It is not considered as a carcinogenic product.

- Genotoxicity:

It is not considered as a mutagenic product.

- Toxicity for reproduction:

Does not harm fertility. Does not harm the unborn child.

Effects via lactation:

Not classified as a hazardous product for children breast-fed.

<u>DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:</u> Routes of exposure

May be absorbed by inhalation of vapour, through the skin and by ingestion.

- Short-term exposure:

Exposure to solvent vapour concentrations in excess of the stated occupational exposure limit, may result in adverse health effects, such as mucous membrane and respiratory system irritation and adverse effects on kidneys, liver and central nervous system. Liquid splashes in the eyes may cause irritation and reversible damage. If swallowed, may cause irritation of the throat; other effects may be the same as described in the exposure to vapours. Causes burns to the skin or eyes by direct contact or to the digestive tract if swallowed. The mists of fine particles are skin and respiratory tract irritants. Causes serious eye damage. Causes skin irritation. May cause respiratory irritation. May cause drowsiness or dizziness.

- Long-term or repeated exposure

Repeated or prolonged contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

INTERACTIVE EFFECTS:

Not available.





 Version: 5
 Revision: 12/12/2022
 Previous revision: 11/02/2022
 Date of printing: 12/12/2022

INFORMATION ABOUT TOXICOCINETICS, METABOLISM AND DISTRIBUTION:

Dermal absorption:

This preparation contains the following substances for which dermal absorption can be very high: 2-methoxy-1-methylethyl acetate.

- Basic toxicokinetics:

Not available.

ADDITIONAL INFORMATION:

Not available.

11.2 INFORMATION ON OTHER HAZARDS:

Endocrine disrupting properties:

This product does not contain substances with endocrine disrupting properties identified or under evaluation.

Other information:

No additional information available.

SECTION 12: ECOLOGICAL INFORMATION

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2021/849 (CLP).

12.1 TOXICITY:

- Acute toxicity in aquatic environment for individual ingredients	CL50 (OECD 203)	CE50 (OECD 202)	CE50 (OECD 201)
	mg/l·96hours	mg/l·48hours	mg/l·72hours
2-methoxy-1-methylethyl acetate	134 - Fishes	408 - Daphniae	1000 - Algae

- No observed effect concentration	NOEC (OECD 210) mg/l · 28 days		NOEC (OECD 201) mg/l · 72 hours
2-methoxy-1-methylethyl acetate		100 - Daphniae	-

- Lowest observed effect concentration

Not available

ASSESSMENT OF AQUATIC TOXICITY:

Aquatic toxicity	Cat.	Main hazards to the aquatic environment	Criteria
 Acute aquatic toxicity: Not classified 		, , , ,	GHS/CLP 4.1.3.5.5.3.
- Chronic aquatic toxicity:		Not classified as a dangerous product with chronic toxicity to aquatic life with long lasting effects (based on available data, the classification criteria are not met).	GHS/CLP 4.1.3.5.5.4.

CLP 4.1.3.5.5.3: Classification of a mixture for acute hazards, based on summation of classified components.

CLP 4.1.3.5.5.4: Classification of a mixture for chronic (long term) hazards, based on summation of classified components.

12.2 PERSISTENCE AND DEGRADABILITY:

- Biodegradability:

Not readily biodegradable.

Aerobic biodegradation for individual ingredients	COD mgO2/g	%DBO/DQO 5 days 14 days 28 days	Biodegradabilidad
2-methoxy-1-methylethyl acetate	1520	22 78 90	Easy

Note: Biodegradability data correspond to an average of data from various bibliographic sources.

- Hydrolysis:

Not available.

- Photodegradability:

Not available.

12.3 BIOACCUMULATIVE POTENTIAL:

Not available.

Bioaccumulation	logPow	BCF	Potential
for individual ingredients	_	L/kg	
2-methoxy-1-methylethyl acetate	0.56	3.2 (calculated)	No bioaccumulable

12.4 MOBILITY IN SOIL:

Not available

110t d a diabio			
Mobility	log Poo	-	Potential
for individual ingredients		Pa·m3/mol 20°C	
2-methoxy-1-methylethyl acetate	0,23	0,42 (calculated)	No bioaccumulable

12.5 RESULTS OF PBT AND VPVB ASSESMENT:(Annex XIII of Regulation (EC) no. 1907/2006:)

Does not contain substances that fulfil the PBT/vPvB criteria.

12.6 ENDOCRINE DISRUPTING PROPERTIES:

This product does not contain substances with endocrine disrupting properties identified or under evaluation.





Version: 5 Revision: 12/12/2022 Previous revision: 11/02/2022 Date of printing: 12/12/2022

OTHER ADVERSE EFFECTS: 12.7

Ozone depletion potential:

Not available.

- Photochemical ozone creation potential:

Not available.

- Earth global warming potential:

In case of fire or incineration liberates CO2.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS:Directive 2008/98/EC~Regulation (EU) no. 1357/2014: 13.1

Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose at an authorised waste collection point. Waste should be handled and disposed in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.

Disposal of empty containers:Directive 94/62/EC~2015/720/EU, Decision 2000/532/EC~2014/955/EU:

Emptied containers and packaging should be disposed in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of empting of the same, being the holder of the residue responsible for their classification, in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in itself.

Procedures for neutralising or destroying the product:

Controlled incineration in special facilities for chemical waste, in accordance with local regulations.

SECTION 14: TRANSPORT INFORMATION

UN NUMBER OR ID NUMBER:

1263

14.2 **UN PROPER SHIPPING NAME:**

PAINT

14.3 TRANSPORT HAZARD CLASS(ES):

> Transport by road (ADR 2021) and Transport by rail (RID 2021):

Good not submitted to ADR.

Transport for viscous liquids in packages with capacity under 450 L according to 2.2.3.1.5. (ADR) or under 30 L according to 2.3.2.5. (IMDG).

Transport by sea (IMDG 39-18):

- Class: - Packing group: Ш - Emergency Sheet (EmS): F-E.S E - First Aid Guide (MFAG): 310,313 - Marine pollutant: Nο

Shipping Bill of lading. - Transport document:

Transport by air (ICAO/IATA 2021): - Class:

- Packing group:

- Transport document: Air Bill of lading.





Transport by inland waterways (ADN):

Not available

14.4

PACKING GROUP: See section 14.3

ENVIRONMENTAL HAZARDS: 14.5

Not applicable (not classified as hazardous for the environment).

SPECIAL PRECAUTIONS FOR USER: 14.6

> Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are upright and secure. Ensure adequate ventilation.

MARITIME TRANSPORT IN BULK ACCORDING TO IMO INSTRUMENTS: 14.7

Not available.





Version: 5 Revision: 12/12/2022 Previous revision: 11/02/2022 Date of printing: 12/12/2022

SECTION 15: REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE

The regulations applicable to this product generally are listed throughout this Safety Data Sheet.

Restrictions on manufacture, placing on market and use:

See section 1.2

Tactile warning of danger:

Not applicable (the classification criteria are not met).

Child safety protection:

Not applicable (the classification criteria are not met).

OTHER REGULATIONS:

Control of the risks inherent in major accidents (Seveso III):

See section 7.2

Other local legislations:

The receiver should verify the possible existence of local regulations applicable to the chemical.

15.2 CHEMICAL SAFETY ASSESSMENT:

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: OTHER INFORMATION

16.1 TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:

Hazard statements according the Regulation (EU) No. 1272/2008~2021/849 (CLP), Annex III:

H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.

EVALUATION OF THE INFORMATION ON THE DANGER OF MIXTURES:

See sections 9.1, 11.1 and 12.1.

ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of Safety Data Sheets and labelling of products as well.

MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:

- · European Chemicals Agency: ECHA, http://echa.europa.eu/
- · Access to European Union Law, http://eur-lex.europa.eu/
- Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970).
- Threshold Limit Values, (AGCIH, 2017).
- European agreement on the international carriage of dangerous goods by road, (ADR 2021).
- International Maritime Dangerous Goods Code IMDG including Amendment 39-18 (IMO, 2018).

ABBREVIATIONS AND ACRONYMS:

List of abbreviations and acronyms that can be used (but not necessarily used) in this Safety Data Sheet:

- $\cdot \ \mathsf{REACH:} \ \mathsf{Regulation} \ \mathsf{concerning} \ \mathsf{the} \ \mathsf{Registration}, \ \mathsf{Evaluation}, \ \mathsf{Authorisation} \ \mathsf{and} \ \mathsf{Restriction} \ \mathsf{of} \ \mathsf{Chemicals}.$
- · GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- · CLP: European regularion on Classificatin, Labelling amd Packaging of substances and chemical mixtures.
- · EINECS: European Inventory of Existing Commercial Chemical Substances.
- · ELINCS: European List of Notified Chemical Substances.
- · CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- · UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials.
- · SVHC: Substances of Very High Concern.
- · PBT: Persistent, bioaccumulable and toxic substances.
- · vPvB: Very persistent and very bioaccumulable substances.
- · VOC: Volatile Organic Compounds.
- · DNEL: Derived No-Effect Level (REACH).
- · PNEC: Predicted No-Effect Concentration (REACH).
- · LC50: Lethal concentration, 50 percent.
- · LD50: Lethal dose, 50 percent.
- · UN: United Nations Organisation.
- · ADR: European agreement concerning the international carriage of dangeous goods by road.
- · RID: Regulations concerning the international transport of dangeous goods by rail.
- · IMDG: International Maritime code for Dangerous Goods.
- · IATA: International Air Transport Association.
- · ICAO: International Civil Aviation Organization.

SAFETY DATA SHEET REGULATIONS:

Safety Data Sheet in accordance with Article 31 of Regulation (EC) No. 1907/2006 (REACH) and Annex of Regulation (EU) No. 2020/878.

 HISTORIC:
 REVISION:

 Version: 4
 11/02/2022

 Version: 5
 12/12/2022

Changes since previous Safety Data Sheet:

Changes that have been introduced with respect to the previous version due to the structural and content adaptation of the Safety Data Sheet to Regulation (EU) No. 2020/878: All sections.

The information of this Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users" working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product"s properties.