

**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL**

## Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

**1.1. Product identifier**

Code: V400PRIMER.2/ISA  
 Product name: SPRAYS - IMPRIMACIONES PLASTICOS 400 ml ISAVAL  
 UFI: 0T90-N0A2-V00R-2Y3V

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Intended use: Plastic primers in aerosol.

Identified Uses	Industrial	Professional	Consumer
Consumer	-	-	✓
Industrial Use	✓	-	-
Professional Use	-	✓	-

**1.3. Details of the supplier of the safety data sheet**

Name: AMBRO-SOL S.R.L.  
 Full address: Via per Pavone del Mella n.21  
 District and Country: 25020 Cigole (BS)  
 Italia  
 Tel. +39 030 9959674  
 Fax +39 030 959265

e-mail address of the competent person  
 responsible for the Safety Data Sheet

[quality@ambro-sol.com](mailto:quality@ambro-sol.com)

**1.4. Emergency telephone number**

For urgent inquiries refer to

Centro Antiveleni di Pavia: Tel. (+39) 0382-24444 (IRCCS Fondazione Maugeri - Pavia)  
 Centro Antiveleni di Bergamo: Tel. 800 883300 (Ospedale Papa Giovanni XXIII - Bergamo)  
 Centro Antiveleni di Firenze: Tel. 055 7947819 (Ospedale Careggi - Firenze)  
 Centro Antiveleni di Roma: Tel. 06 3054 343 (Policlinico Gemelli - Roma)  
 Centro Antiveleni di Napoli: Tel. 081 5453333 (Ospedale Cardarelli - Napoli)  
 Servicio de Información Toxicológica (SIT) España: Tel. 91 5620420 (Instituto Nacional de Toxicología y Ciencias Forenses - España)  
 Centro de Informação Antivenenos (CIAV): Tel. 800 250 250 (Instituto Nacional de Emergência Médica - Portugal)  
 Centre Antipoison de Paris: Tel. 01 40 05 48 48 (Centre Antipoison et de Toxicovigilance de Paris - France)  
 Pomorskie Centrum Toksykologii: Tel. (58) 682 04 04 (Zakład Toksykologii Klinicznej - Polska)  
 American Association of Poison Control Centers (USA): Tel. +1 (800) 222 1222  
 Giftnotrufzentralen (Berlin, Deutschland): Tel. +49 030 19 240

### SECTION 2. Hazards identification

**2.1. Classification of the substance or mixture**

**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL**

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

## Hazard classification and indication:

Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

**2.2. Label elements**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

## Hazard pictograms:



Signal words:            Danger

## Hazard statements:

<b>H222</b>	Extremely flammable aerosol.
<b>H229</b>	Pressurised container: may burst if heated.
<b>H319</b>	Causes serious eye irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H336</b>	May cause drowsiness or dizziness.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.

## Precautionary statements:

<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>P251</b>	Do not pierce or burn, even after use.
<b>P410+P412</b>	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
<b>P211</b>	Do not spray on an open flame or other ignition source.
<b>P280</b>	Wear protective gloves / eye protection / face protection.
<b>P102</b>	Keep out of reach of children.

**Contains:**            Modified chlorinated polyolefin with maleic anhydride  
Acetone

VOC (Directive 2004/42/EC) :

## Special finishes.

VOC given in g/litre of product in a ready-to-use condition :	770,00
Limit value:	840,00

**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL****2.3. Other hazards**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**SECTION 3. Composition/information on ingredients****3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
<b>Dimethyl carbonate</b>		
CAS 616-38-6	$35 \leq x < 39$	Flam. Liq. 2 H225
EC 210-478-4		
INDEX 607-013-00-6		
<b>Acetone</b>		
CAS 67-64-1	$27 \leq x < 31$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC 200-662-2		
INDEX 606-001-00-8		
Reg. no. 01-2119471330-49-XXXX		
<b>Propane</b>		
CAS 74-98-6	$19 \leq x < 23$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: U
EC 200-827-9		
INDEX 601-003-00-5		
Reg. no. 01-2119486944-21-0046		
<b>Butane</b>		
CAS 106-97-8	$9 \leq x < 11$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C U
EC 203-448-7		
INDEX 601-004-00-0		
Reg. no. 01-2119474691-32-XXXX		
<b>Xylene (mixture of isomers)</b>		
CAS 1330-20-7	$1 \leq x < 3$	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Classification note according to Annex VI to the CLP Regulation: C
EC 215-535-7		
INDEX 601-022-00-9		
Reg. no. 01-2119488216-32-XXXX		
<b>Modified chlorinated polyolefin with maleic anhydride</b>		
CAS 68609-36-9	$1 \leq x < 3$	Skin Sens. 1 H317
EC 614-659-2		
INDEX -		
<b>Isobutane</b>		
CAS 75-28-5	$1 \leq x < 3$	Flam. Gas 1A H220, Press. Gas H280

**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL**

EC 200-857-2

INDEX 601-004-00-0

Reg. no. 01-2119485395-27-XXXX

**Ethylbenzene**

CAS 100-41-4

 $0,5 \leq x < 1$ 

Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373

EC 202-849-4

INDEX 601-023-00-4

Reg. no. 01-2119489370-35-XXXX

**Chlorobenzene**

CAS 108-90-7

 $0 \leq x < 0,5$ 

Flam. Liq. 3 H226, Acute Tox. 4 H332, Skin Irrit. 2 H315, Aquatic Chronic 2 H411

EC 203-628-5

INDEX 602-033-00-1

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 30,50 %

**SECTION 4. First aid measures****4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures****5.1. Extinguishing media**

## SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

## UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

**5.2. Special hazards arising from the substance or mixture**

**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

**5.3. Advice for firefighters****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

**6.2. Environmental precautions**

Do not disperse in the environment.

**6.3. Methods and material for containment and cleaning up**

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage****7.1. Precautions for safe handling**

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

**7.3. Specific end use(s)**

Information not available

**SECTION 8. Exposure controls/personal protection**

**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL**

**8.1. Control parameters**

Regulatory References:

DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition, published 2018)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2020

**Dimethyl carbonate**

Predicted no-effect concentration - PNEC

Normal value in fresh water	500	µg/l
Normal value in marine water	50	µg/l
Normal value for fresh water sediment	NEA	
Normal value for marine water sediment	NEA	
Normal value for water, intermittent release	1	mg/l
Normal value of STP microorganisms	99	mg/l
Normal value for the terrestrial compartment	NEA	
Normal value for the atmosphere	NPI	

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		50 mg/kg bw/day		250 µg/kg bw/day				
Inhalation	42,5 mg/m3	42,5 mg/m3	VND	1,1 mg/m3	57 mg/m3	57 mg/m3	NPI	4,4 mg/m3
Skin	8,9 mg/cm2	33,3 mg/kg bw/day	NPI	250 µg/kg bw/day	17,7 mg/cm2	66,7 µg/kg bw/day	NPI	500 mg/kg bw/day

**Acetone**

**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	1200	500	2400 (C)	1000 (C)	
MAK	DEU	1200	500	2400	1000	
VLEP	FRA	1210	500	2420	1000	
VLEP	ITA	1210	500			
VLE	PRT	1210	500			
NDS/NDSch	POL	600		1800		
WEL	GBR	1210	500	3620	1500	
OEL	EU	1210	500			
TLV-ACGIH			250		500	

**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL**

**Predicted no-effect concentration - PNEC**

Normal value in fresh water	10,6	mg/l
Normal value in marine water	1,06	mg/l
Normal value for fresh water sediment	30,4	mg/kg
Normal value for marine water sediment	3,04	mg/kg
Normal value for water, intermittent release	21	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the food chain (secondary poisoning)	29,5	mg/kg
Normal value for the terrestrial compartment	29,5	mg/kg/d
Normal value for the atmosphere	NPI	

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	62 mg/kg				
Inhalation			VND	200 mg/m3	VND	2,420 mg/m3	VND	1,210 mg/m3
Skin			VND	62 mg/kg			VND	186 mg/kg

**Propane  
Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	1800	1000	7200	4000	
MAK	DEU	1800	1000	7200	4000	
VLA	ESP		1000			
NDS/NDSCh	POL	1800				

**Butane  
Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	2400	1000	9600	4000	
MAK	DEU	2400	1000	9600	4000	
VLA	ESP		1000			Gases
VLEP	FRA	1900	800			
NDS/NDSCh	POL	1900		3000		
WEL	GBR	1450	600	1810	750	
WEL	GBR		4			RESP
TLV-ACGIH					1000	

**Xylene (mixture of isomers)  
Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	

**AMBRO-SOL S.R.L.**

Revision nr. 2

Dated 10/10/2020

**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL**

Printed on 24/11/2020

Page n. 8/22

Replaced revision:1 (Dated: 02/02/2020)

AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
VLA	ESP	221	50	442	100	SKIN
VLEP	FRA	221	50	442	100	SKIN
VLEP	ITA	221	50	442	100	SKIN
VLE	PRT	221	50	442	100	SKIN
NDS/NDSch	POL	100		200		SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

<b>Predicted no-effect concentration - PNEC</b>						
Normal value in fresh water				327		µg/l
Normal value in marine water				327		µg/l
Normal value for fresh water sediment				12,46		mg/kg/d
Normal value for marine water sediment				12,46		mg/kg/d
Normal value of STP microorganisms				6,58		mg/l
Normal value for the terrestrial compartment				2,31		mg/kg/d

<b>Health - Derived no-effect level - DNEL / DMEL</b>								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				1,6 mg/kg bw/d				
Inhalation				14,8 mg/m3			289 mg/m3	77 mg/m3
Skin				108 mg/kg bw/d				180 mg/kg bw/d

<b>Isobutane</b>						
<b>Threshold Limit Value</b>						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH			800			

<b>Ethylbenzene</b>						
<b>Threshold Limit Value</b>						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	88	20	176	40	SKIN
MAK	DEU	88	20	176	40	SKIN
VLA	ESP	441	100	884	200	SKIN
VLEP	FRA	88,4	20	442	100	SKIN
VLEP	ITA	442	100	884	200	SKIN
VLE	PRT	442	100	884	200	SKIN
NDS/NDSch	POL	200		400		SKIN
WEL	GBR	441	100	552	125	SKIN





**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL**

	systemic	systemic	systemic
Inhalation		42,3 mg/m3	42,3 mg/m3
Skin			12 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

None required.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	aerosol
Colour	transparent
Odour	characteristic of solvent
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available

**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL**

Flash point	< 0 °C
Evaporation Rate	Not available
Flammability of solids and gases	flammable gas
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	0,75 ÷ 0,79 g/ml a 20°C
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	not applicable
Oxidising properties	not applicable

**9.2. Other information**

VOC (Directive 2004/42/EC) : 100,00 % - 770,00 g/litre

**SECTION 10. Stability and reactivity**

**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions**

No hazardous reactions are foreseeable in normal conditions of use and storage.

Dimethyl carbonate

May form explosive mixtures with: air.

Acetone

Risk of explosion on contact with: bromine trifluoride,fluorine dioxide,hydrogen peroxide,nitrosyl chloride,2-methyl-1,3 butadiene,nitromethane,nitrosyl perchlorate.May react dangerously with: potassium tert-butoxide,alkaline hydroxides,bromine,bromoform,isoprene,sodium,sulphur dioxide,chromium trioxide,chromyl chloride,nitric acid,chloroform,peroxymonosulphuric acid,phosphoryl oxychloride,chromosulphuric acid,fluorine,strong oxidising agents,strong reducing agents.Develops flammable gas on contact with: nitrosyl perchlorate.

Xylene (mixture of isomers)

**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL**

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

Ethylbenzene

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

**10.4. Conditions to avoid**

Avoid overheating.

Acetone

Avoid exposure to: sources of heat, naked flames.

**10.5. Incompatible materials**

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

Dimethyl carbonate

Avoid contact with: oxidising agents, strong reducing agents.

Acetone

Incompatible with: acids, oxidising substances.

**10.6. Hazardous decomposition products**

Acetone

May develop: ketenes, irritant substances.

Ethylbenzene

May develop: methane, styrene, hydrogen, ethane.

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on toxicological effects**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL**

Xylene (mixture of isomers)

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

Ethylbenzene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Xylene (mixture of isomers)

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Ethylbenzene

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispeal). Is irritating for skin, conjunctiva and respiratory tract.

Interactive effects

Xylene (mixture of isomers)

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

> 20 mg/l

ATE (Oral) of the mixture:

Not classified (no significant component)

ATE (Dermal) of the mixture:

>2000 mg/kg

Dimethyl carbonate

LD50 (Oral) > 5000 mg/kg/bw rat

LD50 (Dermal) > 2000 mg/kg/ bw rabbit

LC50 (Inhalation) > 5,36 mg/m<sup>3</sup>/4h rat

Xylene (mixture of isomers)

LD50 (Oral) > 3000 mg/kg rat

**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL**

LD50 (Dermal) > 1700 mg/kg rabbit

LC50 (Inhalation) 5000 ppm/4h rat

Butane

LC50 (Inhalation) > 1442,738 mg/l/15min rat

Propane

LC50 (Inhalation) 800000 ppm 15 min

Ethylbenzene

LD50 (Oral) 3500 mg/kg Rat

LD50 (Dermal) 15354 mg/kg Rabbit

LC50 (Inhalation) 17,2 mg/l/4h Rat

Chlorobenzene

LD50 (Oral) > 2000 mg/kg Rat

LC50 (Inhalation) 15,5 mg/l/4h Rat

Acetone

LD50 (Oral) 5800 mg/kg bw

LD50 (Dermal) 7426 mg/kg bw guinea pig

LC50 (Inhalation) > 20 mg/l/4h air

Isobutane

LC50 (Inhalation) > 1442,738 mg/l/15min rat

**SKIN CORROSION / IRRITATION**

Repeated exposure may cause skin dryness or cracking.

**SERIOUS EYE DAMAGE / IRRITATION**

**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL**

Causes serious eye irritation

**RESPIRATORY OR SKIN SENSITISATION**

Sensitising for the skin

**GERM CELL MUTAGENICITY**

Does not meet the classification criteria for this hazard class

**CARCINOGENICITY**

Does not meet the classification criteria for this hazard class

Xylene (mixture of isomers)

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).  
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

Ethylbenzene

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).  
Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

**REPRODUCTIVE TOXICITY**

Does not meet the classification criteria for this hazard class

**STOT - SINGLE EXPOSURE**

May cause drowsiness or dizziness

**STOT - REPEATED EXPOSURE**

Does not meet the classification criteria for this hazard class

**ASPIRATION HAZARD**

Does not meet the classification criteria for this hazard class

**SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

**12.1. Toxicity**

Dimethyl carbonate

LC50 - for Fish

1134 mg/l/96h 4 days

**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL**

EC50 - for Crustacea	> 80 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 70 mg/l/72h
Chronic NOEC for Fish	100 mg/l 4 days
Chronic NOEC for Crustacea	25 mg/l 21 days
Chronic NOEC for Algae / Aquatic Plants	> 50 mg/l 72 h

Xylene (mixture of isomers)

LC50 - for Fish	2,6 mg/l/96h
EC50 - for Algae / Aquatic Plants	4,6 mg/l/72h
EC10 for Crustacea	1,9 mg/l/21d
Chronic NOEC for Fish	1,3 mg/l 56 days
Chronic NOEC for Crustacea	960 µg/l 7 days
Chronic NOEC for Algae / Aquatic Plants	440 µg/l 73 h

Butane

LC50 - for Fish	> 24,11 mg/l/96h
-----------------	------------------

Propane

LC50 - for Fish	85,82 mg/l/96h
EC50 - for Crustacea	41,82 mg/l/48h

Ethylbenzene

LC50 - for Fish	4,65 mg/l/96h
EC50 - for Crustacea	2,1 mg/l/48h
EC50 - for Algae / Aquatic Plants	5,15 mg/l/72h
Chronic NOEC for Fish	3,3 mg/l 4 days
Chronic NOEC for Crustacea	960 µg/l 7 days
Chronic NOEC for Algae / Aquatic Plants	3,95 mg/l 4 days

Chlorobenzene

LC50 - for Fish	7,72 mg/l/96h Pimephales promelas
-----------------	-----------------------------------

Acetone

LC50 - for Fish	6,83 g/l
EC50 - for Crustacea	8,8 g/l/48h
Chronic NOEC for Crustacea	1,659 g/l 28 days

Isobutane

LC50 - for Fish	> 24,11 mg/l/96h
-----------------	------------------

**12.2. Persistence and degradability**

Propane

Global Warming Potential (GWP): 3. Ozone Depletion Potential (ODP): 0.



**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL**

Dimethyl carbonate  
Rapidly degradable

Xylene (mixture of isomers)

Solubility in water 146 - 208 mg/L @ 25 °C and pH 7 mg/l

Rapidly degradable

Butane

Solubility in water 0,1 - 100 mg/l

Rapidly degradable

Propane

Solubility in water 0,1 - 100 mg/l

Rapidly degradable

Ethylbenzene

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

Chlorobenzene

Solubility in water 100 - 1000 mg/l

NOT rapidly degradable

Acetone

Rapidly degradable

Isobutane

Rapidly degradable

Modified chlorinated polyolefin with maleic  
anhydride

Degradability: information not available

**12.3. Bioaccumulative potential**

Xylene (mixture of isomers)

Partition coefficient: n-octanol/water 3,12

BCF 25,9

Butane

Partition coefficient: n-octanol/water 1,09

Propane

Partition coefficient: n-octanol/water 1,09

Ethylbenzene

**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL**

Partition coefficient: n-octanol/water	3,6
Chlorobenzene	
Partition coefficient: n-octanol/water	3
Acetone	
Partition coefficient: n-octanol/water	-0,23
BCF	3

**12.4. Mobility in soil**

Xylene (mixture of isomers)	
Partition coefficient: soil/water	2,73
Chlorobenzene	
Partition coefficient: soil/water	2,42

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**12.6. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations**

**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

**CONTAMINATED PACKAGING**

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Product residues are to be considered special hazardous waste.

Empty cans, even if completely emptied, must not be dispersed in the environment.

The aerosol container overheated to a temperature above 50Å ° C can burst even if it contains a small residue of gas.

Disposal must take place in an authorized place and in compliance with the laws in force.

Waste transportation can be subject to ADR.

European waste catalog number (contaminated containers):

Aerosol as domestic waste is excluded from the application of the aforementioned standard.

The used aerosol for professional / industrial use can be classified:

15.01.10 \*: packaging containing residues of dangerous substances or contaminated by these substances.

**SECTION 14. Transport information**

**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL**

**14.1. UN number**

ADR / RID, IMDG, 1950  
IATA:

**14.2. UN proper shipping name**

ADR / RID: AEROSOLS  
IMDG: AEROSOLS  
IATA: AEROSOLS, FLAMMABLE

**14.3. Transport hazard class(es)**

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1

IATA: Class: 2 Label: 2.1



**14.4. Packing group**

ADR / RID, IMDG, -  
IATA:

**14.5. Environmental hazards**

ADR / RID: NO  
IMDG: NO  
IATA: NO

**14.6. Special precautions for user**

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
	Special Provision: -		
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 L	
		Maximum quantity: 150 Kg	Packaging instructions: 203
IATA:	Cargo:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Pass.:	A145, A167, A802	
	Special Instructions:		

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL**

Information not relevant

**SECTION 15. Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

Special finishes.

**15.2. Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL**

<b>Flam. Gas 1A</b>	Flammable gas, category 1A
<b>Aerosol 1</b>	Aerosol, category 1
<b>Aerosol 3</b>	Aerosol, category 3
<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Press. Gas</b>	Pressurised gas
<b>Press. Gas (Liq.)</b>	Liquefied gas
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Aquatic Chronic 2</b>	Hazardous to the aquatic environment, chronic toxicity, category 2
<b>H220</b>	Extremely flammable gas.
<b>H222</b>	Extremely flammable aerosol.
<b>H229</b>	Pressurised container: may burst if heated.
<b>H225</b>	Highly flammable liquid and vapour.
<b>H226</b>	Flammable liquid and vapour.
<b>H280</b>	Contains gas under pressure; may burst if heated.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H411</b>	Toxic to aquatic life with long lasting effects.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation

**V400PRIMER.2/ISA - SPRAYS - IMPRIMACIONES PLASTICOS 400 ml  
ISAVAL**

- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  4. Regulation (EU) 2015/830 of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
  16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.