


**SPRAY PERMANENT MULTI-PURPOSE ADHESIVE, 400 ml**


Versión: 14    Date of compilation: 10/10/2020    Date of printing: 24/11/2020

## Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

**1.1. Product identifier**

Code: **I254/ISA**  
 Product name: **SPRAYS - ADHESIVO MULTIUSOS PERMANENTE 400 ml ISAVAL**  
 UFI: **KT70-00EX-U00D-V3QD**

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

 Intended use: **Permanent multi-purpose glue in aerosol.**

Identified Uses	Industrial	Professional	Consumer
Consumer	-	-	✓
Industrial Use	✓	-	-
Professional Use	-	✓	-

**1.3. Details of the supplier of the safety data sheet**

Name: **PINTURAS ISAVAL S.L.**  
 Full address: **c/Velluters, Parcela 2-14 - P.I.Casanova - E**  
 District and Country: **46394 - Ribarroja del Turia (Valencia)**  
**España**  
 Tel. **+34 96 164 00 01**  
 Fax **+34 96 164 00 02**

e-mail address of the competent person responsible for the Safety Data Sheet: **atencionalcliente@isaval.es**

**1.4. Emergency telephone number**    +34 96 1640001 (8:00-18:00 h.) (working hours)

### SECTION 2. Hazards identification

**2.1. Classification of the substance or mixture**

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

**Hazard classification and indication:**

Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 2	H411	Toxic to aquatic life with long lasting effects.

**I254/ISA - SPRAYS - ADHESIVO MULTIUSOS PERMANENTE 400 ml  
ISAVAL****2.2. Label elements**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

<b>H222</b>	Extremely flammable aerosol.
<b>H229</b>	Pressurised container: may burst if heated.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H411</b>	Toxic to aquatic life with long lasting effects.

Precautionary statements:

<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>P251</b>	Do not pierce or burn, even after use.
<b>P410+P412</b>	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
<b>P211</b>	Do not spray on an open flame or other ignition source.
<b>P273</b>	Avoid release to the environment.
<b>P391</b>	Collect spillage.
<b>P102</b>	Keep out of reach of children.

**Contains:** Acetone  
Hydrocarbons, C6, isoalkanes

Statements on the aspiration toxicity classification were not included in the label elements, based on section 1.3.3. of Annex I to CLP.

**2.3. Other hazards**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**SECTION 3. Composition/information on ingredients****3.2. Mixtures**

**I254/ISA - SPRAYS - ADHESIVO MULTIUSOS PERMANENTE 400 ml  
ISAVAL**

Contains:

<b>Identification</b>	<b>x = Conc. %</b>	<b>Classification 1272/2008 (CLP)</b>
<b>Hydrocarbons, C6, isoalkanes</b>		
CAS 64742-49-0	27 ≤ x < 31	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 2 H411, Classification note according to Annex VI to the CLP Regulation: P
EC 265-151-9		
INDEX 649-328-00-1		
Reg. no. 012119484651-34-XXXX		
<b>Propane</b>		
CAS 74-98-6	19 ≤ x < 23	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: U
EC 200-827-9		
INDEX 601-003-00-5		
Reg. no. 01-2119486944-21-0046		
<b>Acetone</b>		
CAS 67-64-1	15 ≤ x < 19	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC 200-662-2		
INDEX 606-001-00-8		
Reg. no. 01-2119471330-49-XXXX		
<b>Butane</b>		
CAS 106-97-8	9 ≤ x < 11	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C U
EC 203-448-7		
INDEX 601-004-00-0		
Reg. no. 01-2119474691-32-XXXX		
<b>Isobutane</b>		
CAS 75-28-5	1 ≤ x < 3	Flam. Gas 1A H220, Press. Gas H280
EC 200-857-2		
INDEX 601-004-00-0		
Reg. no. 01-2119485395-27-XXXX		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 33,20 %

Hydrocarbons, C6, isoalkanes

Hydrocarbons, C6, isoalkanes, <5% n-hexane: a complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20Å ° C to 190Å ° C (-4Å ° F to 374Å ° F).

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists,

**I254/ISA - SPRAYS - ADHESIVO MULTIUSOS PERMANENTE 400 ml  
ISAVAL**

seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures****5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

None in particular.

**5.2. Special hazards arising from the substance or mixture****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

**5.3. Advice for firefighters****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

**6.2. Environmental precautions**

Do not disperse in the environment.

**6.3. Methods and material for containment and cleaning up**

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**AMBRO-SOL S.R.L.**

Revision nr. 14

Dated 10/10/2020

Printed on 24/11/2020

**1254/ISA - SPRAYS - ADHESIVO MULTIUSOS PERMANENTE 400 ml  
ISAVAL**

Replaced revision:13 (Dated: 21/02/2019)

**6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage****7.1. Precautions for safe handling**

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

**7.3. Specific end use(s)**

Information not available

**SECTION 8. Exposure controls/personal protection****8.1. Control parameters**

Regulatory References:

DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
POL	Polska	ROZPORZADZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition, published 2018)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2020

**Hydrocarbons, C6, isoalkanes****Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				1301 mg/kg bw/d				
Inhalation				1137 mg/m3				5306 mg/m3
Skin				1377 mg/kg bw/d				13964 mg/kg bw/d

**Propane  
Threshold Limit Value**

Type	Country	TWA/8h	STEL/15min	Remarks /

**AMBRO-SOL S.R.L.**

Revision nr. 14

Dated 10/10/2020

Printed on 24/11/2020

**I254/ISA - SPRAYS - ADHESIVO MULTIUSOS PERMANENTE 400 ml  
ISAVAL**

Replaced revision:13 (Dated: 21/02/2019)

						Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	1800	1000	7200	4000	
MAK	DEU	1800	1000	7200	4000	
VLA	ESP		1000			
NDS/NDSCh	POL	1800				

**Acetone  
Threshold Limit Value**

Type	Country	TWA/8h	STEL/15min	Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	1200	500	2400 (C)	1000 (C)
MAK	DEU	1200	500	2400	1000
VLEP	FRA	1210	500	2420	1000
VLEP	ITA	1210	500		
VLE	PRT	1210	500		
NDS/NDSCh	POL	600		1800	
WEL	GBR	1210	500	3620	1500
OEL	EU	1210	500		
TLV-ACGIH			250		500

**Predicted no-effect concentration - PNEC**

Normal value in fresh water				10,6	mg/l
Normal value in marine water				1,06	mg/l
Normal value for fresh water sediment				30,4	mg/kg
Normal value for marine water sediment				3,04	mg/kg
Normal value for water, intermittent release				21	mg/l
Normal value of STP microorganisms				100	mg/l
Normal value for the food chain (secondary poisoning)				29,5	mg/kg
Normal value for the terrestrial compartment				29,5	mg/kg/d
Normal value for the atmosphere				NPI	

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	62 mg/kg				
Inhalation			VND	200 mg/m3	VND	2,420 mg/m3	VND	1,210 mg/m3
Skin			VND	62 mg/kg			VND	186 mg/kg

**Butane  
Threshold Limit Value**

Type	Country	TWA/8h	STEL/15min	Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	2400	1000	9600	4000
MAK	DEU	2400	1000	9600	4000

**AMBRO-SOL S.R.L.**

Revision nr. 14

Dated 10/10/2020

Printed on 24/11/2020

**I254/ISA - SPRAYS - ADHESIVO MULTIUSOS PERMANENTE 400 ml  
ISAVAL**

Replaced revision:13 (Dated: 21/02/2019)

VLA	ESP		1000				Gases
VLEP	FRA	1900	800				
NDS/NDSch	POL	1900		3000			
WEL	GBR	1450	600	1810	750		
WEL	GBR		4				RESP
TLV-ACGIH					1000		

**Isobutane  
Threshold Limit Value**

Type	Country	TWA/8h	STEL/15min	Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH			800		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

**HAND PROTECTION**

None required.

**SKIN PROTECTION**

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

**SECTION 9. Physical and chemical properties**

**I254/ISA - SPRAYS - ADHESIVO MULTIUSOS PERMANENTE 400 ml  
ISAVAL****9.1. Information on basic physical and chemical properties**

Appearance	aerosol
Colour	colourless
Odour	characteristic of solvent
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	< 0 °C
Evaporation Rate	Not available
Flammability of solids and gases	flammable gas
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	0,65 ÷ 0,69 g/ml a 20°C
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	not applicable
Oxidising properties	not applicable

**9.2. Other information**

VOC (Directive 2010/75/EC) : 80,40 % - 538,70 g/litre

**SECTION 10. Stability and reactivity****10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions**

No hazardous reactions are foreseeable in normal conditions of use and storage.



**I254/ISA - SPRAYS - ADHESIVO MULTIUSOS PERMANENTE 400 ml  
ISAVAL**

Acetone

Risk of explosion on contact with: bromine trifluoride,fluorine dioxide,hydrogen peroxide,nitrosyl chloride,2-methyl-1,3 butadiene,nitromethane,nitrosyl perchlorate.May react dangerously with: potassium tert-butoxide,alkaline hydroxides,bromine,bromoform,isoprene,sodium,sulphur dioxide,chromium trioxide,chromyl chloride,nitric acid,chloroform,peroxymonosulphuric acid,phosphoryl oxychloride,chromosulphuric acid,fluorine,strong oxidising agents,strong reducing agents.Develops flammable gas on contact with: nitrosyl perchlorate.

**10.4. Conditions to avoid**

Avoid overheating.

Acetone

Avoid exposure to: sources of heat,naked flames.

**10.5. Incompatible materials**

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

Acetone

Incompatible with: acids,oxidising substances.

**10.6. Hazardous decomposition products**

Acetone

May develop: ketenes,irritant substances.

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on toxicological effects**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

**I254/ISA - SPRAYS - ADHESIVO MULTIUSOS PERMANENTE 400 ml  
ISAVAL**

Information not available

**ACUTE TOXICITY**

ATE (Inhalation) of the mixture:  
Not classified (no significant component)  
ATE (Oral) of the mixture:  
Not classified (no significant component)  
ATE (Dermal) of the mixture:  
Not classified (no significant component)

**Butane**

LC50 (Inhalation) > 1442,738 mg/l/15min rat

**Propane**

LC50 (Inhalation) 800000 ppm 15 min

**Acetone**

LD50 (Oral) 5800 mg/kg bw

LD50 (Dermal) 7426 mg/kg bw guinea pig

LC50 (Inhalation) > 20 mg/l/4h air

**Hydrocarbons, C6, isoalkanes**

LD50 (Oral) > 2000 mg/kg bw rat

LD50 (Dermal) > 2000 mg/kg bw rabbit

LC50 (Inhalation) > 25 mg/l/4h air (rat)

**Isobutane**

LC50 (Inhalation) > 1442,738 mg/l/15min rat

**SKIN CORROSION / IRRITATION**

Causes skin irritation

**SERIOUS EYE DAMAGE / IRRITATION**

**I254/ISA - SPRAYS - ADHESIVO MULTIUSOS PERMANENTE 400 ml  
ISAVAL**

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

## SECTION 12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on aquatic environment.

### 12.1. Toxicity

Butane	
LC50 - for Fish	> 24,11 mg/l/96h
Propane	
LC50 - for Fish	85,82 mg/l/96h
EC50 - for Crustacea	41,82 mg/l/48h
Acetone	
LC50 - for Fish	6,83 g/l
EC50 - for Crustacea	8,8 g/l/48h
Chronic NOEC for Crustacea	1,659 g/l 28 days

**I254/ISA - SPRAYS - ADHESIVO MULTIUSOS PERMANENTE 400 ml  
ISAVAL**

Hydrocarbons, C6, isoalkanes	
LC50 - for Fish	8,41 mg/l/96h
EC50 - for Crustacea	4,7 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 12 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	6,47 mg/l

Isobutane	
LC50 - for Fish	> 24,11 mg/l/96h

**12.2. Persistence and degradability**

Propane  
Global Warming Potential (GWP): 3. Ozone Depletion Potential (ODP): 0.

Butane	
Solubility in water	0,1 - 100 mg/l
Rapidly degradable	

Propane	
Solubility in water	0,1 - 100 mg/l
Rapidly degradable	

Acetone	
Rapidly degradable	

Hydrocarbons, C6, isoalkanes	
Rapidly degradable	

Isobutane	
Rapidly degradable	

**12.3. Bioaccumulative potential**

Butane	
Partition coefficient: n-octanol/water	1,09

Propane	
Partition coefficient: n-octanol/water	1,09

Acetone	
Partition coefficient: n-octanol/water	-0,23
BCF	3

**12.4. Mobility in soil**

Hydrocarbons, C6, isoalkanes	
Partition coefficient: soil/water	1,78

**I254/ISA - SPRAYS - ADHESIVO MULTIUSOS PERMANENTE 400 ml  
ISAVAL****12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**12.6. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Product residues are considered hazardous special waste. Do not dispose of in wastewater.

Empty cylinders, although completely emptied, should not be dispersed in the environment.

The overheated aerosol container at a temperature above 50 °C may burst even if it contains a small gas residue.

Waste transport may be subject to ADR.

Refer to applicable regulations.

European Waste Catalog (contaminated containers):

Aerosol as a household waste is excluded from the application of the above standard.

The exhausted commercial / industrial aerosol can be classified as: 15.01.10 \*: packaging containing residues of dangerous or contaminated substances.

**SECTION 14. Transport information****14.1. UN number**

ADR / RID, IMDG, 1950  
IATA:

**14.2. UN proper shipping name**

ADR / RID: AEROSOLS  
IMDG: AEROSOLS (Hydrocarbons, C6, isoalkanes)  
IATA: AEROSOLS, FLAMMABLE

**14.3. Transport hazard class(es)**

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1



**I254/ISA - SPRAYS - ADHESIVO MULTIUSOS PERMANENTE 400 ml  
ISAVAL**

IATA: Class: 2 Label: 2.1



**14.4. Packing group**

ADR / RID, IMDG, IATA: -

**14.5. Environmental hazards**

ADR / RID: Environmentally Hazardous



IMDG: Marine Pollutant



IATA: NO

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

**14.6. Special precautions for user**

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
	Special Provision: -		
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 150 Kg	Packaging instructions: 203
	Pass.:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special Instructions:	A145, A167, A802	

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Information not relevant

**SECTION 15. Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: P3a-E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 40

Substances in Candidate List (Art. 59 REACH)

**I254/ISA - SPRAYS - ADHESIVO MULTIUSOS PERMANENTE 400 ml  
ISAVAL**

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

**15.2. Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Gas 1A</b>	Flammable gas, category 1A
<b>Aerosol 1</b>	Aerosol, category 1
<b>Aerosol 3</b>	Aerosol, category 3
<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Press. Gas (Liq.)</b>	Liquefied gas
<b>Press. Gas</b>	Pressurised gas
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Aquatic Chronic 2</b>	Hazardous to the aquatic environment, chronic toxicity, category 2
<b>H220</b>	Extremely flammable gas.
<b>H222</b>	Extremely flammable aerosol.
<b>H229</b>	Pressurised container: may burst if heated.
<b>H225</b>	Highly flammable liquid and vapour.
<b>H280</b>	Contains gas under pressure; may burst if heated.

**1254/ISA - SPRAYS - ADHESIVO MULTIUSOS PERMANENTE 400 ml  
ISAVAL**

<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H411</b>	Toxic to aquatic life with long lasting effects.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  4. Regulation (EU) 2015/830 of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
  16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition



**AMBRO-SOL S.R.L.**

Revision nr. 14

Dated 10/10/2020

**I254/ISA - SPRAYS - ADHESIVO MULTIUSOS PERMANENTE 400 ml  
ISAVAL**

Printed on 24/11/2020

Replaced revision:13 (Dated: 21/02/2019)

- IFA GESTIS website

- ECHA website

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 08 / 15.