## **Safety Data Sheet**

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - Spain



# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance or preparation

Product name or Trade name:

Sikadur WEA-TL (A)

**Use of the substance/preparation**: Chemical product for construction and industry

Company/undertaking identification

Manufacturer/Distributor : Sika S.A.

Carretera de Fuencarral, 72 Pol Ind

28108 Alcobendas (Madrid)

España

 Telephone no.
 : 91 662 18 18

 Fax no.
 : 91 662 19 38

e-mail address of person responsible for this SDS

: EHS@es.sika.com

Emergency telephone number : 91 662 18 18

Durante el horario normal de trabajo

## 2. HAZARDS IDENTIFICATION

The preparation is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Xi; R36/38

R43 R52/53

**Human health hazards** : Irritating to eyes and skin. May cause sensitization by skin contact.

**Environmental hazards**: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

**Additional warning phrases**: Contains epoxy constituents. See information supplied by the manufacturer.

See section 11 for more detailed information on health effects and symptoms.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical family/ : Filled and modified epoxi resin

Characteristics

Ingredient name	CAS number	%	EC number	Classification	
reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700)		5-25	500-033-5	Xi; R36/38 R43 N; R51/53	[1]
oxirane, mono[(C12-14-alkyloxy)methyl]derivs	68609-97-2	1-2.5	271-846-8	Xi; R36/38 R43 N; R51/53	[1]
See section 16 for the full text of the R-phrases declared above					

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in section 8.

Date of issue : 02.10.2008. MSDS no. : 114221 1/5

Sikadur WEA-TL (A) 02.10.2008 2/5

#### 4. FIRST AID MEASURES

#### First aid measures

**Inhalation** : Get medical attention if adverse health effects persist or are severe.

**Ingestion**: Do not induce vomiting unless directed to do so by medical personnel. Maintain an

open airway. Seek immediate medical attention.

**Skin contact**: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention if symptoms

occur.

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Notes to physician : No specific treatment. Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

See section 11 for more detailed information on health effects and symptoms.

#### 5. FIRE-FIGHTING MEASURES

#### **Extinguishing media**

**Suitable**: Use an extinguishing agent suitable for the surrounding fire.

Not suitable : None known.

Special exposure hazards : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products

: Decomposition products may include the following materials:

carbon oxides

halogenated compounds metal oxide/oxides

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Keep unnecessary and unprotected personnel from entering. Do not touch or walk

through spilled material. Put on appropriate personal protective equipment (see

section 8).

**Environmental precautions**: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains

and sewers. Inform the relevant authorities if the product has caused environmental

pollution (sewers, waterways, soil or air). Water polluting material.

Large spill : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers,

water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth

and place in container for disposal according to local regulations (see section 13).
 Small spill
 Stop leak if without risk. Move containers from spill area. Absorb with an inert

material and place in an appropriate waste disposal container.

### 7. HANDLING AND STORAGE

Handling

: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous.

Date of issue : 02.10.2008. MSDS no. : 114221 2/5

Sikadur WEA-TL (A) 02.10.2008 3/5

### 7. HANDLING AND STORAGE

Storage

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Packaging materials

**Recommended**: Use original container.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure limit values**

#### **Ingredient name**

#### Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

#### **Exposure controls**

Occupational exposure

controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

**Respiratory protection** 

**Hand protection** 

: No special measures required.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is passessory. Passemented: Buth rubber/pitrile rubber gloves

this is necessary. Recommended: Butyl rubber/nitrile rubber gloves.

Eye protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Use barrier skin cream.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### **General information**

#### **Appearance**

Form : Paste.
Color : Gray.

Odor : Characteristic.

#### Important health, safety and environmental information

Flash point : Closed cup: >101°C (>213.8°F)

Date of issue : 02.10.2008. MSDS no. : 114221 3/5

Sikadur WEA-TL (A) 02.10.2008 4/5

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

: ~1.94 g/cm<sup>3</sup> [20°C (68°F)] **Density** 

#### 10. STABILITY AND REACTIVITY

Stability : The product is stable. Under normal conditions of storage and use, hazardous

polymerization will not occur.

Conditions to avoid : No specific data. Materials to avoid : No specific data.

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

#### TOXICOLOGICAL INFORMATION 11.

#### Potential acute health effects

Inhalation : May cause irritation.

Ingestion : Irritating to mouth, throat and stomach.

Skin contact : Irritating to skin. May cause sensitization by skin contact.

Eye contact : Irritating to eyes.

**Chronic effects** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

#### **ECOLOGICAL INFORMATION** 12.

**Environmental effects** : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### **DISPOSAL CONSIDERATIONS 13**.

Methods of disposal

The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European waste catalogue (EWC)

: 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances

**Packaging** 

: Completely emptied packagings may be given for recycling. Empty packaging may still contain hazardous residues. Empty packaging should be removed by a licensed

waste contractor.

15 01 10\* packaging containing residues of or contaminated by dangerous

substances

## TRANSPORT INFORMATION

#### International transport regulations

#### <u>ADR</u>

Not regulated.

IMDG

Not regulated.

Marine pollutant No.

Date of issue : 02.10.2008. **MSDS no.** : 114221 4/5 Sikadur WEA-TL (A) 02.10.2008 5/5

#### TRANSPORT INFORMATION 14.

#### **IATA**

Not regulated.

#### REGULATORY INFORMATION 15.

#### **EU regulations**

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Hazard symbol or symbols : Xi

**Contains** : reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number

average molecular weight <= 700)

oxirane, mono[(C12-14-alkyloxy)methyl]derivs

Risk phrases : R36/38- Irritating to eyes and skin.

R43- May cause sensitization by skin contact.

R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Safety phrases : S24- Avoid contact with skin.

S37- Wear suitable gloves.

Additional warning phrases : Contains epoxy constituents. See information supplied by the manufacturer.

**VOC** content (EU) : VOC (w/w): 0.01%

## OTHER INFORMATION

Full text of classifications referred to in sections 2 and

: R36/38- Irritating to eyes and skin.

R43- May cause sensitization by skin contact.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Full text of classifications referred to in sections 2 and : Xi - Irritant

N - Dangerous for the environment

<u>History</u>

Date of printing : 02.10.2008. Date of issue 02.10.2008.

Date of previous issue : No previous validation.

Indicates information that has changed from previously issued version.

#### Notice to reader

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to any use and processing.

: 02.10.2008. Date of issue **MSDS no.** : 114221 5/5